

Highlights

ECO mode



ECO mode allows you to lower your energy consumption and transmission power

Zero interference



DECT technology guarantees zero interference from any other transmitting product like other baby monitors, cordless phones and cell phones. Data encryption provides a secure and private connection, so you can be sure that you are the only one that can hear your baby

Reassuring crystal clear sound



Hear every tiny giggle, gurgle and hic-up with perfect clarity. DECT technology provides high quality, crystal clear sound so you can hear your baby anytime

Superior operating time



The small, rechargeable parent unit will give you the freedom of cordless roaming for up to 24 hours before re-charging is required

Digital temperature display




Your baby can't regulate its body temperature as well as you can and a slight change in temperature can make your baby restless. A special electronic temperature sensor will immediately alert you, through the digital display on the parent unit, if your baby's room becomes too hot or too cold

Adjustable sound sensitivity




Enables you to adjust the sound and volume levels, so you can hear every giggle, gurgle and hic-up

Rechargeable parent unit



With a range of 330m, belt clip and neck cord so you can be fully mobile in and around the home

Out of range/low power signals



The parent unit of the Philips AVENT baby monitor will alert when the power is low, or if you are out of range

LEDs light to signal noise



Lights are activated to indicate the level of sound in your baby's room. Even with the parent unit is muted, a sound alert will notify you when a set sound level is reached

Specifications

Technical specifications

Operating temperature range: 10 - 40 °C
Storage temperature range: 10 - 40 °C

Tuner/Reception/Transmission

Frequency band: DECT
Automatic channel selection
Number of channels: 120

Convenience

Auto out of range warning
Battery charging indication
Battery low indication

Sound-level lights
Volume control
Sensitivity control

Accessories

AC/DC adaptor
Batteries
Belt clip
DFU/ user manual
Quick start guide
Charging base for parent unit
Neck cord

Power

Charging time: 8 hour(s)
Power supply: 220 - 240 V
Power supply: 120 V (US)
Operating time on battery: 24 hour(s)

Logistic data

F-box dimensions (W x H x D): 220 x 156 x 94 mm

Development stages

Stages: Pregnancy, 0 - 6 months

