

# PHILIPS

## AVENT

Analogue Baby  
Monitor

1 parent unit



SCD485/01



## The essential connection to your baby

### Hear your baby day and night

Our new range of Avent Analogue baby monitors give you ultra clear sound with volume control, sound activated lights and link and low battery indicators, so you can be sure that when your baby needs you, you will know.

#### Ultra clear sound

- Adjustable channel settings to help eliminate interference
- Variable volume control to hear every giggle or murmur

#### Stay reassured whilst on the move

- Stylish, handheld unit with a range of up to 150m
- Sound activated lights to keep you aware of baby's sounds
- Simple lights and sounds to let you know you are connected
- Easy link extra parent units for ultimate mobility

# Highlights

## Adjustable channel settings



40Mhz analogue technology offers adjustable channel settings to help to eliminate interference for a clearer connection to your baby

## Volume control with mute




Adjust the volume of your parent unit so you can hear every tiny giggle, gurgle or hic up. You can also monitor without sound by using the mute function. The sound activated lights will let you know when your baby needs you.

## Operating range




Stay connected with your baby, even when you are far from the nursery with this stylish, hand held battery operated parent unit with a range up to 150m

## Sound activated lights



Lights are activated when your baby makes a sound, so even with the volume turned down low or on mute, you will know when your baby needs you

## Link & low battery indicators



A necessity for your reassurance, light and sound indicators will let you know when you are linked and in range, and will remind you when the battery of your parent unit is low, so you won't lose power unexpectedly.

## Easy link extra parent units



Link more parent units in 2 easy steps, to give you extra mobility in and around your home. Extra parent units sold separately (SCD484)

# Specifications

## Power

Operating time on battery: 6 hour(s)  
Power supply: 110 - 240 V

## Tuner/Reception/Transmission

Frequency band: 40Mhz Analogue  
Number of channels: 2

## Accessories

AC/DC adaptor  
DFU/ user manual

## Convenience

Battery low indication  
Auto out-of-range warning  
Volume control  
Sound-level lights

## Technical specifications

Operating temperature range: 10 - 40 °C  
Storage temperature range: 10 - 40 °C

## Logistic data

F-box dimensions (W x H x D): 200 x 100 x 300 mm

## Development stages

Stage: 0 - 6 months

