

PHILIPS

AVENT

DECT Baby Monitor

SCD496/00



Guaranteed zero interference

With DECT digital technology

This digital technology provides a secured, private connection, because you want to be the only one listening to your baby. Automatically chooses an unused channel and switches as it detects another device using the same channel.

Complete peace of mind

- Indicates a continuous connection between the two units
- Uses lights to indicate if the baby makes a noise
- Guarantees zero interference from any other device

Soothing words

- Allows you to talk to the baby

Mobility in and around the house

- Small, mobile parent unit to freely roam around the house
- 300-m range ensures secure reception in and around the house
- The belt clip provides hands-free convenience and mobility

Highlights

Guaranteed zero interference

Guarantees zero interference from any other device (other baby monitors, cordless phones and mobile phones). Provides a secure and private connection using data encryption. You will be the only one who can hear your baby and you will only hear your own baby.

Digital signal confirmation

Indicates a continuous connection between the baby and the parent unit with visible and audible link indicators.

Sound level lights

Uses lights to indicate if the baby makes a noise, even with volume off.

Small, mobile parent unit

Allows you to freely roam around the house due to the small size, but still hear when your baby needs you.

Belt clip

The belt clip provides hands-free convenience and mobility.

With a range of up to 300 m

With a range of up to 300 m you are assured of a secure reception in and around the house.

Parent talkback

Allows you to hear the baby and talk to the baby.

Specifications

Development stages

Stage: 0–6 months, 6–12 months

Power

Power supply: 230–240 V

Tuner/Reception/Transmission

Automatic channel selection

Number of channels: 120

Convenience

Power on indication

Battery low indication

Auto out-of-range warning

Volume control

Sound-level lights

System check: Battery check light, System check alarm, System check light

Technical specifications

Operating temperature range: 0–40 °C

Tuner/Reception/Transmission

Frequency band: DECT

Accessories

Belt clip

Quick start guide

Accessories

AC/DC adapter: 2 x 9 VDC, 300 mA

DFU/user manual: Dutch, English, Finnish, French, German, Greek, Italian, Portuguese, Spanish, Swedish, Norwegian, Danish

Logistic data

EAN F-box

Technical specifications

Storage temperature range: -20–+60 °C

Logistic data

F-box dimensions (W x H x D): 220 x 187 x 94 mm

