



# Guaranteed zero interference

With DECT digital technology

This digital technology provides a secured, private connection, because you want to be the only one listening to your baby. Automatically chooses an unused channel and switches as it detects another device using the same channel. .

## **Complete peace of mind**

- Indicates a continuous connection between the two units
- Uses lights to indicate if the baby makes noise
- Guarantees zero interference from any other device

## **Soothing words**

- Provides the ability to allow you to talk to the baby

## **Mobility in and around the house**

- Small, mobile parent unit to freely roam around the house
- 300 m range ensures secure reception in and around the house
- The belt clip provides hands-free convenience and mobility

# Highlights

## Guaranteed zero interference



Guarantees zero interference from any other device (other baby monitors, cordless phones and cell phones). Provides a secure and private connection using data encryption. You will be the only one who can hear your baby and you only hear your own baby.

## Digital signal confirmation



Indicates a continuous connection between the baby and the parent unit with visible and audible link indicators.

## Sound level lights

Uses lights to indicate if the baby makes noise, even with volume off.

## Small, mobile parent unit



Allows you to freely roam around the house due to the small size, but still hear when your baby needs you.

## Belt clip



The belt clip provides hands-free convenience and mobility.

## With a range up to 300 m

With a range up to 300 m you are ensured a secure reception in and around the house.

## Parent talkback

Provides the ability to allow you to hear the baby and talk to the baby.

# Specifications

## Development stages

- Stage: 0 - 6 months, 6 - 12 months

## Power

- Power supply: 230-240 V

## Tuner/Reception/Transmission

- Automatic channel selection
- Number of channels: 120

## Convenience

- Auto out-of-range warning
- Power on indication
- Battery low indication
- Volume control
- Sound-level lights
- System check: Battery check light, System check alarm, System check light

## Technical specifications

- Operating temperature range: 0 .. 40 °C

## Tuner/Reception/Transmission

- Frequency band: DECT

## Accessories

- Belt clip
- Quick start guide

## Accessories

- AC/DC adaptor: 2x 9VDC, 300mA
- DFU/ user manual: Dutch, English, Finnish, French, German, Greek, Italian, Portuguese, Spanish, Swedish, Norwegian, Danish

## Logistic data

- EAN F-box

## Technical specifications

- Storage temperature range: -20 .. +60 °C

## Logistic data

- F-box dimensions (W x H x D): 220x187x94 mm



Issue date 2021-02-15

Version: 7.0.1

© 2021 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)