


Analogue baby monitor

SCD450/05



Two parent units

Both parents can constantly stay in touch with the baby. Two parent units for freedom of movement without losing contact with your baby. With small, mobile and rechargeable parent unit, belt clip and digital signal confirmation.

Convenience for you and your child

· Adjust volume and sound sensitivity to suit any situation

Complete peace of mind

- Lights up when batteries need recharging or replacing
- Indicates a continuous connection between the two units
- Minimum interference from other monitors
- Uses lights to indicate if the baby makes a noise

Ultimate mobility in and around the house

- Belt clip and neck cord for hands-free convenience
- $\cdot\,$ Ensures secure reception in and around the house
- Small, mobile parent unit to freely roam around the house
- Now both parents can monitor baby
- Rechargeable, cordless monitoring anywhere

Soothing words

• Soft glow comforts baby if she wakes

Analogue baby monitor

Highlights

16 channels

Minimum interference from other monitors.

Sound level lights

Uses lights to indicate if the baby makes a noise, even with volume off.

Digital signal confirmation



Indicates a continuous connection between the baby and the parent unit with visible and audible link indicators.

Low power indicator

Lights up when batteries need recharging or replacing.

Two parent units

Now both parents can monitor baby.

Small, mobile parent unit



Allows you to freely roam around the house due to the small size, but still hear when your baby needs you.

Up to 200 m range

Ensures secure reception in and around the house.

Cordless parent unit

Rechargeable, cordless monitoring anywhere.

Belt clip and neck cord

The belt clip and neck cord provide hands-free convenience and mobility: clip the parent unit to your belt or wear it around your neck.

Volume control and adjustable sound sensitivity

Adjust volume and sound sensitivity to suit any situation

Soothing night-light

Soft glow comforts baby if she wakes

SCD450/05

Specifications

Power

Operating time on battery: 12 hour(s)

Tuner/Reception/Transmission

Maximum range: 200 m Number of channels: 16

Convenience

Auto out-of-range warning Power on indication Battery low indication Battery charging indication Volume control Sound-level lights System check: Battery check light, System check alarm, System check light

Tuner/Reception/Transmission

Frequency band: 40.675 - 40.690 MHz Pilot tone: Digital

Accessories

Belt clip: Belt clip on both parent units User manual Batteries: 3 x AAA rech. batt pack, small parent unit (incl.) Charger: Charging base for parent unit Quick start guide

Accessories

Docking station: For small parent unit AC/DC adapter: 3 x 9 V DC 200 mA

© 2022 Koninklijke Philips N.V. All Rights reserved. Issue date 2022-01-13 Version: 5.2.1



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com