

Philips Avent
DECT baby monitor



SCD496/00

Guaranteed zero interference

With DECT digital technology

This digital technology provides a secured, private connection, because you want to be the only one listening to your baby. Automatically chooses an unused channel and switches as it detects another device using the same channel. .

Complete peace of mind

- Indicates a continuous connection between the two units
- Uses lights to indicate if the baby makes noise
- Guarantees zero interference from any other device

Soothing words

- Provides the ability to allow you to talk to the baby

Mobility in and around the house

- Small, mobile parent unit to freely roam around the house
- 300 m range ensures secure reception in and around the house
- The belt clip provides hands-free convenience and mobility

PHILIPS
AVENT

Highlights

Guaranteed zero interference



Guarantees zero interference from any other device (other baby monitors, cordless phones and cell phones). Provides a secure and private connection using data encryption. You will be the only one who can hear your baby and you only hear your own baby.

Digital signal confirmation



Indicates a continuous connection between the baby and the parent unit with visible and audible link indicators.

Sound level lights

Uses lights to indicate if the baby makes noise, even with volume off.

Small, mobile parent unit



Allows you to freely roam around the house due to the small size, but still hear when your baby needs you.

Belt clip



The belt clip provides hands-free convenience and mobility.

With a range up to 300 m

With a range up to 300 m you are ensured a secure reception in and around the house.

Parent talkback

Provides the ability to allow you to hear the baby and talk to the baby.

Specifications

Development stages

- Stage: 0 - 6 months, 6 - 12 months

Power

- Power supply: 230-240 V

Tuner/Reception/Transmission

- Automatic channel selection
- Number of channels: 120

Convenience

- Power on indication
- Auto out-of-range warning
- Battery low indication
- Volume control
- Sound-level lights
- System check: Battery check light, System check alarm, System check light

Technical specifications

- Operating temperature range: 0 .. 40 °C

Tuner/Reception/Transmission

- Frequency band: DECT

Accessories

- Belt clip
- Quick start guide

Accessories

- AC/DC adaptor: 2x 9VDC, 300mA
- DFU/ user manual: Dutch, English, Finnish, French, German, Greek, Italian, Portuguese, Spanish, Swedish, Norwegian, Danish

Logistic data

- EAN F-box

Technical specifications

- Storage temperature range: -20 .. +60 °C

Logistic data

- F-box dimensions (W x H x D): 220x187x94 mm

