



Guaranteed zero interference

With DECT digital technology

This digital technology provides a secured, private connection, because you want to be the only one listening to your baby. Automatically chooses an unused channel and switches as it detects another device using the same channel. .

Complete peace of mind

- Indicates a continuous connection between the two units
- Uses lights to indicate if the baby makes noise
- Guarantees zero interference from any other device

Mobility in and around the house

- Small, mobile parent unit to freely roam around the house
- Rechargeable parent unit for minimum 24 hours of monitoring
- 300 m range ensures secure reception in and around the house
- The belt clip provides hands-free convenience and mobility

Soothing sights and words

- Provides the ability to allow you to talk to the baby
- Comforts the baby in the dark with soothing stars

Highlights

Guaranteed zero interference



Guarantees zero interference from any other device (other baby monitors, cordless phones and cell phones). Provides a secure and private connection using data encryption. You will be the only one who can hear your baby and you only hear your own baby.

Digital signal confirmation



Indicates a continuous connection between the baby and the parent unit with visible and audible link indicators.

Sound level lights

Uses lights to indicate if the baby makes noise, even with volume off.

Rechargeable parent unit



The rechargeable parent unit gives you a minimum of 24 hours of cordless monitoring with a range of up to 300 m (900 feet).

Small, mobile parent unit



Allows you to freely roam around the house due to the small size, but still hear when your baby needs you.

Belt clip



The belt clip provides hands-free convenience and mobility.

With a range up to 300 m

With a range up to 300 m you are ensured a secure reception in and around the house.

Starry night-light

Nightlight with soothing stars to comfort your baby.

Parent talkback

Provides the ability to allow you to hear the baby and talk to the baby.

Specifications

Development stages

- Stage: 0 - 6 months, 6 - 12 months

Power

- Operating time on battery: 24 hour(s)
- Power supply: 230-240 V
- Charging time: 8 hour(s)

Tuner/Reception/Transmission

- Automatic channel selection
- Number of channels: 120

Convenience

- Battery low indication
- Auto out-of-range warning
- Power on indication
- Battery charging indication
- Night light
- Volume control
- Sound-level lights
- System check: Battery check light, System check alarm, System check light

Technical specifications

- Operating temperature range: 0 .. 40 °C

Power

- Rechargeable

Tuner/Reception/Transmission

- Frequency band: DECT

Accessories

- Belt clip
- Batteries: 2 x AAA NiMH rechargeable
- Quick start guide

Accessories

- AC/DC adaptor: 2x 9VDC, 300mA
- DFU/ user manual: Dutch, English, Finnish, French, German, Greek, Italian, Portuguese, Spanish, Swedish, Norwegian, Danish

Logistic data

- EAN F-box

Technical specifications

- Storage temperature range: -20 .. +60 °C

Logistic data

- F-box dimensions (W x H x D): 220x187x94 mm



Issue date 2021-02-15

Version: 7.0.1

© 2021 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com