

PHILIPS

DECT baby monitor

SCD487/00



Guaranteed zero interference

With DECT digital technology

Enjoy complete reassurance. With DECT digital technology, you are guaranteed a secure, zero interference connection between you and your baby. Soothing your baby is simple with the glowing, starry night-light on the baby unit.

Complete peace of mind

- Indicates a continuous connection between the two units
- Uses lights to indicate if the baby makes noise
- Provides the ability to allow you to talk back to the baby
- Guarantees zero interference from any other device

Ultimate mobility in and around the house

- Small, mobile parent unit to freely roam around the house
- 300 m range ensures secure reception in and around the house

Soothing words

- Comforts the baby in the dark with soothing stars

Highlights

Guaranteed zero interference

Guarantees zero interference from any other device (other baby monitors, cordless phones and cell phones). Provides a secure and private connection using data encryption. You will be the only one who can hear your baby and you only hear your own baby.

Sound level lights

Uses lights to indicate if the baby makes noise, even with volume off.

Digital signal confirmation

Indicates a continuous connection between the baby and the parent unit with visible and audible link indicators.

Small, mobile parent unit

Allows you to freely roam around the house due to the small size, but still hear when your baby needs you.

With a range up to 300 m

With a range up to 300 m you are ensured a secure reception in and around the house.

Talk-back

Provides the ability to allow you to talk back to the baby.

Starry night-light

Nightlight with soothing stars to comfort your baby.

Specifications

Power

Power supply: AC/DC Adapter

Tuner/Reception/Transmission

Automatic channel selection

Number of channels: 120

Convenience

Auto out-of-range warning

Power on indication

Battery low indication

Volume control

Night light

Sound-level lights

System check: Battery check light, System check alarm, System check light

Technical specifications

Operating temperature range: 0 .. 40 °C

Power

Rechargeable: No

Tuner/Reception/Transmission

Frequency band: DECT

Accessories

Belt clip

Accessories

AC/DC adaptor: 9 V DC, 300 mA; 3 V 6 DE, 200 mA

DFU/ user manual: Danish/Norwegian, Dutch, English, Finnish, French, German, Greek, Italian, Portuguese, Spanish, Swedish

Technical specifications

Storage temperature range: -20 .. +60 °C

