

PHILIPS

 Product Picture

AVENT

DECT baby monitor

SCD497/00

Guaranteed zero interference

With DECT digital technology

This digital technology provides a secured, private connection, because you want to be the only one listening to your baby. Automatically chooses an unused channel and switches as it detects another device using the same channel. .

Complete peace of mind

- Indicates a continuous connection between the two units
- Uses lights to indicate if the baby makes noise

Mobility in and around the house

- Small, mobile parent unit to freely roam around the house
- Rechargeable parent unit for minimum 24 hours of monitoring
- 300 m range ensures secure reception in and around the house
- The belt clip provides hands-free convenience and mobility

Soothing sights and words

- Provides the ability to allow you to talk to the baby
- Comforts the baby in the dark with soothing stars

Highlights

Digital signal confirmation

Indicates a continuous connection between the baby and the parent unit with visible and audible link indicators.

Sound level lights

Uses lights to indicate if the baby makes noise, even with volume off.

Rechargeable parent unit

The rechargeable parent unit gives you a minimum of 24 hours of cordless monitoring with a range of up to 300 m (900 feet).

Small, mobile parent unit

Allows you to freely roam around the house due to the small size, but still hear when your baby needs you.

Belt clip

The belt clip provides hands-free convenience and mobility.

With a range up to 300 m

With a range up to 300 m you are ensured a secure reception in and around the house.

Starry night-light

Nightlight with soothing stars to comfort your baby.

Parent talkback

Provides the ability to allow you to hear the baby and talk to the baby.

Specifications

Development stages

Stage: 0 - 6 months, 6 - 12 months

Power

Operating time on battery: 24 hour(s)

Power supply: 230-240 V

Charging time: 8 hour(s)

Tuner/Reception/Transmission

Automatic channel selection

Number of channels: 120

Convenience

Power on indication

Battery low indication

Auto out-of-range warning

Battery charging indication

Night light

Volume control

Sound-level lights

System check: Battery check light, System check alarm, System check light

Technical specifications

Operating temperature range: 0 .. 40 °C

Power

Rechargeable

Tuner/Reception/Transmission

Frequency band: DECT

Accessories

Belt clip

Batteries: 2 x AAA NiMH rechargeable

Quick start guide

Accessories

AC/DC adaptor: 2x 9VDC, 300mA

DFU/ user manual: Dutch, English, Finnish, French, German, Greek, Italian, Portuguese, Spanish, Swedish, Norwegian, Danish

Logistic data

EAN F-box

Technical specifications

Storage temperature range: -20 .. +60 °C

Logistic data

F-box dimensions (W x H x D):

220x187x94 mm

