Garment Care range 2002

PROVAPOR AZUR
SUPERVAPOR
AZUR 4000
ELANCE PLUS CASSETTE
AZUR EXCEL PLUS
ELANCE 3000
MISTRAL 2000
COMFORT

PHILIPS
Let's make things better

GC 6026 GC 6024 GC 6022 GC 6020 GC 6019

PROVAPOR AZUR

	Provapor GC 6026	Provapor GC 6024	Provapor GC 6022	Provapor GC 6020	Provapor GC 6019
Technical data					
Power (W)	Iron 800 Boiler 1200	Iron 800 Boiler 1200	Iron 800 Boiler 1200	Iron 800 Boiler 1200	Iron 800 Boiler 1200
Voltage (V)	220-240	220-240	220-240	220-240	220-240
Dimensions (mm)					
Iron	370x245x370	370x245x370	370x245x370	370x245x370v	370x245x370
F-box	430x300x215	430x300x215	430x300x215	430x300x215	430x300x215
A-box	na	na	na	na	na
Pieces per unit	1	1	1	1	1
Weight iron (gr)	3850	3850	3850	3850	3850
Pallet capacity	54/60	54/60	54/60	54/60	54/60
Features					
Soleplate	Careeza™	Careeza™	Careeza™	Careeza™	Optinox
Steam					
- Variable steam	●	●	–	–	–
- Steam output (gr)	90	70	70	70	60
- Positions (incl. 0 pos)	stepless/cont.	stepless/cont.	na	na	na
Shot of steam (gr)	100	–	–	–	–
Vertical shot of steam	perm. vert. steam	perm. vert. steam	perm. vert. steam	perm. vert. steam	perm. vert. steam
Water					
Contents (ml)	1000	1000	1000	1000	1000
Drip stop	na	na	na	na	na
Detachable Tank	–	–	–	–	–
Anti Calc					
Anti Calc Formula	●	–	–	–	–
Others					
Cord length (m)	1.8	1.8	1.8	1.8	1.8
Cordwinder	–	–	–	–	–
Pilot lamp	●	●	●	●	●
Swivel (degrees)	360	360	360	360	360
Soleplate cover	–	–	–	–	–
Def. tray	–	–	–	–	–
Boiler material	inox	inox	inox	inox	inox
Pressure	3.5 bar	3 bar	2.5 bar	2.5 bar	2.5 bar
Boiler ready light	●	●	–	–	–
Boiler empty light	–	–	–	–	–
De-pressurize function	●	●	●	●	●

GC 6048 GC 6046 GC 6044 GC 6040

SUPERVAPOR

	Supervapor GC 6048	Supervapor GC 6046	Supervapor GC 6044	Supervapor GC 6040
Technical data				
Power (W)	Iron 700 Boiler 1000	Iron 700 Boiler 1000	Iron 700 Boiler 1000	Iron 700 Boiler 1600
Voltage (V)	220-240	220-240	220-240	220-240
Dimensions (mm)				
Iron	175x300x375	175x300x375	175x300x375	175x300x375
F-box	430x300x215	430x300x215	430x300x215	430x300x215
A-box	n.a.	n.a.	n.a.	n.a.
Pieces per unit	1	1	1	1
Weight iron (gr)	4800	4800	4800	4800
Pallet capacity	54/60	54/60	54/60	54/60
Features				
Soleplate	Aluminium	Aluminium	Aluminium	Aluminium
Steam				
- Variable steam	●	●	●	–
- Steam output (gr)	90	80	60	60
- Positions (incl. 0 pos)	6	6	6	–
Jet of steam (gr)	80	80	–	–
Vertical shot of steam	perm. vert. steam	perm. vert. steam	perm. vert. steam	perm. vert. steam
Water				
Contents (ml)	1500	1500	1500	1500
Heating up (min.)	9.5	9.5	9.5	9.5
Drip stop	na	na	na	na
Detachable Tank	–	–	–	–
Anti Calc				
Anti Calc Formula	●	–	–	–
Others				
Button groove	●	●	–	–
Cord length (m)	1.8	1.8	1.8	1.8
Cordwinder	storage lock	storage lock	storage lock	storage lock
Pilot lamp	●	●	●	●
Soft touch	cork	cork	cork	cork
Swivel (degrees)	180	180	180	180
Soleplate cover	–	–	–	–
Boiler material	inox	inox	inox	nox
Pressure	3.5 bar	3 bar	2.5 bar	2 bar
Boiler ready light	●	●	●	●
Boiler empty light	–	–	–	–
De-pressurize function	●	●	●	●
Removable tray	●	●	●	●
Manometer	●	–	–	–

GC 4043 GC 4038 GC 4035 GC 4033 GC 4028 GC 4023 GC 4020 GC 4018 GC 4015 GC 4013 GC 4005

AZUR 4000

	GC4043	GC4038	GC4035	GC4033	GC4028	GC4023	GC4020	GC4018	GC4015	GC4013	GC4005
Technical data											
Power (W)	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Dimensions (mm)											
Iron	309x134x167	303x120x151	303x120x151	303x120x151	309x134x167	303x120x151	303x120x151	303x120x151	303x120x151	303x120x151	303x120x151
F-box	328x143x181	328x129x163	328x129x163	328x129x163	328x143x181	328x129x163	328x129x163	328x129x163	328x129x163	328x129x163	328x129x163
A-box	460x345x392	419x345x357	419x345x357	419x345x357	460x345x392	419x345x357	419x345x357	419x345x357	419x345x357	419x345x357	419x345x357
Pieces per unit	6	6	6	6	6	6	6	6	6	6	6
Weight product (gr)	1650	1470	1470	1470	1650	1470	1470	1470	1470	1470	1470
Pallet capacity	150	216	216	216	150	216	216	216	216	216	216
Features											
Soleplate	Careeza™	Careeza™	Careeza™	Careeza™	Careeza™	Careeza™	Careeza™	Careeza™	Careeza™	Careeza™	Careeza™
Steam											
Variable steam											
- Steam output (gr)	0-40	0-40	0-40	0-40	0-40	0-40	0-40	0-40	0-40	0-40	0-40
- Positions (incl. 0 pos)	7	7	7	7	7	7	7	7	7	7	7
Shot of steam (gr)	95	95	80	95	95	95	80	95	80	95	80
Vertical shot of steam	●	●	●	●	●	●	●	●	●	●	–
Turbo steam	–	–	–	–	–	–	–	–	–	–	–
Water											
Contents (ml)	350	350	350	350	350	350	350	350	350	350	350
Visible	●	●	●	●	●	●	●	●	●	●	●
Spray	●	●	●	●	●	●	●	●	●	●	●
Drip stop	●	●	●	●	●	●	●	●	●	●	●
Detachable Tank	–	–	–	–	–	–	–	–	–	–	–
Anti Calc											
Auto Anti Calc Formula	●	●	●	●	●	●	●	●	●	–	–
Self/Calc-Clean	●	●	●	●	●	●	●	●	●	●	●
Others											
Cord length (m)	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
Cordwinder	●	●	●	●	●	●	●	●	●	●	●
Pilot lamp	●	●	●	●	●	●	●	●	●	●	●
Soft touch	●	●	●	–	–	●	●	–	–	–	–
Auto Shut Off	●	●	●	●	–	–	–	–	–	–	–
Swivel (degrees)	360(ball)	360(ball)	360(ball)	360(ball)	360(ball)	360(ball)	360(ball)	360(ball)	360(ball)	360(ball)	360(ball)
Soleplate cover	●	–	–	–	●	–	–	–	–	–	–
Carry case	–	–	–	–	–	–	–	–	–	–	–

HI 478 HI 468 HI 458

ELANCE PLUS CASSETTE

	Cassette HI478	Cassette HI468	Cassette HI458
Technical data			
Power (W)	1800	1800	1800
Voltage (V)	220-240	220-240	220-240
Dimensions (mm)			
Iron	288x117x140	288x117x140	288x117x140
F-box	318x129x157	318x129x157	318x129x157
A-box	416x336x359	416x336x359	416x336x359
Pieces per unit	6	6	6
Weight iron (gr)	1340	1340	1340
Pallet capacity	216	216	216
Features			
Soleplate	Optinox	Optinox	Optinox
Steam			
Variable steam			
- Steam output (gr)	0-25	0-25	0-25
- Positions (incl. 0 pos)	5	5	5
Shot of steam (gr)	50	50	50
Vertical shot of steam	●	●	●
Extra steam (gr)	–	–	–
Water			
Contents (ml)	240	240	240
Visible	●	●	●
Spray	●	●	●
Drip stop	●	●	●
Detachable Tank	●	●	●
Anti Calc			
Auto Anti Calc Formula	●	●	–
Self/Calc-Clean	●	●	●
Others			
Cord length (m)	2.4	2.4	2.4
Cordwinder	●	●	●
Pilot lamp	●	●	●
Soft touch	–	–	–
Auto Shut Off	●	–	–
Swivel (degrees)	180	180	180
Soleplate cover	–	–	–
Carry case	–	–	–

International range (note: not all models will be available in all countries)

HI 838 | HI 566 | HI 565 | HI 556 | HI 555

AZUR EXCEL PLUS

	Aquazur HI838	Cord/Cordless HI566	Cord/Cordless HI565	Cord/Cordless HI556	Cord/Cordless HI555
Technical data					
Power (W)	1900	1900	1900	1900	1900
Voltage (V)	220-240	220-240	220-240	220-240	220-240
Dimensions (mm)					
Iron	280x114x150	320x256x138	320x256x138	320x256x138	320x256x138
Stand	320x185x65	–	–	–	–
F-box	340x200x210	358x324x174	333x273x149	358x324x174	333x273x149
A-box	625x360x245	545x348x370	615x295x345	545x348x370	615x295x345
Pieces per unit	3	3	4	3	4
Weight iron (gr)	1150	1990	1990	1990	1990
Weight case (gr)	–	710	–	710	–
Weight stand (gr)	1220	–	–	–	–
Pallet capacity	144	90	144	90	144
Features					
Soleplate	Anodilium	Anodilium	Anodilium	Anodilium	Anodilium
Steam					
Variable steam					
- Steam output (gr)	0-35	0-30	0-30	0-30	0-30
- Positions (incl. 0 pos)	4	7	7	7	7
Shot of steam (gr)	65	60	60	60	60
Vertical shot of steam	●	●	●	●	●
Extra steam (gr)	–	40	40	–	–
Water					
Contents (ml)	800	250	250	250	250
Visible	●	●	●	●	●
Spray	●	●	●	●	●
Drip stop	●	●	●	●	●
Detachable Tank	–	–	–	–	–
Anti Calc					
Anti Calc Formula	● (Cassette)	●	●	●	●
Self/Calc-Clean	●	●	●	●	●
Others					
Cord length (m)	1.7+1.7	2.4	2.4	2.4	2.4
Cordwinder		●	●	●	●
Pilot lamp	●	●	●	●	●
Soft touch	●	●	●	–	–
Auto Shut Off	–	●	●	–	–
Swivel (degrees)	360 (ball)	180	180	180	180
Soleplate cover	–	–	–	–	–
Carry case	–	●	–	●	–

GC 3035 | GC 3030 | GC 3025 | GC 3020 | GC 3016 | GC 3015 | GC 3010 | GC 3006 | GC 3005

ELANCE 3000

	GC 3035	GC 3030	GC 3025	GC 3020	GC 3016	GC 3015	GC 3010	GC 3006	GC 3005
Technical data									
Power (W)	1900	1900	1900	1800	1800	1800	1800	1800	1800
Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Dimensions (mm)									
Iron	285x120x145	285x120x145	285x120x145	285x120x145	285x120x145	285x120x145	285x120x145	285x120x145	285x120x145
F-box	318x130x165	318x130x165	318x130x165	318x130x165	318x130x165	318x130x165	318x130x165	318x130x165	318x130x165
A-box	410x328x346	410x328x346	410x328x346	410x328x346	410x328x346	410x328x346	410x328x346	410x328x346	410x328x346
Pieces per unit	6	6	6	6	6	6	6	6	6
Weight iron (gr)	1300	1300	1300	1300	1300	1300	1300	1300	1300
Pallet capacity	216	216	216	216	216	216	216	216	216
Features									
Soleplate	Careeza	Careeza	Careeza	Careeza	Careeza	Careeza	Careeza	Careeza	Careeza
Steam									
- Variable steam									
- Steam output (gr)	0-35	0-35	0-35	0-30	0-30	0-30	0-30	0-30	0-30
- Steam positions	5	5	5	5	5	5	5	5	5
- Shot of steam (gr/min)	85	85	85	75	75	75	75	75	75
- Vertical shot of st. (gr/min)	●	●	●	●	●	●	●	–	–
- Turbo steam	–	–	–	–	–	–	–	–	–
Water									
- Tank Cap. (ml)	300	300	300	300	300	300	300	300	300
- Visible	●	●	●	●	●	●	●	●	●
- Spray	●	●	●	●	●	●	●	●	●
- Drip stop	●	●	●	●	–	●	–	–	–
- Det tank	–	–	–	–	–	–	–	–	–
Anti Calc									
- Auto Anti-Calc	●	●	●	●	●	–	–	–	–
- Calc Clean	●	●	●	●	●	●	●	●	●
Others									
Cord length (m)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Cordwinder	●	●	●	●	●	●	●	●	●
Pilot lamp	●	●	●	●	●	●	●	●	●
Soft touch	●	●	–	–	–	–	–	–	–
Auto Shut Off	●	–	–	–	–	–	–	–	–
Ball swivel	360 (ball)	360 (ball)	360 (ball)	360 (ball)	360 (ball)	360 (ball)	360 (ball)	360 (ball)	360 (ball)
Anti-slip	●	●	●	–	–	–	–	–	–
Soleplate cover	–	–	–	–	–	–	–	–	–
Carry case	–	–	–	–	–	–	–	–	–

GC 2030 | GC 2025 | GC 2020 | GC 2015 | GC 2010 | GC 2005

MISTRAL 2000

	GC 2030	GC 2025	GC 2020	GC 2015/16[1]	GC 2010	GC 2005/06[2]
Technical data						
Power (W)	1600	1600	1600	1600	1600	1600
Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240
Dimensions (mm)						
Iron	277x115x138	277x115x138	277x115x138	277x115x138	277x115x138	277x115x138
F-box	298x128x156	298x128x156	298x128x156	298x128x156	298x128x156	298x128x156
A-box	416x317x336	416x317x336	416x317x336	416x317x336	416x317x336	416x317x336
Pieces per unit	6	6	6	6	6	6
Weight iron (gr)	1120	1100	1100	1100	1100	1100
Pallet capacity	288	288	288	288	288	288
Features						
Soleplate	Ceralon	Ceralon	Ceralon	Ceralon	Ceralon	Ceralon
Steam						
Variable steam						
- Steam output (gr)	0-25	0-25	0-25	0-25	0-25	0-25
- Positions (incl. 0 pos)	3	3	3	3	3	3
Shot of steam (gr)	45	45	–	–	45	45
Vertical shot of steam	●	●	–	●	–	–
Extra steam (gr)	–	–	30	–	–	30
Water						
Contents (ml)	200	200	200	200	200	200
Visible	●	●	●	●	●	●
Spray	●	●	●	●	●	●
Drip stop	●	●	●	●	–	–
Detachable Tank	–	–	–	–	–	–
Anti Calc						
Anti Calc Formula	–	–	–	–	–	–
Calc Clean	●	●	●	●	●	●
Others						
Cord length (m)	1.9	1.9	1.9	1.9	1.9	1.9
Cordwinder	●	●	●	●	●	●
Pilot lamp	●	●	●	●	●	●
Soft touch	–	–	–	–	–	–
Auto Shut Off	●	–	–	–	–	–
Swivel (degrees)	180	180	180	180	180	180
Soleplate cover	–	–	–	–	–	–
Carry case	–	–	–	–	–	–

[1] GC 2015 peach
GC 2016 blue

[2] GC 2005 green
GC 2006 yellow

HI 295/296 | HI 285/286 | HI 275/276 | HI 265/266 | HI 255/256 | HI 225/226 | HI 215/216 | HI 205/206

COMFORT

	Cassette HI 295 / 296	Cassette HI 285 / 286	Cassette HI 275 / 276	Cassette HI 265 / 266	Cassette HI 255 / 256	Classical HI 225 / 226	Classical HI 215 / 216	Classical HI 205 / 206
Technical data								
Power (W)	1200	1200	1200	1200	1200	1200	1200	1200
Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Dimensions (mm)								
Iron	256x110x140	256x110x140	256x110x140	256x110x140	256x110x140	253x110x131	253x110x131	253x110x131
F-box	284x114x146	284x114x146	284x114x146	284x114x146	284x114x146	272x112x140	272x112x140	272x112x140
A-box	493x292x306	493x292x306	493x292x306	493x292x306	493x292x306	485x280x294	485x280x294	485x280x294
Pieces per unit	8	8	8	8	8	8	8	8
Weight iron (gr)	1100	1100	1100	1100	1100	1100	1100	1100
Pallet capacity	288	288	288	288	288	336	336	336
Features								
Soleplate	Aluminium/Ceralon	Aluminium/Ceralon	Aluminium/Ceralon	Aluminium/Ceralon	Aluminium/Ceralon	Aluminium/Ceralon	Aluminium/Ceralon	Aluminium/Ceralon
Steam								
Variable steam								
- Steam output (gr)	0-15	0-15	0-15	0-15	0-15	0-15	0-15	0-15
- Positions (incl. 0 pos)	3	3	3	3	3	3	3	3
Shot of steam (gr)	–	30	–	–	–	–	–	–
Vertical shot of steam	–	–	–	–	–	–	–	–
Extra steam (gr)	25	–	25	–	–	25	–	–
Water								
Contents (ml)	120	120	120	120	120	170	170	170
Visible	●	●	●	●	●	●	●	●
Spray	●	●	●	●	–	●	●	–
Drip stop	–	–	–	–	–	–	–	–
Detachable Tank	●	●	●	●	●	–	–	–
Anti Calc								
Anti Calc Formula	–	–	–	–	–	–	–	–
Calc Clean	●	●	●	●	●	●	●	●
Others								
Cord length (m)	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
Cordwinder	●	●	●	●	●	●	●	●
Pilot lamp	●	●	●	●	●	●	●	●
Soft touch	–	–	–	–	–	–	–	–
Auto Shut Off	●	–	–	–	–	–	–	–
Swivel (degrees)	180	180	180	180	180	180	180	180
Soleplate cover	–	–	–	–	–	–	–	–
Carry case	–	–	–	–	–	–	–	–