

**PHILIPS**

*EarlyVue*

VS30 vital signs monitor



# Philips EarlyVue VS30 ordering guide



EarlyVue VS30\*  
863359

Option

Measurement parameter features and options

<b>Blood pressure</b>		
Philips noninvasive blood pressure (including STAT and QuickNBP)	•	
NBP auto intervals (including 5 programmable intervals)	•	
<b>Respiration</b>		
Respiration rate (RR) - manual	•	
Airway respiration (awRR)	•	E01
Masimo rainbow Acoustic Respiration - RRa (requires SP5)	o	R21
Masimo rainbow Respiration from pleth - RRp (requires SP5)	o	R31
<b>Temperature (requires 1)</b>		
Predictive temperature	o	T01
Ear temperature - cable for Riester thermometer only (must order Riester thermometer 989803220891 separately)	o	T02
Temporal (arterial) temperature	o	T03
Manual temperature - no probe, temporal cradle only	o	T04
<b>SpO<sub>2</sub> (requires 1)</b>		
Philips FAST SpO <sub>2</sub>	o	SP1
Masimo rainbow SET™ SpO <sub>2</sub>	o	SP5
Masimo rainbow Total Hemoglobin - SpHb (requires SP5)	o	R01
<b>Capnography</b>		
Microstream etCO <sub>2</sub>	o	E01

• Standard o Optional

\* EarlyVue VS30, 863359, is not for sale in North America.

## Software features and options

### EarlyVue VS30 Option 863359

Auto-set alarm limits - customized to patient	•	
HL7 data export	•	
Patient trending: tabular and graphical formats	2	
Maximum number of waveforms displayed	3	
Four monitoring modes Spotcheck, interval, continuous, no alarm	4	
QuickCapture up to 35 customizable observation/assessment fields	•	
QuickAlerts Basic - Single parameter alarm limits with customizable advisories	•	
QuickAlerts EWS (local on-device)	○	G01
QuickAlerts Advanced (license to IGS/PIC iX)	○	G01
Alarms configurable for volume, tone and pausing	•	

## Hardware features and options

Stores up to 1,000 patient records	•	
Toggle between dark/light display options	•	
360° alarm light	•	
Task light	•	
10.1" color touchscreen	•	
Integrated audio speakers	2	
VGA-out connector (for training purposes)	•	
One lithium-ion battery pack, 9 cells	•	
Integrated recorder with paper	○	E05

## Connectivity features and options

Compatible with Imprivata's enterprise Single Sign-On	•	
Compatible with Philips Device Management DB (A.02+)	•	
Nurse call connector	•	
Time-sync with hospital or network clock	•	
QuickCheck workflows	8	
USB ports	2	
Compatible with Philips (IGS/PIC iX)	•	G01
Wireless data transmission (802.11 a/b/g/n)	○	W01

## Warranty and service

Jadak barcode scanner programming service	•	
Software maintenance updates	•	
3 year parts-only warranty (varies by market)	•	S01

Additional clinical and IT integration services are available but vary by market, please see your Philips representative for complete service availability.

© 2024 Koninklijke Philips N.V. All rights reserved. Koninklijke Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and hereby disclaims any liability resulting from the use of this publication. Microstream is a trademark of Medtronic companies. Masimo, rainbow®, SET™ and SpHb, are trademarks or registered trademarks of Masimo Corporation.



How to reach us  
Please visit [www.philips.com](http://www.philips.com)  
[healthcare@philips.com](mailto:healthcare@philips.com)

## Accessories and cable options (see IFU for additional choices)

Not all products are available in all geographies, please contact your Philips representative for complete portfolio availability.

Philips Easy Care reusable NBP cuffs Available sizes: infant, pediatric, small adult, adult, adult long, large adult, large adult long, thigh	M4552B, M4553B, M4554B, M4555B, M4556B, M4557B, M4558B, M4559B
Philips Adult NBP air hose (1.5m or 3m)	989803209761, 989803209771
Philips SpO <sub>2</sub> finger glove sensor (requires SP1)	M1191BL
Philips SpO <sub>2</sub> finger clip sensor (requires SP1)	M1196A
<b>Red 25 LNC-4, Straight</b> Masimo rainbow SET™ SpO <sub>2</sub> , 25-pin cable to LNCS sensors, 4 ft (requires SP5)	9898 031 86531 (Masimo PN: 3630)
<b>RD rainbow SET R25-12, Straight</b> Masimo RD rainbow SET R25-pin cable to RD sensors, 12 ft (requires SP5)	9898 032 06931 (Masimo PN: 4078)
<b>rainbow RC25-4, Straight</b> Masimo rainbow SET™ SpO <sub>2</sub> -SpHb, 25-pin cable to M-LNCS SpO <sub>2</sub> sensors or 15-pin rainbow sensors, 4 ft (requires R01, not available with R21)	9898 031 82421 (Masimo PN: 3628)
<b>RAM Dual Cable RC25-10</b> Masimo rainbow SET™ SpO <sub>2</sub> -SpHb-RRa 25-pin cable to M-LNCS/RAS, 10 ft (requires R21 if measuring SpO <sub>2</sub> and RRa only)	9898 031 82431 (Masimo PN: 3503)
<b>Riester Ear Thermometer</b> ri-thermo® tymPRO+ with Smart Cradle	9898 032 20891 (Order with T02 option)

## Workflow accessories

VSM premium rollstand with mounting plate (see separate ordering guide for complete list of optional roll stand accessories)	9898 032 06541
VS30 Mounting Kit (for SureSigns legacy rollstand)	9898 031 95541
Wall mount	9898 031 95571
Lithium ion battery pack, 9 cells	9898 031 99221
HS-1 2D barcode scanner - programmable (Jadak)	9898 031 76611
HS-1R RFID barcode scanner (Jadak)	M8024A_#E16
Wave ID Mini RFID reader (rf IDEAS)	9898 032 20761
XP 2D barcode scanner (Honeywell)	9898 032 17551
Serial interface adapter	9898 031 59601
Recording paper, 5 rolls	9898 031 36891



Philips Medizin Systeme Böblingen GmbH  
Hewlett-Packard Strasse 2  
71034 Böblingen  
Germany

00000227-01-04\* Dec 2024