

Philips
Water filter pitcher

Microfiltration

GAC + ion-exchange resin
1.5 L tank for filtered water

AWP2918



Clean water made easy

Microfiltration system reduces lead and chlorine

With a multi-stage microfiltration system, this water filter pitcher reduces VOCs and pesticides and removes up to 99% of chlorine and lead for healthy and tasty drinking water*. It also reduces water hardness.

Cleaner water

- Effectively reduces lead, pesticides, VOCs and chlorine

Made easy

- Dust-proof spout keeps water fresh and clean
- Simply discard the one-piece filter after use

PHILIPS

Water filter pitcher
Microfiltration GAC + ion-exchange resin, 1.5 L tank for filtered water

AWP2918/10

Specifications

Filtration performance

- Chlorine reduction: Yes, up to 99%*
- Bacteria removal: N/A
- Soluble lead reduction: Yes, up to 99%*
- Water hardness reduction

Filter specifications

- Main filter media: Granular activated carbon/GAC, ion-exchange resin
- Filtration capacity: 200 L

Input water conditions

- Input water pressure: (atmospheric) 0-1 Bar
- Input water quality: Mains tap water
- Input water temperature: 5-38 °C

General specifications

- Replacement filter cartridge: AWP200/AWP201
- Water flow rate: 0.25 L/min

Country of origin

- Pitcher: China
- Filter: China

Highlights

One-piece disposable filter

Simply discard the one-piece filter when it reaches the end of its service life. The one-piece design prevents secondary pollution.

Dust-proof spout

By preventing dust from getting in through the water outlet, the dust-proof spout keeps the water fresh and clean.

4-stage microfiltration

The 4 stage filtration system consists of non-woven fabric, granular activated carbon, resin and another layer of non-woven fabric, which effectively reduces pesticides, chemicals, microplastics and up to 99% lead* and chlorine for crisp and pure-tasting water. It also reduces water hardness.



Issue date 2023-11-01

Version: 3.0.1

EAN: 48 97099 30176 9

© 2023 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com

* **Based on test results from the international certification testing agency BV under laboratory conditions. Soluble lead reduction is still 88% at the end of the filter's service life.