

PHILIPS

Pocket projector

PicoPix

50 lumens

PPX4350



Project your life

PicoPix pocket projector

Equipped with HDMI, USB and micro SD slot it's never been so easy to project videos and pictures. With the integrated media player and the Bluetooth audio function the PicoPix can be connected to Bluetooth speakers.

Wireless connectivity

- Bluetooth audio function

Excellent image quality

- WavEngine with LED technology
- Project HD videos and images up to 60" (152 cm) in size

High usability

- HDMI interface, micro SD slot, integrated media player
- Support of MHL for mobile devices

USBQuickLink

- USB plug & socket for power and to play videos

Specifications

Technology

Display technology: DLP WavEngine

Light source: RGB LED

LED light sources: Last over 30.000 hours

Brightness: up to 50 lumens

Contrast ratio: 1300:1

Resolution: 640 x 360 pixel

Throw ratio: 2,2:1

Screen size (diagonal): 25 cm-152 cm / 10"-60"

Screen distance: 48 cm-285 cm / 19"-112"

Aspect ratio: 16:9

Projection modes: front, front ceiling, rear, rear ceiling

Wall color correction: blue, green, pink, white, yellow

Focus adjustment: Manual

Integrated media player

Internal memory: 4 GB

Noise level: < 28 dba

Sound

Internal speaker: 1 Watt (max)

Supported audio formats: mp3, wav

Connection

Bluetooth: Connects PPX 4350 to external bluetooth speakers

USB: Slave - mass storage device (x-change data with PC); Master - connect mass storage devices; Charging

HDMI: mini HDMI with HDCP

External Memory: micro SD/SDHC

Output audio: 3.5 mm audio out jack for headphones

Internal media player

Supported video formats: container: avi, mov, mp4, mkv; codecs: MJPEG, MPEG4, H.264"

Supported audio formats: mp3, wav

Power source

Internal battery: Internal battery: 1800mA, Optimal mode: 1.5 hours, Eco mode: 2 hours

Dimensions

Packed (W x D x H): 130 x 86 x 65 mm / 5.12 x 3.39 x 2.56 inch

Unpacked (W x D x H): 97 x 54 x 17 mm / 3.81 x 2.12 x 1.00 inch

Weight

Packed: 192 g / 6.17 oz

Unpacked: 129 g / 4.14 oz

Temperature range

Operation: 5 ~ 35° C

Storage packed: -25 ~ 60° C

Storage unpacked: 0 ~ 45° C

Relative humidity

Operation: 15 ~ 85% RH

Storage packed: 5 ~ 93% RH

Storage unpacked: 15 ~ 85% RH

Standard package includes

PPX4350

User guide: on internal memory

Quick start guide

Warranty card

Mini-HDMI to HDMI cable

