



Project your life

PicoPix pocket projector

Equipped with HDMI and USB interface it's never been so easy to project videos and pictures. The USBQuickLink offers a USB plug to charge the device. No matter where you are - Project your life with PPX4150!

Excellent image quality

WavEngine with LED technology

High usability

· Support of MHL for mobile devices

USBQuickLink

• USB plug and socket for power and easy connection

Specifications

Technology

Display technology: DLP WavEngine

Light source: RGB LED

LED light sources: last over 30.000 hours

Brightness: up to 50 lumens Contrast ratio: 1300:1 Resolution: 640 x 360 pixel

Throw ratio: 2,2:1

Screen size (diagonal): 25 cm-152 cm /

10"-60"

Screen distance: 48 cm-285 cm / 19"-112"

Aspect ratio: 16:9

Projection modes: front, front ceiling, rear, rear

ceiling

Wall color correction: blue, green, pink, white,

yellow

Focus adjustment: manual Noise level: < 28 dba

Sound

Internal speaker: 1 Watt (max)

Connection

USB: Slave - mass storage device (x-change data with PC); Master - connect mass storage

devices; Charging

HDMI: mini HDMI with HDCP

Output audio: 3.5 mm audio out jack for

headphones

Power source

Internal battery: Internal battery: 1800mA, Optimal mode: 1.5 hours, Eco mode: 2 hours

Dimensions

Packed (W x D x H): $130 \times 86 \times 65 \text{ mm} / 5.12 \times 3.39 \times 2.56 \text{ inch}$

Unpacked (W x D x H): $97 \times 54 \times 17 \text{ mm} / 3.81 \times 2.12 \times 0.67 \text{ inch}$

Weight

Packed: 192 g / 6.17 oz Unpacked: 129 g / 4.14 oz

Temperature range

Operation: 5 ~ 35° C / 41 - 95° F Storage packed: -25 ~ 60° C / -13 - 140° F Storage unpacked: 0 ~ 45° C / 32 - 113° F

Relative humidity

Operation: 15 ~ 85% RH Storage packed: 5 ~ 93% RH Storage unpacked: 15 ~ 85% RH

Standard package includes

PPX4150

Mini-HDMI to HDMI cable

Quick start guide

User guide: on internal memory

Warranty card





