

# PHILIPS

20 inch LED light bar

Ultinon Drive 2000

Road-legal ECE R149 - 37,5

5300 lm. +400m beam length

LED position-light function

All terrain, all weather

LUMUD2003LX1



## Boosted visibility brings safer driving

Extra brightness for everyday use

See far and wide with crisp, white light projected up to 400 meters. The Ultinon Drive 2003L LED light bar is 100% road-legal with a tough, one-piece design integrating advanced cooling tech. It shrugs off water, dust, rust and impacts.

### **Boosted visibility makes you safer on the road**

- Extra brightness for superior visibility

### **Be noticed with additional position lights**

- Extra position lights that get you noticed

### **Built to withstand difficult driving conditions**

- Corrosion-free, stainless-steel mounting brackets

### **Robust design for challenging conditions**

- Robust design for tough environments

### **Road-legal auxiliary lights**

- Powerful road-legal LED light bars

# Highlights

## Up to 331-meter visibility

The Philips Ultinon Drive 2003L LED light bar gives you extra high-beam brightness to illuminate the road ahead for up to 400 meters\*. Producing 5300 lumens (effective), our LED light bar complies with ECE-R149-27,5 and provides ample visibility ahead and at the road's edges for faster reactions. Its cool light color of 6000 Kelvin creates better contrast and keeps drivers focused.

## Bright LED position lights

Try our Philips Ultinon Drive 2003L LED light bar with position lights, and you'll never go unnoticed on side roads or in parking areas.

## Built for tough environments

The Philips Ultinon Drive 2003L LED light bar is built to withstand tough conditions throughout your journey. It is shock-resistant (IK07-rated) to ensure faultless performance on and off the road, with an unbreakable polycarbonate lens. It can handle immersion

in water (IP67-rated) to provide reliable illumination for your overland adventures, wherever your trail leads.

## Road-legal LED lights

The Philips Ultinon Drive 2003L series meets ECE-R149 standards and is 100% road-legal for high-beam and position-light functions. For added safety, Philips LED light bars are tested to EMC R10 specification to ensure they will function smoothly with your vehicle's electrical systems.

## Corrosion-free brackets

The mounting brackets for the Philips Ultinon Drive 2003L LED light bar are made of stainless steel, which is corrosion-free. They can withstand snow, ice and even salt. Built from durable, high-quality materials, your Philips auxiliary LED lights will provide years of reliable service.

# Specifications

## Electrical characteristics

**Voltage:** 9-30 Volt DC

## Light characteristics

**Beam length 1 lux-m:** 400

**Beam pattern:** Combo beam

**Color temperature:** 6000 K K

**Effective lumen output:** 5300 lumens

**Raw lumen output:** 9920 lumens

**Beam length 3 lux-m:** 189

## Ordering information

**GOC:** 01836694

**Order entry:** UD2003LX1

## Packaging Data

**EAN1:** 8719018018366

**EAN3:** 8719018018373

## Packed product information

**Box dimensions-L(mm):** 520

**Box dimensions-W(mm):** 80

**Box dimensions-H(mm):** 80

**MOQ (for professionals):** 4

**Number of product in the box:** 1 lamp

**Gross weight box-g:** 1072±55

**Net weight product-g:** 1392±55

## Product description

**Boost function installation:** No

**Boost mode activation:** No

**Break resistance**

**Corrosion protection:** Yes, aluminum powder coated

**corrosion-free brackets:** Side mounting brackets

**ECE R10**

**ECE R148**

**ECE R149**

**ECE reference number:** 37.5

**Heat sink:** Aluminum powder coated die-cast

**Impact protection rating (IK):** IK07

**Ingress protection rating (IP):** IP67

**Installation angle:** 360°

**Material:** Aluminum die-cast

**Number of LEDs:** 16x 5W

**Offroad boost:** No

**One-piece body design**

**Operating temperature:** -40° C to 80° C

**Parking position light**

**Plug type:** 3-pin DT Connector with 0.5m cable

**Range:** Ultinon Drive 2000

**Scratch resistant lens**

**Technology:** LED

**Width:** 508 mm / 20 inch

