PHILIPS

7 inch round LED driving light

Ultinon Drive 2000

Road-legal ECE R149 - 37,5 4200 lm, +390m beam length LED position-light function All terrain, all weather

LUMUD2001RX1





Boosted visibility brings safer driving Extra brightness for everyday use

See far and wide with crisp, white light projected up to 390 meters. The Ultinon Drive 2001R LED driving light is 100% road-legal with a tough, one-piece design integrating advanced cooling tech. It shrugs off water, dust, rust and impacts.

- Boosted visibility makes you safer on the road
- Extra brightness for superior visibility
- Built to withstand difficult driving conditions
- Robust design for tough environments
- Robust design for challenging conditions

Corrosion-free body, stainless-steel mounting brackets

Road-legal auxiliary lights

• Powerful road-legal LED driving light

Highlights

Up to 390-meter visibility

The Philips Ultinon Drive 2001R gives you extra high-beam brightness to illuminate the road ahead for up to 390 meters*. Producing 4400 lumens (effective), our LED light bar complies with ECE-R149 and provides ample visibility ahead and at the road's edges for faster reactions. Its cool light color of 6500 Kelvin creates better contrast and keeps drivers focused.

Built for tough environments

The Philips Ultinon Drive 2001R is built to withstand tough conditions throughout your journey. It is shock-resistant (IK07-rated) to ensure faultless performance on and off the road, with an unbreakable polycarbonate lens. It can handle immersion in water and power washing (IP68 & IP69K-rated) to provide reliable illumination for your overland adventures, wherever your trail leads.

Corrosion-free brackets

The mounting brackets for the Philips Ultinon Drive 2001R are made of stainless steel, which is corrosion-free. They can withstand snow, ice and even salt. Built from durable, high-quality materials, your Philips auxiliary LED light will provide years of reliable service.

Road-legal LED light

The Philips Ultinon Drive 2001R meets ECE-R149 standards and is 100% road-legal for high-beam and position-light functions. For added safety, Philips LED driving lights are tested to EMC R10 specification to ensure they will function smoothly with your vehicle's electrical systems.

Specifications

Electrical characteristics

Voltage: 9-30 Volt DC

Light characteristics

Beam length 1 lux-m: 390 Beam pattern: Combo beam Color temperature: 6500 K K Effective lumen output: 4200 lumens Raw lumen output: 10000 lumens

Ordering information

GOC: 01852633 Order entry: UD2001RX1

Packaging Data

EAN1: 8719018018526 EAN3: 8719018018533

Packed product information

Box dimensions-L(mm): 362 Box dimensions-W(mm): 105 Box dimensions-H(mm): 90 MOQ (for professionals): 2 Number of product in the box: 1 lamp

Product description

Boost function installation: No Boost mode activation: No **Break resistance** Corrosion protection: Yes, aluminum powder coated corrosion-free brackets: Side mounting brackets ECE R10 ECE R148: n/a **ECE R149** ECE reference number: 37.5 Heat sink: Aluminum powder coated die-cast Impact protection rating (IK): IK07 Ingress protection rating (IP): IP68 & IP69K Installation angle: 360° Material: Aluminum die-cast Number of LEDs: 40x 5W Offroad boost: No One-piece body design Operating temperature: -40° C to 80° C Parking position light Plug type: 2-pin DT Connector with 0.5m cable Range: Ultinon Drive 2000 Scratch resistant lens Technology: LED Width: 180 mm / 7 inch

© 2022 Lumileds Holding B.V. All Rights reserved.

their respective owners.

Specifications are subject to change without notice. Trademarks are the property of Lumileds Holding B.V. or

Issue date 2022-11-08 Version: 2.0.1

12 NC: 8670 001 86493

www.philips.com

