
PHILIPS

10 inch LED light bar

Ultinon Drive 2000

Road-legal ECE R149-20 3200 lm. +294m beam lenght LED position-light function All terrain, all weather

LUMUD2002LX1



Boosted visibility brings safer driving

Extra brightness for everyday use

See far and wide with crisp, white light projected up to 294 meters. The Ultinon Drive 2002L LED light bar is 100% road-legal with a tough, one-piece design integrating advanced cooling tech. It shrugs off water, dust, rust and impacts.

Boosted visibility makes you safer on the road

• Extra brightness for superior visibility

Be noticed with additional position lights

• Extra position lights that get you noticed

Built to withstand difficult driving conditions

• Robust design for tough environments

Robust design for challenging conditions

Corrosion-free, stainless-steel mounting brackets

Road-legal auxiliary lights

• Powerful road-legal LED light bars

Highlights

Up to 294-meter visibility

The Philips Ultinon Drive 2002L LED light bar gives you extra high-beam brightness to illuminate the road ahead for up to 294 meters*. Producing 3200 lumens (effective), our LED light bar complies with ECE-R149-12,5 and provides ample visibility ahead and at the road's edges for faster reactions. Its cool light color of 6000 Kelvin creates better contrast and keeps drivers focused.

Bright LED position lights

Try our Philips Ultinon Drive 2002L LED light bar with position lights, and you'll never go unnoticed on side roads or in parking areas.

Built for tough environments

The Philips Ultinon Drive 2002L LED light bar is built to withstand tough conditions throughout your journey. It is shock-resistant (IK07-rated) to ensure faultless performance on and off the road, with an unbreakable polycarbonate lens. It can handle immersion in water (IP67-rated) to provide reliable illumination for your overland adventures, wherever your trail leads.

Corrosion-free brackets

The mounting brackets for the Philips Ultinon Drive 2002L LED light bar are made of stainless steel, which is corrosion-free. They can withstand snow, ice and even salt. Built from durable, high-quality materials, your Philips auxiliary LED lights will provide years of reliable service.

Road-legal LED lights

The Philips Ultinon Drive 2002L LED light bar meets ECE-R149 standards and is 100% roadlegal for high-beam and position-light functions. For added safety, Philips LED light bars are tested to EMC R10 specification to ensure they will function smoothly with your vehicle's electrical systems.

LUMUD2002LX1/40

Specifications

Electrical characteristics

Voltage: 9-30 Volt DC

Light characteristics

Beam length 1 lux-m: 294 Beam pattern: Combo beam Color temperature: 6000 K K Effective lumen output: 3200 lumens Raw lumen output: 4960 lumens Beam length 3 lux-m: 150

Ordering information

GOC: 01834294 Order entry: UD2002LX1

Packaging Data

EAN1: 8719018018342 EAN3: 8719018018359

Packed product information

Box dimensions-L(mm): 280 Box dimensions-W(mm): 80 Box dimensions-H(mm): 80 MOQ (for professionals): 4 Number of product in the box: 1 lamp Gross weight box-g: 840±30 Net weight product-g: 600±30

Product description

Boost function installation: No Boost mode activation: No Break resistance Corrosion protection: Yes, aluminum powder coated corrosion-free brackets: Side mounting brackets ECE R10 **ECE R148 ECE R149** ECE reference number: 20 Heat sink: Aluminum powder coated die-cast Impact protection rating (IK): IK07 Ingress protection rating (IP): IP67 Installation angle: 360° Material: Aluminum die-cast Number of LEDs: 8x 5W Offroad boost: No One-piece body design Operating temperature: -40° C to 65° C Parking position light Plug type: 3-pin DT Connector with 0.5m cable Range: Ultinon Drive 2000 Scratch resistant lens Technology: LED Width: 266 mm / 10 inch

© 2023 Lumileds Holding B.V. All Rights reserved.

their respective owners

Specifications are subject to change without notice. Trademarks are the property of Lumileds Holding B.V. or Issue date 2023-02-25 Version: 1.0.1

12 NC: 8670 001 89852

www.philips.com



* Beam length measured on 1 lux.