

LUMUD2001LX2



# Boosted visibility brings safer driving

## Extra brightness for everyday use

See far and wide with crisp, white light projected up to 270 meters. The Ultinon Drive 2001L LED light bar is 100% road-legal with a tough, one-piece design integrating advanced cooling tech. It shrugs off water, dust, rust and impacts.

## Boosted visibility makes you safer on the road

• Extra brightness for superior visibility

### Be noticed with additional position lights

• Extra position lights that get you noticed

## **Built to withstand difficult driving conditions**

• Robust design for tough environments

## Robust design for challenging conditions

• Corrosion-free, stainless-steel mounting brackets

### Road-legal auxiliary lights

• Powerful road-legal LED light bars

## Highlights

#### **Bright LED position lights**

Try our Philips Ultinon Drive 2001L LED light bar with position lights, and you'll never go unnoticed on side roads or in parking areas.

#### **Built for tough environments**

The Philips Ultinon Drive 2001L LED light bar is built to withstand tough conditions throughout your journey. It is shock-resistant (IK07-rated) to ensure faultless performance on and off the road, with an unbreakable polycarbonate lens. It can handle immersion in water (IP67-rated) to provide reliable illumination for your overland adventures, wherever your trail leads.

#### **Corrosion-free brackets**

The mounting brackets for the Philips Ultinon Drive 2001L LED light bar are made of stainless steel, which is corrosion-free. They can withstand snow, ice and even salt. Built from durable, high-quality materials, your Philips auxiliary LED lights will provide years of reliable service.

#### Road-legal LED lights

The Philips Ultinon Drive 2001L series meets ECE-R149 standards and is 100% road-legal for high-beam and position-light functions. For added safety, Philips LED light bars are tested to EMC R10 specification to ensure they will function smoothly with your vehicle's electrical systems.

#### Up to 270-meter visibility

The Philips Ultinon Drive 2001L LED light bar gives you extra high-beam brightness to illuminate the road ahead for up to 270 meters\*. Producing 2000 lumens (effective), our LED lightbar complies with ECE-R149-10 and provides ample visibility ahead and at the road's edges for faster reactions. Its cool light color of 6500 Kelvin creates better contrast and keeps drivers focused.

## Specifications

#### **Electrical characteristics**

Voltage: 9-30 Volt DC

#### **Light characteristics**

Beam length 1 lux-m: 270 Beam pattern: Combo beam Color temperature: 6000 K K Effective lumen output: 2000 lumens Raw lumen output: 3270 lumens Beam length 3 lux-m: 140

#### **Ordering information**

GOC: 01832894 Order entry: UD2001LX2

#### **Packaging Data**

EAN1: 8719018018328 EAN3: 8719018018335

#### **Packed product information**

Box dimensions-L(mm): 180 Box dimensions-W(mm): 150 Box dimensions-H(mm): 80 MOQ (for professionals): 4 Number of product in the box: 2 lamps Gross weight box-g: 1138±36 Net weight product-g: 1138±36

### **Product description**

Boost function installation: No Boost mode activation: No Break resistance

Corrosion protection: Yes, aluminum powder

corrosion-free brackets: Side mounting

brackets ECE R10 **ECE R148 ECE R149** 

ECE reference number: 10

Heat sink: Aluminum powder coated die-cast

Impact protection rating (IK): IK07 Ingress protection rating (IP): IP67

Installation angle: 360° Material: Aluminum die-cast Number of LEDs: 16x 5W, 6x 5W

Offroad boost: No One-piece body design

Operating temperature: -40° C to 65° C

Parking position light

Plug type: 3-pin DT Connector with 0.5m

Range: Ultinon Drive 2000 Scratch resistant lens Technology: LED Width: 163 mm / 6 inch

© 2023 Lumileds Holding B.V. All Rights reserved

their respective owners.

Issue date 2023-02-25

12 NC: 8670 001 89851

www.philips.com



Specifications are subject to change without notice. Trademarks are the property of Lumileds Holding B.V. or

<sup>\*</sup> Beam length measured on 1 lux.