

PHILIPS

10 inch double row
LED lightbar

Ultinon Drive 5050L

Road-legal ECE R149-40

3300 lm, 427m beam length

All-terrain, all-weather fit

Offroad boost function

LUMUD5050LX1

 Product Picture

Powerful brightness for a safer drive

Bright, durable gear for overland journeys

Projecting light for 427m (boost: 448m), the Ultinon Drive 5050L LED lightbar is road-legal and provides a boost for offroad challenges. It ensures safety through brightness, is built to last, corrosion-free, resistant to water and shocks.

Greater safety with powerful brightness

- Bright, long beam for superior visibility

Boost function for safer offroad experiences

- Enhanced safety offroad with boost function for more power

Durable equipment for challenging conditions


- Sturdy one-piece body for tough environments
- IP69K waterproof to master the elements
- Corrosion-free, stainless-steel mounting brackets

Road-legal auxiliary lights

- Powerful road-legal LED lightbars

Highlights

Full visibility for 427 meters



The Philips Ultinon Drive 5050L provides an outstanding beam that illuminates the road ahead for 427 meters.* With 3300 lumen (effective) coming from its cumulated, powerful 100W LEDs and ECE-R149-40, it provides ample visibility for faster reactions. A combined spot and flood light, it shines both far and wide, helping you see roadside hazards too. The lamps' highly homogenous beam and cool light color of 6500 Kelvin keep you focused without straining your eyes.

Boost for extra offroad power



The Philips Ultinon Drive 5050L is equipped with two light functions: for on-road drives, the lightbar brings you outstanding homologated brightness for greater safety. Offroad, you can opt for increased intensity. Switch on your

boost function to unleash its full power and increase the beam length to 448 meters. More performance for tougher conditions.

Sturdy one-piece body



The Philips Ultinon Drive 5000L series is built in a single piece to withstand the toughest conditions. This allows for excellent heat management and consistently high light output throughout your journey. Rated IK07, it is shock-resistant to ensure faultless performance on and off the road. Its unbreakable polycarbonate lens can take any hit without damage or scratches and the convenient DT connector guarantees a perfect connection.

Waterproof for durable light



With its ingenious screwless design, the Ultinon Drive 5000L series can withstand the wettest conditions. IP68 and IP69K certification means

it will perform, wherever your road leads and whatever the weather. And it will be more than a match for any power washer you use to clean your car afterwards.

Corrosion-free brackets

The mounting brackets are made of stainless steel, which is corrosion-free. They can withstand snow, ice and even salt. Built from durable, high-quality materials, your auxiliary lights will provide years of reliable service.

Road-legal lights



The Philips Ultinon Drive 5000L series meets ECE-R149 standards and is road-legal. For added safety, Philips LED lightbars are tested to EMC R10 specification to ensure they will function smoothly with your vehicle's electrical systems.

Specifications

Electrical characteristics

Voltage: 9-30 Volt DC

Product description

Impact protection rating (IK): IK07

Ingress protection rating (IP): IP68 & IP69K

ECE R10

ECE R149

ECE reference number: 40

Material: Aluminum die-cast

Technology: LED

Number of LEDs: 20x 5W

Operating temperature: -40° C to 80° C

Heat sink: 13-piece 1.5mm

Installation angle: 360°

Scratch resistant lens

Break resistance

Corrosion-free brackets: Yes, included

One-piece body design

Offroad boost

Plug type: Connector with 0.5m cable

Range: Ultinon Drive 5000

Boost mode activation: Dashboard switch

Boost function installation: Cable included

Width: 10 inch

Light characteristics

Color temperature: 6500 K K

Beam length 3 lux-m: 245

Beam length 1 lux-m: 425

Beam width 3 lux-m: 64

Beam width 1 lux-m: 90

Beam length 3 lux (boost)-m: 258

Beam length 1 lux (boost)-m: 448

Effective lumen output: 3300

Effective lumen output (boost): 4000

Raw lumen output: 9520

Packed product information

Dimensions-L(mm): 339

Dimensions-W(mm): 49.3

Dimensions-H(mm): 84.2

Box dimensions-L(mm): 350

Box dimensions-W(mm): 90

Box dimensions-H(mm): 105

Net weight product-g: 1010

Gross weight box-g: 1020

MOQ (for professionals): 4

Ordering information

Order entry: UD5050LX1

GOC: 01493194

Packaging Data

EAN1: 8719018014931

EAN3: 8719018014924

