19 inch LCD Monitor

when screen size matters

Big screen productivity : With outstanding ergonomics and great front-of-screen performance plus SmartManage for remote, LAN-based monitor management and low power consumption, the Philips 190S5 delivers an outstanding return on investment.

Lower total cost of ownership

- SmartManage manages display devices remotely
- · Lower power consumption than industry average
- · Kensington anti-theft lock secures monitor against theft

Outstanding front of screen performance

- Fast response time capable of handling fast moving pictures
- SXGA 1280 x 1024 resolution for sharper display
- sRGB ensures color matching between display and printouts

Maximum comfort for maximum productivity

- · Screen height adjustable for ideal viewing angle
- Screen tilt and swivel adjustment for ideal viewing angle
- Cable management for a tidy work space

Great convenience

- Embedded power supply eliminates external power adaptors
- VESA mounting pattern for easy wall mounting of display

















19 inch I CD Monitor

Commercial Specifications

Picture/ **Display**

- LCD Panel Type
- Panel Size
- Effective Viewing Area
- Pixel Pitch
- Brightness (nits)
- Contrast Ratio
- Display Colors
- Viewing Angle (C/R > 5)
- Response Time
- White Chromaticity, 6500° K x = 0.313 / y = 0.329
- White Chromaticity, 9300° K x = 0.283 / y = 0.297.
- Maximum Resolution
- . Recommended Resolution .
- Factory Preset Modes
- User Definable Modes
- Horizontal Scanning Frequency 30 82 KHz Refresh Rate (V)
- sRGB
- Connectivity
- Signal Input

Convenience

- Convenience Enhancements
- Monitor Controls
- OSD Languages
- Other Convenience Features
- Plug & Play Compatibility
- Regulatory Approvals
- Swive
- Tilt
- VESA Mount

Accessories

- User Manual Included Accessories
- DDC/Cl. Windows 98/ME/2000/XP CE Mark, E2000, FCC-B, UL, CSA, NUTEK, Energy Star, SEMKO,

Kensington Lock

Spanish

- TCO '03, TCO '99, TUV/GS,
- TUV Ergo +/- 175 -5° to 30°
- 100 mm x 100 mm
 - Yes AC Power Cord, VGA Cable

- **Dimensions**
- Depth (with base) Height (with base)
- Width (with base)
- MTBF
- Relative Humidity
- Temperature Range (Operation)
- Temperature Range (Storage)
- Weight

Power

- Complies With
- Consumption
- Off Mode
- Power LED Indicator
- Power Supply

Product Highlights

SmartManage

A system for monitoring, managing and checking status of display devices as well as delivering remote support to users who experience difficulties all accomplished over a LAN.

Lower power consumption

Reduction of the electrical power required to operate a device.

Kensington anti-theft lock

A security device that fixes the monitor in place to prevent theft.

Fast response time

The amount of time it takes for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Lower numbers mean faster transitions and therefore result in fewer visible image artifacts.

SXGA, 1280 x 1024 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. For example, a 1280-by-1024 pixel screen is capable of displaying 1280 distinct dots on each of 1024 lines, or about 1.3 million pixels.

sRGB ready

Calibrated RGB that is optimized for the vast majority of computer peripherals, monitors, operating systems and browsers, allowing accurate color mapping with very little data overhead.

Adjustable height

The ability to set your monitor to the most pleasurable viewing height. Height adjustment makes computer work more comfortable and reduces fatigue or eyestrain, even when you spend long hours working on the computer. It makes you more broductive.

Screen tilt and swivel

Movement of a screen to attain the ideal viewing angle.

Cable management

A system for organizing cables and wires required for the operation of a display device to have a tidy work space.

Embedded power supply

A power adaptor built into the body of a display device that replaces a bulky external power adaptor.

VESA mounting holes

A unified industry standard for mounting IT equipment set by the Video Electronics Standards Association.

2004



Trademarks owned by Royal Philips Electronics 2004 © Royal Philips Electronics - All rights reserved As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency. Microsoft and Windows are registered trademarks of Microsoft Corporation. All data subject to change without notice Release date: June 2004 www.philips.com

20 % - 80 % 5°C to 35°C -20°C to 60°C 7.16 kg E2000, Energy Star,

NUTFK 34 W (Typical) 1 W Operation, Green; Stand by/Sleep, Amber

235 mm

419 mm

425 mm

50,000 hrs (excl.

CCFL 40,000) hrs

Built-in

Analog (VGA)

On-screen Display, SmartManage

Auto, Brightness control,

Left/Right, Menu (OK),

Power On/Off, Up/Down,

English, French, German,

Italian, Simplified Chinese,

1280 x 1024 bixels.

Anti-glare Polarizer,

RGB Vertical Stripe

376.3 x 301.1 mm

0.294 x 0.294 mm

- Horizontal : 160° - Vertical : 160°

1280 x 1024 @ 75Hz

19"/ 48 cm

250

500:1

16 M

16 ms

1.5 modes

14 modes

56 - 76 Hz

Yes

1280 x 1024 @ 60Hz