

Attractive 16:9 HD display offers great value

Enjoy more with this Vista-ready HD display! With VGA inputs, Auto format, SmartContrast and Glossy finish, the 192E1 is a great choice for all your needs

Great picture quality

- · Ready to display HD content
- 16:9 display for best widescreen gaming and video
- SmartContrast 25000:1 for incredible rich black details
- 5ms fast response time

Design that complements any interior


- Glossy finish to enhance your decor
- Small footprint to blend into any lifestyle

Environmentally friendly green design

- Energy Star for energy efficiency and low power consumption
- \bullet Eco-friendly materials that meets international standards

Great convenience

 $\bullet\,$ Easy picture format control switching in wide and 4:3 format



48 cm (19") w E-line

192E1SB1



Highlights

High definition monitor

A high definition monitor is a display device designed to deliver the exceptional picture quality of high definition pictures, one fully prepared for HD sources like HD set top boxes. A HD monitor offers picture quality beyond that of progressive scan, conforming to strict standards for HD screens that display high resolution, top picture quality signals through a universal connection for either analog VGA or uncompressed DVI digital connections and supports HDCP. It displays 720p (1280x720p @ 50 and 60 Hz progressive) and 1080i (1920x1080i @ 50 and 60 Hz interlaced) signals.

16:9 widescreen aspect ratio

An aspect ratio is an expression of a video image's width compared to its height. The 16:9 widescreen aspect ratio is standard for universal to highdefinition television and European digital television. A native 16:9 aspect ratio means outstanding game and video display without bars at top and bottom of the picture and without the quality loss than comes from scaling, altering an image to fit on a different screen size.

5ms on/off response time

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and, therefore, results in fewer visible image artifacts in the display of transition of texts and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

SmartContrast ratio 25000:1



You want the LCD flat display with the highest contrast and most vibrant images. Philips advanced




video processing combined with unique extreme dimming and backlight boosting technology results in vibrant images. SmartContrast will increase the contrast with excellent blacklevel and accurate rendition of dark shades and colors. It gives a bright. lifelike picture with high contrast and vibrant colors.

Energy Star 5.0

Energy Star is a US EPA sponsored energy efficiency program also adopted by many other countries. Energy Star certification ensures that you are buying a product which meets the latest power efficiency standards which operates with maximum power efficiency at all operational levels. New Philips monitors are certified for Energy Star 5.0 specifications and meet or exceed the standard. For example, in sleep mode Energy Star 5.0 requires less than 1watt power consumption, whereas Philips monitors consume less than 0.5 watts. Further details can be obtained from www.energystar.gov

Easy picture format control



Philips easy picture format control on OSD is to switch from the 4:3 aspect ratio to the widescreen mode and back again to match the display's aspect ratio with your content for working with wide documents without scrolling or viewing widescreen media in the widescreen mode and distortion-free. native mode display of 4:3 ratio content.

Specifications

Picture/Display

- LCD panel type: TFT-LCD
- Panel Size: 18.5 inch/ 47 cm
- · Aspect ratio: 16:9
- Pixel pitch: 0.30 x 0.30 mm
- SmartContrast ratio (dynamic): 25000:1
- Viewing angle: 176° (H) / 170° (V), @ C/R > 5
- Brightness: 250 cd/m²
- Contrast ratio (typical): 1000:1
- Response time (typical): 5 ms
- Optimum resolution: 1366 x 768 @ 60 Hz
- Display colors: 16.7 M
- Scanning Frequency: 30 83 kHz (H) / 56 -75 Hz
- sRGB

Connectivity

- Signal Input: VGA (Analog), DVI-D (digital, HDCP)
- · Sync Input: Separate Sync, Sync on Green

Convenience

- User convenience: Brightness, Auto, Auto picture, Menu, Power On/Off
- · OSD Languages: English, French, German, Spanish, Italian, Russian, Simplified Chinese, Portuguese,
- Other convenience: VESA mount (100x100mm), Kensington lock
- Plug & Play Compatibility: DDC/CI, Windows 98/ 2000/XP/Vista, sRGB

Stand

• Tilt: -5/20 degree

Power

- Power LED indicator: Operation Blue, Stand by/ sleep -blue(blinking)
- Power supply: Built-in, 100-240VAC, 50/60Hz
- On mode: <13.2W (EnergyStar 5.0 test method)
- Standby mode: <0.8W
- Off mode: <0.5W

- Product with stand (mm): $444 \times 340 \times 192$ mm
- Product without stand (mm): $444 \times 286 \times 57 \text{ mm}$
- Packaging in mm (WxHxD): $520 \times 352 \times 133 \text{ mm}$

- Product with stand (kg): 3.2 kg
- Product without stand (kg): 2.9 kg
- Product with packaging (kg): 4.3 kg

Operating conditions

- Temperature range (operation): 0 to 40 °C
- \bullet Temperature Range (storage): -20 to 60 $^{\circ}\text{C}$
- Relative humidity: 20%-80 %
- MTBF: 50,000 hour(s)

Sustainability

- · Environmental and energy: EPEAT Silver, RoHS, EnergyStar 5.0
- Recyclable packaging material: 100 %

Compliance and standards

• Regulatory Approvals: BSMI, CE Mark, FCC, Class B, UL/cUL

Cabinet

- · Color: Black
- Finish: Glossy



Issue date 2011-06-07

Version: 1.0.1

© 2011 Koninklijke Philips Electronics N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

12 NC: 8670 000 66722 EAN: 87 12581 55891 8 www.philips.com