



Simplify your connections

with USB-C docking monitor

The Philips B line monitor with USB-C docking replaces cable clutter. View Full HD image and recharge your laptop all at the same time with a single USB-C cable. SmartErgo base, Flicker-free and LowBlue mode make work easy on the eyes.

Excellent performance

• IPS technology for full colours and wide viewing angles

Single cable USB-C connection

- Connect your notebook with one USB-C cable
- Power and re-charge compatible notebook from the monitor
- USB 3.2 high-speed data transfer

Designed for the way you work

- SmartErgoBase enables user-friendly ergonomic adjustments
- · HDMI ensures universal digital connectivity
- Less eye fatigue with Flicker-Free technology
- LowBlue Mode for easy-on-the-eyes productivity

Designed for sustainability

- $\bullet \ \ PowerSensor \ saves \ up \ to \ 70\% \ energy \ costs$
- Designed to meet environmental standards

LCD monitor with USB-C 273B9/00

Highlights

USB-C connection




This Philips display features a USB type-C connector with power delivery. With intelligent and flexible power management, you can power charge your compatible device directly. Its slim, reversible USB-C allows for easy, one-cable connection. You can watch high-resolution video and transfer data at super speed, while powering up and recharging your compatible device at the same time.

Power and re-charge notebook

This monitor features a built-in USB-C connector that meets USB Power Delivery standard. With intelligent and flexible power management, you can now power up and/or re-charge your compatible* Notebook directly from the Monitor using a single USB-C cable.

IPS technology



IPS displays use advanced technology that gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle — even in 90-degree Pivot mode! Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colours, making it ideal not only for Photos, films and web browsing, but also for professional applications that demand colour accuracy and consistent brightness at all times.

SmartErgoBase



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base can swivel, tilt and rotate to various angles to ensure maximum comfort. The height-adjustable stand guarantees the optimal viewing level, reducing the physical strains of a long workday, while cable management reduces cable clutter and keeps the workspace neat and professional.

Flicker-Free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-Free technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave-length blue light rays from LED displays can cause eye

damage and affect vision over time. Developed for wellbeing, the Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. An HDMI cable enables high-quality digital video and audio to be transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

PowerSensor



PowerSensor is a built-in 'people sensor' that transmits and receives harmless infrared signals to determine if the user is present and automatically reduces monitor brightness when the user steps away from the desk, cutting energy costs by up to 70 percent and prolonging monitor life.

















LCD monitor with USB-C 273B9/00

Specifications

Picture/Display

Panel Size: 27 inch/68.6 cm

Aspect ratio: 16:9

LCD panel type: IPS technology Backlight type: W-LED system Pixel pitch: 0.3114 x 0.3114 mm

Brightness: 250 cd/m² Display colours: 16.7 M

Colour gamut (typical): NTSC 76%*, sRGB 98%*

Contrast ratio (typical): 1000:1 SmartContrast: 50,000,000:1

Response time (typical): 4 ms (Grey to Grey)* Viewing angle: 178° (H)/ 178° (V), @ C/R > 10

Picture enhancement: SmartImage

Maximum resolution: 1920 x 1080 @ 75 Hz*
Effective viewing area: 597.888 (H) x 336.312 (V)
Scanning Frequency: 30–85 kHz (H) / 48–75 Hz

(V) sRGB Flicker-free Pixel Density: 82 PPI LowBlue Mode

Display Screen Coating: Anti-Glare, 3H, Haze

25% EasyRead Adaptive sync

Connectivity

Signal Input: VGA (Analogue), DisplayPort 1.2 x 1, HDMI 1.4 x 1, USB-C 3.2 Gen 1 x 1 (upstream, power delivery up to 65 W)

Sync Input: Separate Sync, Sync on Green

Audio (In/Out): PC audio-in, Headphone out

USB:: USB-C 3.2 Gen 1 x 1 (upstream), USB 3.2 x 4 (downstream with 1 fast charge B.C 1.2)

HDCP: HDCP 1.4 (DP/HDMI/USB-C)

USB

Power delivery: USB PD version 3.0 Super speed: Data and Video transfer DP: Built-in DisplayPort Alt mode USB-C max. power delivery: Up to 65 W (5 V/3 A;

9 V/3 A; 10 V/3 A; 12 V/3 A; 15 V/3 A;

20 V/3.25 A)

USB-C: Reversible plug connector

Convenience

Built-in Speakers: 2W x 2 Plug and Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7 User convenience: SmartImage, Input,
PowerSensor, Menu, Power On/Off
OSD Languages: Brazil Portuguese, Czech, Dutch,

English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian Other convenience: Kensington lock, VESA

mount (100 x 100 mm)

Control software: SmartControl

Stand

Height adjustment: 150 mm Pivot: -/+ 90 degree

Swivel: -/+ 175 degree Tilt: -5~30 degree

Power

ECO mode: 13.5 W (typ.)

Power supply: Built-in, 100–240 VAC, 50–60 Hz Off mode: Zero watts with Zero switch On mode: 16.5 W (typ.) (EnergyStar 8.0 test

method)

Standby mode: < 0.5 W (typ.)

Power LED indicator: Operation - White, Standby

mode - White (flashing)
Energy Label Class: E

Dimensions

Packaging in mm (W x H x D):

780 x 525 x 188 mm

Product without stand (mm): 614 x 372 x 61 mm Product with stand (max height): 614 x 558 x

224 mm

Weight

Product with packaging (kg): 10.91 kg Product with stand (kg): 7.03 kg Product without stand (kg): 4.59 kg

Operating conditions

Altitude: Operation: +12,000 ft (3658 m), Non-

operation: +40,000 ft (12,192 m)

Temperature range (operation): 0°C to 40°C °C

Relative humidity: 20%-80 %

Temperature range (storage): -20°C to 60°C °C MTBF (demonstrated): 70,000 hrs (excluded

backlight)

Sustainability

Environmental and energy: PowerSensor, EnergyStar 8.0, EPEAT*, TCO Certified Edge,

WEEE, RoHS

Post-consumer recycled plastic: 85% Recyclable packaging material: 100 % Specific Substances: PVC/BFR free housing,

Mercury free

Compliance and standards

Regulatory Approvals: CE Mark, FCC Class B, SEMKO, CU-EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB. CB

Cabinet

Finish: Texture Foot: Black Front bezel: Black Rear cover: Black

What's in the box?

Cables: HDMI cable, DP cable, USB-C to C/A

cable, Power cable Monitor with stand User Documentation

- * "IPS" word mark / trademark and related patents on technologies belong to their respective owners.
- * The maximum resolution works for either USB-C, DP or HDMI input.
- * Response time value equal to SmartResponse
- * NTSC Area based on CIE 1976
- * sRGB Area based on CIE1931
- * Activities such as screen sharing and online streaming over the Internet can impact your network performance. Your hardware and network bandwidth will determine the overall audio and video quality.
- * For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details.
- * For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mode
- * EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in your country.
- * The monitor may look different from feature images.

© 2025 Koninklijke Philips N.V. All Rights reserved. Issue date 2025-02-19 Version: 4.4.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 76419 7

www.philips.com

