

excellent and robust display solution

Excellent and robust, the network-controlled Philips 300WN5 LCD monitor provides a reliable and multi-function solution with Philips leading display technology that guarantees your message gets out to the public crystal clear.

Less management effort for maximum productivity

- Monitor is network controllable for remote management
- Brightness automatically adjusts with ambient conditions
- Automatic alert provides advance warning of overheating

Lower total cost of ownership

- Lifecycle is longer than plasma displays
- Intelligent power management for lower consumption
- Hidden control buttons prevent tampering with settings

Better front of screen experience

- Easy plug and play DVI ensures true digital experience
- WXGA, wide format, 1280x768 resolution for sharper display
- Ready for 480i, 480p, 576i, 576p, 720p and 1080i HDTV
- DCDi™ eliminates combing and jagged edges for a sharp image
- PiP allows watching a second source simultaneously



Included Accessories



Remote Control



Base



Speakers



PHILIPS

30 inch LCD Monitor

Commercial Specifications

Picture/ Display

- LCD Panel Type1280 x 768 Pixels, Anti-glare Polarizer
- Panel Size29.53" / 75 cm
- Pixel Pitch0.5025 x 0.1675 mm
- Brightness600 cd/m²
- Contrast Ratio800:1
- Display Colors16.7 M
- Viewing Angle (C/R > 10°)- Horizontal : 170°
- Vertical : 170°
- Response Time16 ms
- White Chromaticity, 5300° K $x = 0.328 / y = 0.344$
- White Chromaticity, 6500° K $x = 0.313 / y = 0.329$
- White Chromaticity, 9300° K $x = 0.283 / y = 0.297$
- Maximum Resolution1280 x 768 @ 60Hz
- Recommended Resolution1280 x 768 @ 60Hz
- Factory Preset Modes12 Modes
- Horizontal Scanning Frequency31 - 49 KHz
- Refresh Rate (V)60 Hz
- sRGBYes
- Aspect Ratio15:9
- Picture EnhancementPicture in Picture, Progressive Scan, De-interlacer

Connectivity

- AV InputComponent (YPbPr) x1, Composite (CVBS) x1, S-video x1, SCART x1, Audio (L/R) for YPbPr x1, Audio (L/R) x1, 75 ohm RF (TV) x1
- AV OutputComposite (CVBS) x1, Audio (L/R) x1, 3.5 mm Jack (L/R) x1, Ext 3.5 mm Jack x1
- PCD-Sub x1, DVI-D x1, 3.5 mm PC Audio Input x1, RS232 x1

Convenience

- Detachable Audio5W RMS x 2 (80 PMPO) Stereo Speaker
- SoftwareVirtual Surrounding Sound
- Child ProtectionParental Control
- Convenience EnhancementsOn-screen Display, Automatic Brightness Control, Automatic Overheat Warning
- Monitor ControlsLeft/Right, Menu (OK), Power On/Off, Up/Down, Input Select
- OSD LanguagesEnglish, French, German, Italian, Spanish, Simplified Chinese
- Plug & Play CompatibilitysRGB, Windows 98/ME /2000/XP
- Regulatory ApprovalsCE Mark, FCC-B, UL, CSA, NUTEK, Energy Star
- Teletext10 Pages (EU, AP)
- Closed CaptionYes (AP, NA)
- VESA Mount100 x 100 mm

Accessories

- Included AccessoriesAC Power Cord, Remote Control, VGA Cable, DVI-D Cable, Speakers (L/R) 1 Set
- StandYes
- User ManualYes

Dimensions

- Depth (with speakers)183 mm
- Height (with speakers)505 mm
- Width (with speakers)867.7 mm
- Depth (w/o base & speakers)115 mm
- Height (w/o base & speakers)469.3 mm
- Width (w/o base & speakers)726.7 mm
- MTBF50,000 hrs
- Relative Humidity20 % - 80 %
- Temperature (Operation)5°C to 35°C
- Temperature (Storage)-20°C to 60°C
- Weight16 kg

Power

- Complies WithEnergy Star, NUTEK
- Consumption130 W (PC), 150 W (TV) < 2 W
- Off ModeOperation, Blue, Stand by/Sleep, Amber Built-in
- Power LED Indicator
- Power Supply

Supported Display Resolution

- Computer Formats640 x 480, 60 Hz, 800 x 600, 60 Hz, 1024 x 768, 60 Hz, 1280 x 768, 60 Hz
- Video Formats480i 60 Hz, 480p 60 Hz, 576i 50 Hz, 576p 50 Hz, 720p 60 Hz, 50 Hz, 1080i 60 Hz, 50 Hz

Tuner/Reception/Transmission

- TV SystemNTSC, PAL, SECAM

Product Highlights

Network controllability: RS232

A system by which IT staff can control and adjust monitors remotely via RS232 protocol.

Automatic brightness control

The adjustment of display settings to correspond with ambient light without user intervention.

Automatic overheat warning

Automatic generation and delivery of an alert when a monitor overheated.

Long lifecycle

A longer lifecycle means a lower total cost of ownership and adds up to long-term savings.

Intelligent power management

Utilizing energy-efficient technologies in product design to reduce power consumption and significantly lower the total cost of ownership.

Hidden control buttons

Control buttons placed at the rear of a monitor used for public display to prevent tampering with display settings.

In-box DVI cable

A DVI cable is shipped with product.

WXGA 1280 x 768 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. WXGA provides the resolutions 1280 by 768 pixels. In addition, WXGA allows monitors to be non-interlaced. This ensures a better display performance and accurate color display effect.

HDTV ready

The ability to display a signal that complies with the high-resolution TV standard, which is part of the group of digital TV standards. HDTV uses the wide landscape style format similar to movie theater screens.

DCDi de-interlacing

DCDi enhances the quality of all images by eliminating the stair-step jagged edges so often seen on progressive scan displays. The result is natural images with exceptional detail.

Picture In Picture (PIP)

Provides the ability to watch simultaneously two different sources, either two video sources or a combination with data/graphics.



Trademarks owned by Royal Philips Electronics
2004 © Royal Philips Electronics - All rights reserved
As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency.
Microsoft and Windows are registered trademarks of Microsoft Corporation.
All data subject to change without notice
Release date: October 2004, v.2
www.philips.com