

Q-Line Display

- 49"
- 3840 x 2160 (4K UHD)
- Ultra HD

49BDL3050O/00

Show more

Simple, smart, sharp 18/7 display.

Turn up the stopping power with the Q-Line UHD Android display that goes big on resolution. Benefit from fast, hardware-free installation and superb picture quality. Easily display online and local content.

Benefits

Superb picture. Smooth performance

- Android SoC processor. Native and web apps
- Ultra-HD. Rich images. Stunning contrast
- IPS panel: rich color consistency from every angle

Effortless setup. Total control.

- Remote system management through CMND
- Operate, monitor and maintain with CMND & Control
- CMND & Create. Develop and launch your own content

• CMND & Deploy. Install and launch apps remotely

Cost-effective system solution

- Internal memory. Upload content for instant play
- Energy-saving automatic backlight control
- Integrated HTML5 browser. Play and control online content
- Integrated media player. Easily schedule USB content

Features

Powered by Android

Control your display via an Internet connection. Android-powered Philips Professional Displays are optimized for native Android apps, and you can

install web apps directly to the display too. A new Android OS ensures the software is kept secure and remain to the latest specification for longer.



CMND

Take control of your Philips Professional Display network. CMND lets you manage, update, maintain, and play via one easy-to-use interface. From installation to daily operation.



CMND & Deploy



tent without the need for a permanent external player. Your al display has an internal memory, which allows you to the display for instant playback. The internal memory also ons as a cache for online streaming.

Quickly install and launch any app-even when you're off-site and working

Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

CMND & Create



Take control of your content with CMND & Create. A drag-and-drop interface makes it simple to publish your own content-whether it's a daily specials board or branded corporate information. Preloaded templates and integrated widgets ensure your stills, text, and video will be up and running in no time.

Specifications

[field not found 'disclaimer_text']

Picture/Display

Diagonal screen size	48.5 inch
(inch)	
Diagonal screen size	123.2 cm
(metric)	
n i i i	2040 24

Panel resolution 3840×2160 Optimum resolution 3840 x 2160 @ 60 Hz 350 cd/m² Brightness

1200:1 Contrast ratio (typical) Response time 9 ms (typical)

16:9 Aspect ratio Viewing angle (hori-178 degree zontal) 178 degree Viewing angle

(vertical) Pixel pitch 0.27963 x0.27963 mm Display colors 1.07 Billion

Picture enhancement 3/2 - 2/2 motion pull down

3D Combfilter Progressive scan 3D MA deinterlacing

Dynamic contrast enhancement

Color Enhancement

Color Temperature Adjustment De-interlacer

Noise Reduction Smart Picture Android 5.0.1

Operating system Panel technology

Supported Display Resolution

640 x 480, 60, 72, 75Hz Computer formats

720 x 400, 70Hz $800 \times 600, 60, 75$ Hz 1024 x 768, 60, 75Hz

1280 x 768, 60Hz 1280 x 800, 60Hz 1280 x 1024, 60Hz 1360 x 768, 60Hz 1600 x 1200, 60Hz 1920 x 1080, 60Hz 3840 x 2160, 30, 60Hz 480i, 30, 60Hz 480p, 30, 60Hz 576i, 25, 50Hz 576p, 25, 50Hz

720p, 50, 60Hz 1080i, 25, 30Hz 1080p, 50, 60Hz 2160p, 30,50, 60Hz

Connectivity

Video formats

DVI-D Video input

VGA (Analog D-Sub) HDMI (x2) USB 2.0 (x2)

Audio input 3.5 mm jack Audio Left/Right (RCA) Audio output External control

RS232C (in/out) 2.5 mm jack IR (in/out) 3.5 mm jack

RJ45

Convenience

Screen saving func-

Pixel Shift, Low Brightness

Keyboard control Network controllable

Lockable LAN (RJ45) RS232 Smart Power

Energy saving func-

Placement

Landscape (18/7)

Portrait (12/7) [Portrait (12/7)]

Remote control Lockable

signal

Ease of installation Remote Control Lock

Memory

8GB eMMC Kensington lock Other convenience

VESA mount (400x400mm) Signal loop through IR Loopthrough

RS232

Tiled Matrix Up to 10×15

Dimensions

Bezel width 11.9 (Top/Left/Right) 14.4 (Bottom)

1099.2 mm Set Width Set Height 631.9 mm Set Depth 62.4 mm Set Width (inch) 43.28 inch Set Height (inch) 24.88 inch Set Depth (inch) 2.46 inch Product weight 11.4 kg Product weight (lb) 25.13 lb

Wall Mount 400 x 400 mm, M6

Operating conditions

Altitude 0 ~ 3000 m 5 ~ 40 °C Temperature range

(operation)

Temperature range -20 ~ 60 °C

(storage)

20 ~ 80 (operation),10 - 90%(storage) Relative humidity

MTBF 50,000 hour(s)

Power

100 ~ 240 VAC, 50 ~ 60 Hz Mains power 125 W

Consumption (On

mode)

Standby power <0.5W

consumption

Power Saving Smart Power

Features

Sound

Built-in speakers $2 \times 10W$ RMS

Accessories

Included accessories AC Power Cord

RS232 cable Quick start guide IR sensor cable (1.8M) Batteries for remote control

Remote Control Optional accessories Table top stand

Included Accessories RS232 daisy-chain cable USB Cover and screw x1 Stand BM05923/BM02542/BM05922

Multimedia Applications

USB Playback Video ASF

AVI DAT FLV MKV MP4 MPEG MPG TS VOB **WEBM**

WMV

USB Playback Picture BMP

IPEG JPG

PNG

USB Playback Audio AAC

M4A MP3 **WMA**

Miscellaneous

Warranty On-Screen Display

Languages

3 year warranty Arabic

Simplified Chinese

Traditional Chinese

English French German Italian Polish Russian Spanish . Turkish Japanese Czech Danish Dutch Finnish Norwegian Portuguese

Regulatory approvals CE

UL/cUL СВ FCC, Class B **BSMI** CCC EAC **EMF** EnergyStar 7.0

Swedish

PSB CECP

Internal Player

Storage 8GB eMMC

CPU ARM Quad-core processor

Memory 2GB DDR3



data subject to change 2023, June 18

Version: 12.1.2 EAN: 8712581743635 © 2023 Koninklijke Philips N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com