

Philips LCD monitor

V Line 20 (19.5" / 49.5 cm diag.)

203V5LSB2

Great LED images in vivid colors

Enjoy vivid LED pictures on this Philips display. Essential features like SmartContrast that ensures rich bright images makes it a great choice!

Great choice

- Compact design saves space
- Mercury Free eco-friendly display
- VESA mount allows for flexibility

Vivid pictures every time

• LED technology for vivid colors



Highlights

LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of LCD backlight, resulting in super high contrast ratio. It also gives superior color reproduction thanks to consistent brightness across the screen.

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

Compact design saves space

Compact design saves space

VESA mount

VESA mount allows for flexibility



Specifications

Connectivity

- Signal Input: VGA (Analog)
- Sync Input: Separate Sync

Picture/Display

- Panel Size: 19.5 inch / 49.5 cm
- Aspect ratio: 16:9
- LCD panel type: TFT-LCD
- Backlight type: W-LED system
- Pixel pitch: 0.26 x 0.26 mm
- Optimum resolution: 1600 x 900 @ 60 Hz
- Brightness: 200 cd/m²
- Display colors: 16.7 M
- Contrast ratio (typical): 600:1

- Response time (typical): 5 ms
 Viewing angle: 90° (H) / 65° (V), @ C/R > 10
 Effective viewing area: 433.9 (H) × 236.3 (V)
- Scanning Frequency: 30 -83 kHz (H) / 56 -75 Hz (V) sRGB

Convenience

- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 7, Windows 8
- User convenience: Power On/Off
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
- Other convenience: Kensington lock, VESA mount (100x100mm)

Stand

• Tilt: -3/10 degree

Power

• Power supply: Built-in, 100-240VAC, 50-60Hz

- Off mode: 0.5 W (typ.)
- On mode: 14.52 W (typ.) (EnergyStar 6.0 test method)
- Standby mode: 0.5 W (typ.)
- Power LED indicator: Operation White, Standby mode- White (blinking)

Dimensions

- Product with stand (mm): 465 x 345 x 170 mm
- Packaging in mm (WxHxD): 503 x 350 x 109 mm
- Product without stand (mm): 465 x 285 x 48 mm

Weight

- Product with packaging (kg): 3.23 kg
- Product with stand (kg): 2.33 kg
- Product without stand (kg): 2.03 kg

Operating conditions

- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- Temperature range (operation): 0°C to 40°C °C
- MTBF: 30,000 hour(s)
- Relative humidity: 20%-80 %
- Temperature range (storage): -20°C to 60°C °C

Sustainability

- Environmental and energy: RoHS, Mercury Free
- Recyclable packaging material: 100 %

Compliance and standards

 Regulatory Approvals: BSMI, CE Mark, FCC Class B, GOST, SEMKO, TUV/ISO9241-307, cETLus, WEEE

Cabinet

- Color: Black
- Finish: Hairline (front bezel) / Texture (rear cover)

Issue date 2024-03-23 © 2024 Koninklijke Philips N.V. All Rights reserved. Version: 6.0.1 Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

> EAN: 87 12581 75134 0 www.philips.com

203V5LSB2/89