PIELDS

Philips LCD monitor with LED backlight

V Line 15.6" / 39.6 cm

163V5LSB23

# Great LED images in vivid colours

Enjoy vivid LED pictures on this Philips display. Compact design and VESA mount give your workspace flexibility. It's a great choice!

#### Vivid pictures every time

• LED technology for vivid colours

#### **Great choice**

- Compact design saves space
- VESA mount allows for flexibility
- Mercury Free eco-friendly display



## Specifications

#### Picture/Display

- LCD panel type: TFT-LCD
- Backlight type: W-LED system
- Panel Size: 15.6 inch/39.6 cm
- Effective viewing area: 344.2 (H)  $\times$  193.5 (V)
- Aspect ratio: 16:9
- Optimum resolution: 1366 x 768 @ 60 Hz
- Response time (typical): 12 ms
- Brightness: 220 cd/m<sup>2</sup>
- Contrast ratio (typical): 500:1
- Pixel pitch: 0.252 x 0.252 mm
- Viewing angle:  $90^{\circ}$  (H) /  $60^{\circ}$  (V), @ C/R > 10
- Display colours: 262 K
  Scapping Englished 20 (
- Scanning Frequency: 30-60 kHz (H) / 58-62 Hz (V) • sRGB

#### Connectivity

- Signal Input: VGA (Analogue)
- Sync Input: Separate Sync, Sync on Green

#### Convenience

- User convenience: Power On/Off
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Turkish, Traditional Chinese, Ukrainian
- Other convenience: Kensington lock
- Plug and Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7

#### Stand

• Tilt: -3/10 degree





#### Power

- On mode: 6.97 W (typ.)
- Standby mode: 0.5 W
- Off mode: 0.5 W
- Power LED indicator: Operation White, Standby mode White (flashing)
- Power supply: Built-in, 100-240 VAC, 50-60 Hz

#### Dimensions

- Product with stand (mm): 375 x 300 x 141 mm
- Product without stand (mm): 375 x 233 x 47 mm
- Packaging in mm (W x H x D): 432 x 301 x 108 mm

#### Weight

- Product with stand (kg): 0.94 kg
- Product without stand (kg): 0.79 kg
- Product with packaging (kg): 1.74 kg

#### **Operating conditions**

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%–80% %
- Altitude: Operation: +12,000 ft (3658 m), Non-
- operation: +40,000 ft (12,192 m)
- MTBF: 30,000 hour(s)

#### Sustainability

- Environmental and energy: RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

#### Cabinet

- Colour: Black
- Finish: Hairline (front bezel)/Texture (rear cover)



### 163V5LSB23/57

## Highlights

#### LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content, which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of the LCD backlight, resulting in a super high contrast ratio. It also gives superior colour reproduction thanks to consistent brightness across the screen.

#### **Mercury Free**

Philips monitors with LED backlighting are free from Mercury, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its lifecycle, from manufacturing to disposal.

HILIPS	Issue date 2020-07-17	© 2020 Koninklijke Philips N.V. All Rights reserved.
	Version: 12.0.1	Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.
Ŧ	12 NC: 8670 001 03118 EAN: 87 12581 68811 0	www.philips.com