

Philips Signage Solutions
Q-Line Display

49"

3840 x 2160 (4K UHD)
Ultra HD

50BDL3050Q



Intensify your signage experience

With priceless performance

Deliver startlingly clear images in a more eco-friendly way with the Q-Line display. High on performance and reliability, yet low on power consumption, it is ideal for projects where no compromise is accepted.

Optimized for public viewing

- 4K Ultra HD: resolution like you've never seen it before

Innovative solutions for any signage application

- Connect and control your content via the cloud with HTML5
- Schedule what you want, when you want with SmartPlayer
- Android: Run your own app or choose your favorite app to run
- CMND: Take control of your displays
- Create and update content with CMND & Create

Care about you, your business and your audience

- SmartPower for energy saving
- Manage settings of multiple displays with CMND & Control

PHILIPS

Q-Line Display
49" 3840 x 2160 (4K UHD), Ultra HD

Highlights

4K Ultra HD Resolution

See your Signage Solutions like never before thanks to four times the resolution of a conventional Full HD display. 3840 x 2160 pixels provide an image so refined, so lifelike, it's a window to a new world.

Powered by Android


With Android OS integrated into the display, you can work with the most developed OS on the planet and save your own app directly into the display. Or, choose from the large library of Android apps and play content from there. With the built-in scheduler, you can daypart your apps and content based on your customer and time of day and with the auto orientation feature, showing content in portrait or landscape is as simple as turning the display.

CMND & Control



With CMND & Control, easily manage multiple displays in a central location. With real time display monitoring, setting and software updates from a remote location, and the ability to customize and configure multiple displays at once, such as video wall or menu board displays, controlling your suite of displays has never been easier.

CMND



A robust display management platform, CMND puts the power back into your hands. Update and manage content with CMND & Create or control your settings with CMND & Control. It's all possible with CMND.

CMND & Create



Design and create compelling content with CMND & Create, a powerful authoring tool. With a drag and drop interface, preloaded templates, and integrated widgets, you'll be able to amaze your customers with compelling content. Available in portrait and landscape mode.

SmartBrowser



Connect and control your content via the cloud with the integrated HTML5 browser.

50BDL3050Q/75


Design your signage content online and connect it with a display or with your complete network. Simply plug in a RJ45 internet cable for network connection, connect the display with the dedicated url-address and you are ready to play your cloud based content.

SmartPlayer



Turn your USB into a true cost effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on screen menu, and enjoy your own created playlists anytime, anywhere.

SmartPower



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.



Specifications

Connectivity

- Audio output: Audio Left/Right (RCA)
- Video input: DVI-D, VGA (Analog D-Sub), HDMI (x2), USB 2.0 (x2)
- Audio input: 3.5 mm jack
- External control: RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack, RJ45

Picture/Display

- Diagonal screen size (metric): 125.73 cm
- Diagonal screen size (inch): 49.5 inch
- Aspect ratio: 16:9
- Panel resolution: 3840 x 2160
- Pixel pitch: 0.2854 x 0.2854 mm
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 350 cd/m²
- Display colors: 1.07 Billion
- Contrast ratio (typical): 4000:1
- Response time (typical): 8 ms
- Viewing angle (horizontal): 178 degree
- Viewing angle (vertical): 178 degree
- Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, Progressive scan, 3D MA deinterlacing, Dynamic contrast enhancement, Color Enhancement, Color Temperature Adjustment, De-interlacer, Noise Reduction, Smart Picture
- Panel technology: AMVA
- Operating system: Android 5.0.1

Convenience

- Placement: Landscape (18/7)
- Tiled Matrix: Up to 10 x 15
- Screen saving functions: Pixel Shift, Low Brightness
- Keyboard control: Lockable
- Remote control signal: Lockable
- Signal loop through: IR Loophthrough, RS232
- Ease of installation: Remote Control Lock
- Energy saving functions: Smart Power
- Other convenience: Kensington lock, VESA mount (400x400mm)
- Network controllable: LAN (RJ45), RS232
- Memory: 8GB eMMC

Sound

- Built-in speakers: 2 x 10W RMS

Power

- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- Consumption (On mode): 128 W
- Consumption (Typical): 140 W
- Consumption (Max): 180 W
- Standby power consumption: <0.5W
- Power Saving Features: Smart Power

Supported Display Resolution

- Computer formats: 1280 x 768, 60Hz, 1280 x 800, 60Hz, 1360 x 768, 60Hz, 1280 x 1024, 60Hz, 720

- x 400, 70Hz, 1024 x 768, 60, 75Hz, 800 x 600, 60, 75Hz, 1600 x 1200, 60Hz, 1920 x 1080, 60Hz, 640 x 480, 60, 72, 75Hz, 3840 x 2160, 30, 60Hz
- Video formats: 720p, 50, 60Hz, 1080p, 50, 60Hz, 1080i, 25, 30Hz, 480i, 30, 60Hz, 576i, 25, 50Hz, 480p, 30, 60Hz, 576p, 25, 50Hz, 2160p, 30, 50, 60Hz

Dimensions

- Set Width: 1123.6 mm
- Product weight: 12.8 kg
- Set Height: 646.7 mm
- Set Depth: 67.8 mm
- Set Width (inch): 44.24 inch
- Set Height (inch): 25.5 inch
- Wall Mount: 400 x 400 mm, M6
- Set Depth (inch): 2.67 inch
- Bezel width: 11.8 (Top/Left/Right) 14.3 (Bottom) mm
- Product weight (lb): 28.16 lb

Operating conditions

- Altitude: 0 ~ 3000 m
- Temperature range (operation): 0~ 40 °C
- MTBF: 50,000 hour(s)
- Relative humidity: 20 ~ 80% (operation), 5 - 95%(storage) %
- Temperature range (storage): -20 ~ 60 °C

Multimedia Applications

- USB Playback Video: MKV, MP4, MPEG, MPG, TS, VOB, WMV, ASF, AVI, DAT, FLV, WEBM
- USB Playback Picture: BMP, JPEG, JPG, PNG
- USB Playback Audio: AAC, M4A, MP3, WMA

Internal Player

- CPU: ARM Quad-core processor
- Memory: 2GB DDR3
- Storage: 8GB eMMC

Accessories

- Included accessories: AC Power Cord, RS232 cable, Batteries for remote control, Quick start guide, Remote Control, IR sensor cable (1.8M)
- Included Accessories: RS232 daisy-chain cable
- Stand: BM05923/BM02542/BM05922

Miscellaneous

- On-Screen Display Languages: Arabic, Simplified Chinese, Traditional Chinese, English, French, German, Italian, Polish, Russian, Spanish, Turkish, Japanese, Czech, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish
- Warranty: 3 year warranty
- Regulatory approvals: CE, UL/cUL, CB, FCC, Class B, BSMI, CCC, EAC, EMF, EnergyStar 7.0, PSB, CEC



Issue date 2024-03-24

Version: 5.0.1

EAN: 87 12581 75219 4

© 2024 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com