



Electronic paper display

- 3000 series
- 13 (13.3" / 33.8 cm diag.)
- 1200 x 1600 (UXGA)

13B1K3300/89

Read easier on your screen

with ePaper display

Philips ePaper display delivers a comfortable viewing experience for extended reading sessions. Featuring a reflective display with no blue light and versatile connectivity. Designed for eco-consciousness and sustainability.

Benefits

[ePaper display: Read in comfort for long periods](#)

- Paper-like experience for ultimate reading comfort
- Features like anti-glare to ensure eye strain reduction
- On-screen menu for setting viewing mode preferences

[Features designed for you](#)

- SmartConnect with HDMI, DisplayPort and USB-C connections
- SmartRemote menu allows easy control to view your content

- SmartErgoBase enables people-friendly ergonomic adjustments

[Greener everyday](#)

- Environmentally sustainable and user-friendly packaging
- Low power consumption saves energy bills

PHILIPS

Business Monitor

Features

Electronic paper display




The Philips ePaper display protects your eyes and the environment. With E Ink technology, content displays like paper without emitting a harsh backlight. Work longer without eye fatigue or headaches caused by conventional flickering, backlit LCD monitors. The features of anti-glare, no flickering and no blue light help avoid eye strain. Ultra-low power consumption and paperless display are designed to meet suitability goals.

SmartConnect



Philips displays come equipped with multiple connections such as USB-C, DisplayPort and HDMI connector, enabling you to enjoy high resolution uncompressed video and audio content.

SmartRemote software*



The new SmartRemote software by Philips allows you to control your ePaper monitor via an easy-to-use on-screen menu. You can drag files into the tool window, search content, zoom in, zoom out, and switch pages. Reduce distractions by displaying just what you need. Go to Philips website support page to download the latest App version.

SmartErgoBase



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base can swivel, tilt and rotate to various angles to ensure maximum comfort. The height adjustable stand guarantees the optimal viewing level, reducing the physical strains of a long workday, while cable management reduces cable clutter and keeps the workspace neat and professional.

Eco-Friendly Packaging



This model uses 100% recyclable packaging, using no Styrofoam at all. Additionally, in consideration for people and time, the packaging is easy to remove.

Specifications

[field not found 'disclaimer_text']

Picture/Display

Monitor Panel Type	EPD
Panel Size	13.3 inch / 33.8 cm
Display Screen	Anti-Glare, 3H, Haze 15%
Coating	
Effective viewing area	278.4 (H) x 202.8 (V)
Aspect ratio	3:4
Optimum resolution	1200 x 1600
Pixel Density	150 PPI
Pixel pitch	0.169 x 0.169 mm
Display colors	4 bits grey scale

Connectivity

Signal Input	DisplayPort 1.2 x 1, HDMI 1.4 x 1, USB-C x 1 (DP Alt mode, Power Delivery)
HDCP	HDCP 1.4 (HDMI / DisplayPort / USB-C)
Audio (In/Out)	Audio out
Sync Input	Separate Sync

Power Delivery

Version	USB PD version 3.0
USB-C (output)	up to 15W (5V/3A)
USB-C (input)	up to 65W (5V/3A, 7V/3A, 9V/3A, 10V/3A, 12V/3A, 15V/3A, 20V/3.25A)

Convenience

User convenience	Clear Front light Mode Level Menu/Power Brazil Portuguese Czech Dutch English Finnish French German Greek Hungarian Italian
OSD Languages	

Business Monitor

	Japanese		
	Korean		
	Polish		
	Portuguese		
	Russian		
	Simplified Chinese		
	Spanish		
	Swedish		
	Traditional Chinese		
	Turkish		
	Ukrainian		
Other convenience	Kensington lock		
	VESA mount (100x100mm)		
Plug & Play Compatibility	Front light (White / Warm)		
	DDC/CI		
	Mac OS X		
	sRGB		
	Windows 11 / 10 / 8.1 / 8		
Stand			
Height adjustment	100 mm		
Pivot	-/+90		
Swivel	-/+180 degree		
Tilt	-5/25 degree		
Power			
On mode	6.5 W (typ.)		
Standby mode	0.4 W (typ.)		
Off mode	0.3 W (typ.)		
Power LED indicator	Operation - White		
	Standby mode- White (blinking)		
Power supply	External		
	100-240VAC, 50-60Hz		
Dimensions			
Product with stand(max height)	247 x 482 x 172 mm		
Product without stand (mm)	247 x 324 x 23 mm		
Packaging in mm (WxHxD)	390 x 420 x 159 mm		
Weight			
Product with stand (kg)	1.85 kg		
Product without stand (kg)	1.06 kg		
Product with packaging (kg)	3.96 kg		
Operating conditions			
Temperature range (operation)	0°C to 40 °C		
Temperature range (storage)	-20°C to 60 °C		
Relative humidity	20%-80 %		
Altitude	Operation: +12,000ft (3,658m), Non-operation: +40,000ft (12,192m)		
Sustainability			
Environmental and energy	RoHS		
Recyclable packaging material	100 %		
Specific Substances	Mercury free		
	PVC / BFR free housing		
Compliance and standards			
Regulatory Approvals	CB		
	CCC		
	CE Mark		
	FCC Class B		
	ICES-003		
	cETLus		
Cabinet			
Front bezel	Black		
Rear cover	Black		
Foot	Black		
Finish	Texture		

* The SmartRemote app is solely compatible with operating systems Windows 10 and above and it is currently not compatible with macOS.

* For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mode

* Activities such as screen sharing, on-line streaming video and audio over the Internet can impact your network performance. Your hardware, network bandwidth and its performance will determine overall audio and video quality.

* For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details.

* The monitor may look different from feature images.



data subject to change
2023, June 18

Version: 2.0.1
EAN: 8712581800864

© 2023 Koninklijke Philips N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com