

16 (15.6"/39.6 cm diag.) 1920 x 1080 (Full HD)

16B1P3302D



Performance, adaptability, work on the go

This monitor is portable, lightweight and perfectly suited for improving workflow productivity when travelling. While on the road, the Dual USB-C feature facilitates sharing and presenting material or running a multi-screen setup.

Features designed for you

- LowBlue mode and Flicker-free easy-on-the eyes viewing
- EasyRead mode for a paper-like reading experience

Great performance

- IPS LED wide view technology for image and colour accuracy
- SmartImage pre-sets for easy optimised image settings
- 16:9 Full HD display for crisp, detailed images

Productivity on the go

- Continuous tilt stand to fit your viewing needs
- Lightweight and foldable design for portability
- Dual USB-C: For ultimate connectivity

Highlights

Dual USB-C

This feature is geared toward those who are looking for a product that facilitates productivity. This monitor showcases two ports on the side of the monitor where each USB-C cord can be plugged in and then used simultaneously for multiple purposes; such as, but not limited to: charging, presenting and as an add-on to a dual screen setup.

Multi-angle stand




Our continuous tilt stand bends from 0 to 90 degrees with the kind of flexibility to allow you to get comfortable anywhere you need to keep up with your work.

Performance, adaptability



Enjoy a clean, portable, dual-screen workstation. The soft, smooth, pliable USB-C cable is designed to be easy to carry and fit in any bag.

IPS technology



IPS displays use an advanced technology which gives you extra-wide viewing angles of 170/170 degrees, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colours, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand colour accuracy and consistent brightness at all times.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 x 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colours, expect a true-to-life picture.

Smartimage



SmartImage is an exclusive leading edge Philips technology that analyses the content displayed on your screen and optimises your display

performance. This user-friendly interface allows you to select various modes, like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimises the contrast, colour saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time at the touch of a single button!

LowBlue Mode and Flicker-free



Our LowBlue Mode and Flicker-free technology have been developed to reduce eye strain and fatigue often caused by long hours in front of a monitor.

EasyRead mode



EasyRead mode for a paper-like reading experience

















ie Mode USB-C

Portable monitor 16B1P3302D/00

Specifications

Picture/Display

Panel Size: 15.6 inch/39.6 cm

Aspect ratio: 16:9

LCD panel type: IPS technology Backlight type: W-LED system Pixel pitch: 0.17925 x 0.17925 mm

Brightness: 250 cd/m²

Display colours: 16.2 M (6 bit + FRC)

Colour gamut (typical): NTSC 46%*, sRGB 64%*

Contrast ratio (typical): 700:1 SmartContrast: 50,000,000:1

Response time (typical): 4 ms (Grey to Grey)* Viewing angle: 170° (H)/170° (V), @ C/R > 10

Picture enhancement: SmartImage Maximum resolution: 1920 x 1080 @ 75 Hz Effective viewing area: 344.16 (H) x 193.59 (V) Scanning Frequency: Landscape mode: 30-85 kHz (H)/48-75 Hz (V); Portrait mode: 30-150

kHz (H)/48-75 Hz (V)

sRGB Flicker-free Pixel Density: 141 PPI

LowBlue Mode

Display Screen Coating: Anti-Glare, 3H, Haze

25% EasyRead

Connectivity

Signal Input: USB-C x 2 (DP Alt mode, Data,

Power delivery)

Sync Input: Separate Sync Audio (In/Out): Audio out

HDCP: HDCP 1.4 (USB-C), HDCP 2.2 (USB-C)

Power Delivery

Version: PD version 3.0

USB-C (input): Up to 90 W (5 V/3 A, 7 V/3 A, 9 V/3 A, 10 V/3 A, 12 V/3 A, 15 V/3 A,

20 V/4.5 A)

USB-C (output): Up to 65 W (5 V/3 A, 7 V/3 A, 9 V/3 A, 10 V/3 A, 12 V/3 A, 15 V/3 A,

20 V/3.25 A)

Convenience

Plug and Play Compatibility: DDC/CI, Mac OS X,

sRGB, Windows 11/10/8.1/8

User convenience: SmartImage, Input, Menu,

Power On/Off

OSD Languages: Brazil Portuguese, Czech, Dutch, English, French, Finnish, German, Greek, Hungarian, Italian, Japanese, Korean, Portuguese, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish,

Other convenience: VESA mount: Yes*
Control software: SmartControl

Stand

Pivot: 90 degree Tilt: 0 ~ 90 degree

Power

ECO mode: 4.4 W Off mode: 0.3 W

On mode: 6.2 W (EnergyStar test method)

Standby mode: 0.5 W

Power LED indicator: Operation - White, Standby

mode - White (flashing)
Energy Label Class: C

Dimensions

Packaging in mm (W x H x D): 404 x 281 x 103 mm Product with stand (max height): 359 x 232 x 119 mm

Weight

Product with packaging (kg): 2.08 kg Product with stand (kg): 1.03 kg

Operating conditions

Altitude: Operation: +12,000 ft (3658 m), Non-

operation: +40,000 ft (12,192 m)

Temperature range (operation): 0°C to 40 °C

Relative humidity: 20%-80 %

Temperature range (storage): -20°C to 60 °C MTBF (demonstrated): 70,000 hrs (excluded

backlight)

Sustainability

Environmental and energy: EnergyStar 8.0,

EPEAT*, RoHS

Post-consumer recycled plastic: 60% Recyclable packaging material: 100 %

Specific Substances: Mercury free, PVC/BFR free

housing

Compliance and standards

Regulatory Approvals: CB, TUV/GS, TUV Ergo, CU-EAC, EAEU ROHS, CE Mark, FCC Class B, ICES-003, cETLus

Cabinet

Finish: Texture Foot: Black Front bezel: Black Rear cover: Black

What's in the box?

Cables: USB-C to C/A Y cable

Monitor with stand
User Documentation
Accessory: Protective case

- * Response time value equal to SmartResponse
- * NTSC Area based on CIE 1976
- * sRGB Coverage based on CIE1931
- * For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mode
- * For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details.
- * This monitor is powered through the USB port. Please refer to user manual for more information. * For VESA mounts, please refer to "VESA Mounting" in user
- manual for more information.
 * EPEAT rating is valid only where Philips registers the
- PEAI rating is valid only where Philips registers th product. Please visit https://www.epeat.net/ for registration status in your country.
- * The monitor may look different from feature images.

© 2025 Koninklijke Philips N.V. All Rights reserved. Issue date 2025-04-28 Version: 2.3.1

EAN: 87 12581 79952 6

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

