

Philips Monitor LCD monitor

5000 series

24 (23.8" / 60.5 cm diag.) 1920 x 1080 (Full HD)

24E1N5300HE

Collaboration simplified

with built-in webcam

This Philips monitor is designed for the remote work environment. The integrated 5MP webcam delivers sharp images, and noise cancelling mic helps people hear you loud and clear.

Features designed for you

- EasySelect menu toggle key for quick on-screen menu access
- Built-in stereo speakers for multimedia
- Cable management reduces cable clutter for neat workspace
- LowBlue mode and Flicker-free easy-on-the eyes viewing
- Tilt, pivot and height-adjust for an ideal viewing position
- Connect your notebook with one USB-C cable

Superb Picture Quality

- 16:9 Full HD display for crisp detailed images
- · IPS LED wide view technology for image and color accuracy
- Effortlessly smooth gameplay with AMD FreeSync $^{\rm TM}$ technology




Highlights

USB-C connection



This Philips display features a USB type-C connector with power delivery. With intelligent and flexible power management, you can power charge your compatible device directly. Its slim, reversible USB-C allows for easy, one-cable connection. You can watch high resolution video and transfer data at a super-speed, while powering up and recharging your compatible device at the same time.

IPS technology



IPS displays use an advanced technology which gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colors, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand color accuracy and consistent brightness at all times.

Ultra-smooth gaming



Gaming shouldn't be a choice between choppy gameplay or broken frames. With the new Philips monitor it doesn't have to be. Get fluid, artifact-free performance at virtually any framerate with AMD FreeSync™ technology, smooth quick refresh and ultra-fast response

Built-in stereo speakers



A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

LowBlue Mode & Flicker-free



Our LowBlue Mode and Flicker-free technology have been developed to reduce eye strain and fatigue often caused by long hours in front of a monitor.

Compact Ergo Base



The Compact Ergo Base is a people-friendly Philips monitor base that tilts, pivot and height-adjusts so each user can position the monitor for maximum viewing comfort and efficiency.

EasySelect Menu Toggle Key



The discreetly placed EasySelect Menu Toggle Key allows you to make quick and easy adjustments to monitor settings in the On-Screen Display menu.

Cable management



Cable management is an intimate design that maintains tidy workspace by organizing cables and wires required for the operation of a display device.



















Specifications

Picture/Display

• Panel Size: 23.8 inch / 60.5 cm

• Aspect ratio: 16:9

· LCD panel type: IPS technology

Backlight type: W-LED system

• Pixel pitch: 0.2745 x 0.2745 mm

• Brightness: 300 cd/m²

• Display colors: 16.7 M

• Color gamut (typical): NTSC 104.8%*, sRGB 120.9%

• Contrast ratio (typical): 1000:1

SmartContrast: Mega Infinity DCR

• Response time (typical): 4 ms (Gray to Gray)*

• Viewing angle: 178° (H) / 178° (V), @ C/R > 10

• Picture enhancement: SmartImage game

Maximum resolution: 1920 x 1080 @ 75 Hz*

Effective viewing area: 527.04 (H) x 296.46 (V)

 Scanning Frequency: 30 - 85 kHz (H) / 48 - 75 Hz (V)

• sRGB

• Flicker-free

• Pixel Density: 92.56 PPI

LowBlue Mode

• Display Screen Coating: Anti-Glare, 3H, Haze 25%

MPRT: 1 ms

EasyRead

AMD FreeSync™ technology

Connectivity

• Signal Input: HDMI 1.4 x 1, DisplayPort 1.2 x 1, USB-C 3.2 Gen 1 x 1 (upstream, Power Delivery up to 65W)

• Sync Input: Separate Sync

• Audio (In/Out): Audio out

 USB:: USB 3.2 x 4 (downstream with 1 fast charge B.C 1.2)

• Power delivery: USB PD version 3.0

· Super speed: Data and Video transfer

• DP: Built-in Display Port Alt mode

• USB-C max. power delivery: Up to 65W (5V/3A, 9V/3A, 10V/3A, 12V/3A, 15V/3A, 20V/3.25A)

• USB-C: Reversible plug connector

Convenience

• Built-in Speakers: 5 W x 2

• Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7

• User convenience: Power On/Off, Menu, Volume, Input, SmartImage Game

• OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish,

Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian

• Other convenience: Kensington lock, VESA mount (100x100mm)

• Built-in webcam: 5.0 megapixel camera with microphone and LED indicator

Noise cancellation

Stand

· Height adjustment: 130 mm

• Pivot: -/+ 90 degree

• Tilt: -5/20 degree

• Power supply: External, 100-240VAC, 50-60Hz

• Off mode: 0.3 W (typ.)

• On mode: 24.2 W (typ.)

• Standby mode: 0.5 W (typ.)

 Power LED indicator: Operation - White, Standby mode- White (blinking)

Dimensions

• Packaging in mm (WxHxD): 600 x 526 x 143 mm

• Product without stand (mm): 540 x 336 x 43 mm

• Product with stand(max height): $540 \times 494 \times$ 198 mm

Weight

• Product with packaging (kg): 7.65 kg

• Product with stand (kg): 4.37 kg

• Product without stand (kg): 2.71 kg

Operating conditions

 Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)

ullet Temperature range (operation): 0 to 40 $^{\circ}$ C

• MTBF: 50,000 hrs (excluding backlight) hour(s)

• Relative humidity: 20%-80 %

• Temperature range (storage): -20 to 60 °C

Sustainability

· Environmental and energy: RoHS

• Recyclable packaging material: 100 %

· Specific Substances: Mercury free, PVC / BFR free housing

Compliance and standards

 Regulatory Approvals: CB, CE Mark, CU-EAC, EAEU RoHS, FCC Class B, ICES-003, TUV/ ISO9241-307, TUV-BAUART

Cabinet

· Color: Black

• Finish: Textured

* "IPS" word mark / trademark and related patents on technologies belong to their respective owners.

The maximum resolution works for either HDMI input or DP input. * For best output performance, please always ensure that your graphic card is capable of achieving the maximum resolution and refresh rate of this Philips display.

Response time value equal to SmartResponse

* MPRT is to adjust brightness for blur reduction, so cannot adjust brightness while MPRT is turned on. To reduce motion blur, LED backlight will strobe synchronously with screen refresh, which may

* MPRT is gaming-optimized mode. Turn on MPRT may cause noticeable screen flickering. It is recommended to turn off when you

are not using the gaming function.

* NTSC Area based on CIE1976

* sRGB Area based on CIE1931

* 2020 Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, AMD FreeSync™ and combinations thereof are trademarks of Advanced Micro Devices, Inc. Other product names used in this publication are for identification purposes only and may

be trademarks of their respective companies.

* For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mode

For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more

* The monitor may look different from feature images.



Issue date 2024-11-20

Version: 4.4.1

© 2024 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 79780 5 www.philips.com