

Philips Signage Solutions Q-Line Display

32"
Direct LED Backlight

SignageSolutions

BDL3230QL

Intensify your signage experience

with priceless smart performance

Deliver startlingly clear images in a more eco-friendly way. High on performance and reliability, yet low on power consumption, it is ideal for projects where there is no room for compromise.

Care about you, your business and your audience

- SmartPower for energy saving
- Show clinical images consistently with D-image

Maximising the impact of your message

- Manage and control your network remotely via SmartControl
- Full HD LED for brilliant images with incredible contrast

Innovative solutions for any signage application

- Connect and control your content via the cloud with HTML5
- Schedule what you want, when you want with SmartPlayer
- Free and easy-to-use content management with SmartCMS
- · Save and play content with internal memory



Highlights

SmartPower



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

SmartControl



SmartControl lets you remotely control and manage your network of displays via RJ45 and RS232C. Easily fine-tune all display settings including resolution, brightness, contrast and cloning of your settings over your complete network.

SmartBrowser



Connect and control your content via the cloud with the integrated HTML5 browser. Design your signage content online and connect it with a display or with your entire

network. Simply plug in a RJ45 Internet cable for network connection and connect the display with the dedicated URL address, and you are ready to play your cloud-based content.

SmartPlayer

Turn your USB into a true cost-effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on-screen menu, and enjoy your own playlists anytime, anywhere.

SmartCMS



Free and easy-to-use content management system that works exclusively with Philips Signage Solutions displays to manage your digital signage content. With SmartCMS you can create and schedule your own content over 24 hours every day. Simply create your network, design your content and schedule your playlist, and you are ready to play!

Full HD LED technology

Picture Quality matters. Standard displays deliver quality, but you expect more. Imagine crisp detail paired with high brightness, incredible contrast and realistic colours for a true-to-life picture.

Clinical D-image



D-image helps you to review and diagnose clinical images with consistent and accurate display performance. To achieve reliable clinical interpretations, our professional displays are factory calibrated to give optimised greyscale standard display performance. D-image helps you to excel in every aspect of patient care.

Internal Memory

Save and play content with internal memory. Upload your media into the display and playback content immediately. Working in conjunction with the internal browser, it also serves as a memory cache when streaming online content. If the network ever fails, the internal memory keeps content running by playing a cached version of the content, ensuring that your media stays up even if the network goes down.













Specifications

Picture/Display

- Diagonal screen size: 31.5 inch / 80 cm
- Panel resolution: 1920 x 1080p
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 350 cd/m²
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Aspect ratio: 16:9
- Viewing Angle (H / V): 178 / 178 degree
- Pixel pitch: 0.36375 x 0.36375 mm
- Display colours: approximately 16.77 million
- DICOM: Clinical D-image
- · Contrast ratio (typical): 1400:1

Supported Display Resolution

Computer formats

Resolution	Refresh rate
640×480	60, 67, 72, 75 Hz
800×600	56, 60, 72, 75 Hz
1024×768	60 Hz
1280×768	60 Hz
1280×800	60 Hz
1360×768	60 Hz
1366 x 768	60 Hz
1440×900	60 Hz
1600 x 1200	60 Hz
1920 x 1080	60 Hz
1920 x 1200	60 Hz

Video formats

Resolution	Refresh rate
480i	60 Hz
480p	60 Hz
576p	50 Hz
576i	50 Hz
720p	50, 60 Hz
1080i	50, 60 Hz
1080 _D	50, 60 Hz

Connectivity

- Video input: DVI-D, HDMI, VGA (Analogue D-Sub), Component (RCA), Composite (RCA)
- Audio input: 3.5-mm jack, Audio Left/Right (RCA)
- Audio output: Audio Left/Right (RCA)
- External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack
- Other connections: USB

Convenience

• Tiled Matrix: Up to 15 x 15

- Screen-saving functions: Pixel Shift
- Signal Loop Through: RS232, IR Loop through
- · Energy-saving functions: Smart Power
- Network controllable: RS232, RJ45, One Wire (HDMI-CEC)
- · Keyboard control: Hidden, Lockable
- Memory: 8 GB eMMC, Internal memory access
- Start-up: Switch on delay, Switch on status, Wake up on LAN
- Start-up window: enable/disable Philips logo

Dimensions

- Set dimensions (W x H x D): 726.5 x 425.4 x 63.6 mm
- Set dimensions in inch (W x H x D): $28.6 \times 16.75 \times 2.5$ inch
- Bezel width: 11.9 (TLR)/17.2 (B) mm
- VESA Mount: 100 x 100 mm, 200 x 200 mm, M4
- Product weight: 5.20 kg
- Product weight (lb): 14.74 lb

Operating conditions

- Temperature range (operation): 5 ~ 40 °C
- Temperature range (storage): -20 ~ 60 °C
- Relative humidity: 20 ~ 80 %
- MTBF: 50,000 hour(s)

Power

- Consumption (On mode): 57 W (EnergyStar 6.0 test method)
- Standby power consumption: <0.5 W
- Mains power: 100 ~ 240 VAC

Sound


• Built-in speakers: 2 x 10 W RMS


Accessories

- Included accessories: Remote Control, Batteries for remote control, AC Power Cord, VGA cable, RS232 cable, Quick start guide, Warranty Leaflet
- Stand: BM02541(Option)

Miscellaneous

- On-Screen Display Languages: English, French, German, Italian, Japanese, Polish, Russian, Spanish, Simplified Chinese, Turkish, Traditional Chinese
- Regulatory approvals: CE, UL/cUL, CCC, C-Tick, CB, BSMI, EPA, CECP, GOST
- Warranty: 3-year warranty







Issue date 2022-05-18

© 2022 Koninklijke Philips N.V. All Rights reserved.

Version: 3.2.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 33964 EAN: 87 12581 73727 6

www.philips.com

Multimedia Applications

- USB Playback Video: 3G2, 3GP, ASF, ASX, AVI, DAT, DivX, F4V, FLV, M2TS, M4V, MK3D, MKV, MOV, MP4, MPE, MPEG, MPG, MTS, QT, TRP, TS, TTS, VOB, WEBM, WMV, Xvid
- USB Playback Picture: BMP, GIF, JPEG, JPG
- USB Playback Audio: AAC, AC3, AIF, AIFF, AMR, EC3, M4A, MP3, OGA, OGG, WAV, WMA