

Philips LCD widescreen monitor **49 cm (19.1") wide** WXGA+ **190VW9FB**



Great value, best savings on widescreen display

This Vista-ready 190VW9 delivers the simple, straight forward and reliable widescreen display performance you need without costly extras that strain your budget and without compromising on quality.

Best Value for Money

- Widescreen LCD displays more content without scrolling
- 5ms fast response time
- Empowered for Windows Vista
- Energy Star for energy efficiency and low power consumption
- · Complies with RoHS standards to care for the environment

Great convenience

- · Screen tilts to your ideal, individualized viewing angle
- Embedded power supply eliminates external power adaptors
- sRGB ensures color matching between display and printouts
- Kensington anti-theft lock-ready for added security



Specifications

Picture/Display

- LCD panel type: 1440 x 900 pixels, Anti-glare polarizer, RGB vertical stripe
- Panel Size: 19"/ 48.1 cm
- Effective viewing area: 408.24 X 255.15 mm
- Pixel pitch: 0.285 x 0.285 mm
- Brightness: 300 cd/m²
- Contrast ratio (typical): 800:1 • Display colors: 16.7 M
- Viewing angle: 160° (H) / 160° (V), @ C/R > 10
- Response time (typical): 5 ms
- Maximum Resolution: 1440 x 900 @ 75 Hz • Optimum resolution: 1440 x 900 @ 60 Hz
- Video Dot Rate: 165 MHz
- Horizontal Scanning Frequency: 30 83 kHz Vertical Scanning Frequency: 56 -75 Hz
- sRGB
- Aspect ratio: 16:10

Connectivity

• Signal Input: VGA (Analog)

- Sync Input: Composite Sync, Separate Sync, Sync on Green
- Sync input impedance: 2.2k ohm
- Video input impedance: 75 ohm
- Video input signal levels: 0.7 Vpp

Convenience

- User convenience: On-screen Display
- Monitor Controls: Auto (Back), Input (Down), Brightness (Up), Menu, Power On/Off
- OSD Languages: English, French, German, Italian, Portuguese, Russian, Simplified Chinese, Spanish, Turkish
- Other convenience: Kensington lock compatible
- Plug & Play Compatibility: DDC/Cl, sRGB,







90VW9FB/62

Highlights

WideScreen Design

This wide screen design employs a wider aspect ratio to enable it to display more information.

5ms on/off response time

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and. therefore, results in fewer visible image artifacts in the display of transition of texts and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

Windows Vista ready

Philips Vista-ready monitors are empowered for vibrant, exciting display of this new, visually sophisticated and demanding Windows operating system, designed to enhance your entertainment experience, make you more productive and help you control your computing experience at home and in the office, making viewing, finding and organizing information for work or play quick, efficient and easy.

Energy Star Energy Star-labeled home electrical products are designed to use less energy - saving you money while reducing environmental pollution. In fact, Energy Star-compliant products consume less than 1 watt of power while in standby mode. As an Energy Star partner, Philips develops products that meet the Energy Star guidelines for energy efficiency. This is achieved by having low standby power consumption through innovatively designed standby circuitry and stringent selection of components made with high efficiency materials.

Compliant with RoHS standards

Philips designs and produces display products in compliance with strict Restriction of Hazardous Substances (RoHS) standards that restrict lead and other toxic substances that can harm the environment.

Adjustable tilt

Adjustable tilt is backward and forward movement of a screen on its base to achieve custom positioning for an ideal viewing angle and more comfort for people who spend long hours working on the computer.

Embedded power supply

An embedded power supply is a power adaptor built into the body of a display device that replaces a bulky external power adaptor.

sRGB ready

sRGB is an industry standard that ensures the best possible match between the colors displayed on your screen and those in your printouts.

Kensington lock compatible

Small apertures built into the display's frame for use with a locking device that secures a display to a fixed object for added protection against theft.

Issue date 2022-05-10

© 2022 Koninklijke Philips N.V.

Version: 3.0.7

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V.

12 NC: 8670 000 40143 EAN: 87 12581 42709 2

Power · Complies with: Energy Star Consumption (On mode): < 35 W

• Consumption (Off Mode): < 1 W • Power LED indicator: Operation - green, Stand by/

Windows 98, Windows 2000, Windows XP,

• Regulatory approvals: CE Mark, Energy Star, FCC

Windows Vista

Class B, ÚL/cUL

• VESA Mount: 100 x 100 mm

Box dimensions (W x H x D):

• Set dimensions (W x H x D):

Box dimensions in inch (W x H x D):

• Set dimensions in inch ($W \times H \times D$):

• Set dimensions with stand (W x H x D):

Set dimensions with stand in inch (W x H x D):

• Temperature range (operation): 0°C to 40°C

• Temperature range (storage): -20°C to 60°C

375 x 145 x 490 mm

14.8 x 5.7 x 19.3 inch

439 x 304 x 60.9 mm

17.3 x 12.0 x 2.4 inch

17.3 x 14.3 x 7.6 inch

• MTBF: 50.000 hrs

439 x 363.1 x 191.7 mm

• Relative humidity: 20% - 80%

• Product weight (+stand): 3.6 kg

• Weight incl. Packaging: 4.95 kg

• Weight incl. Packaging (lb): 10.9

• Product weight (+stand) (lb): 7.9 lb

• Tilt: -5° to 20°

Dimensions

- sleep Amber
- Power supply: Built-in, 100-240VAC, 50/60Hz







All Rights reserved.

www.philips.com

or their respective owners.