



Crisp views, efficient performance

with PowerSensor

The Philips PowerSensor display using 85% post consumer recycled plastics and PVC, BFR-free housing is ideal for eco-friendly productivity

Brilliant performance

- SmartImage pre-sets for easy optimised image settings
- IPS technology for full colours and wide viewing angles
- Narrow-border display for a seamless appearance

Features for the way you work

- Built-in stereo speakers for multimedia
- SmartConnect with DisplayPort, HDMI and VGA connections
- Webcam pops up when you need it; secures down when you don't
- USB 3.0 enables fast data transfers and smart phone charging

Sustainable Eco-design


• PowerSensor saves up to 70% energy costs

Designed for comfortable productivity

- SmartErgoBase enables user-friendly ergonomic adjustments
- Less eye fatigue with Flicker-Free technology
- LowBlue Mode for easy-on-the-eyes productivity

Highlights

IPS technology



IPS displays use advanced technology that gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle - even in 90-degree Pivot mode! Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colours, making it ideal not only for Photos, films and web browsing, but also for professional applications that demand colour accuracy and consistent brightness at all times.

Ultra-narrow Border



The new Philips displays feature ultra-narrow borders which allow for minimal distractions and maximum viewing size. Especially suited for multi-display or tiling setups like gaming, graphic design and professional applications, the ultranarrow border display gives you the feeling of using one large display.

Smartimage



SmartImage is an exclusive leading edge Philips technology that analyses the content displayed on your screen and optimises your display

performance. This user-friendly interface allows you to select various modes, like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimises the contrast, colour saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time at the touch of a single button!

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave-length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, the Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

Flicker-Free technology



Due to the way brightness is controlled on LEDbacklit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-Free technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

SmartErgoBase



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base can swivel, tilt and rotate to various angles to ensure maximum comfort. The height-adjustable stand guarantees the optimal viewing level, reducing the physical strains of a long workday, while cable management reduces cable clutter and keeps the workspace neat and professional.

Pop-up webcam



Webcams are great for connecting with others and collaborating on that important project. Sometimes, though, you don't want a webcam looking down on your desk. Our ingenious new pop-up webcam design pops up when it's time for meetings and for security tucks away nicely when you are not using it.

















Flicker-free

Highlights

Built-in stereo speakers



A pair of high-quality stereo speakers built into a display device. They may be visible front firing, or invisible down firing, top firing, rear firing etc. depending on model and design.

SmartConnect

With a plethora of connectivity, these Philips displays come equipped with multiple connections like VGA, Display Port and universal HDMI connector, enabling you to enjoy high-resolution uncompressed video and audio content. USB connections ensure that you can have super-speed data transfers while having global connectivity. Regardless of what source you use, you can rest assured that this Philips display will ensure your investment is not made obsolete any time soon!

PowerSensor



PowerSensor is a built-in 'people sensor' that transmits and receives harmless infrared signals to determine if the user is present and automatically reduces monitor brightness when the user steps away from the desk, cutting energy costs by up to 70 percent and prolonging monitor life.













Specifications

Picture/Display

Panel Size: 23.8 inch/60.5 cm

Aspect ratio: 16:9

LCD panel type: IPS technology Backlight type: W-LED system Pixel pitch: 0.275 x 0.275 mm

Optimum resolution: 1920 x 1080 @ 60 Hz

Brightness: 250 cd/m²
Display colours: 16.7 M
Contrast ratio (typical): 1000:1
SmartContrast: 20,000,000:1

Response time (typical): 5 ms (Grey to Grey)* Viewing angle: 178° (H)/178° (V), @ C/R > 10

Picture enhancement: SmartImage Effective viewing area: 527 (H) x 296.5 (V) Scanning Frequency: 30 - 83 kHz (H) / 56 - 76 Hz (V)

sRGB Flicker-free

Connectivity

Signal Input: VGA (Analogue), DisplayPort 1.2, HDMI 1.4

USB: USB 3.0 x 3 (1 w/fast charging)*
Sync Input: Separate Sync, Sync on Green

Audio (In/Out): PC audio-in, Headphone out

Convenience

Built-in Speakers: 2 W x 2

Plug and Play Compatibility: DDC/CI, Mac $\operatorname{OS} X$,

sRGB, Windows 10 / 8.1 / 8 / 7
User convenience: SmartImage, Input,
PowerSensor, Menu, Power On/Off, LowBlue
Mode

OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian

Other convenience: Kensington lock, VESA mount (100 x 100 mm)
Control software: SmartControl

Built-in webcam: Pop-up 2.0 megapixel FHD camera with microphone and LED indictor

Stand

Height adjustment: 130 mm

Pivot: 90 degree Swivel: -175/+175 degree

Tilt: -5/20 degree

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

© 2025 Koninklijke Philips N.V.

All Rights reserved

Issue date 2025-02-12 Version: 10.0.2

EAN: 87 12581 74055 9

www.philips.com

Power

ECO mode: 10.3 W (typ.)

Power supply: Built-in, 100–240 VAC, 50–60 Hz

Off mode: Zero watts with AC switch On mode: 13.14 W (typ.) (EnergyStar test

method)

Standby mode: <0.3 W (typ.)

Power LED indicator: Operation - White, Standby

mode - White (flashing) Energy Label Class: E

Dimensions

Packaging in mm (W x H x D): 603 x 492 x

187 mm

Product without stand (mm): 541 x 332 x 57 mm Product with stand (max height): 541 x 492 x

257 mm

Weight

Product with packaging (kg): 8.35 kg Product with stand (kg): 5.83 kg Product without stand (kg): 3.52 kg

Operating conditions

Altitude: Operation: +12,000 ft (3658 m), Non-

operation: +40,000 ft (12,192 m)

Temperature range (operation): 0°C to 40 °C

Relative humidity: 20%-80 %

Temperature range (storage): -20°C to 60 °C MTBF (demonstrated): 70,000 hrs (excluded

backlight)

Sustainability

Environmental and energy: EnergyStar 8.0, PowerSensor, EPEAT*, TCO Certified Edge, RoHS Post consumer recycled plastic: 85% Recyclable packaging material: 100 % Specific Substances: PVC/BFR free housing,

Mercury free

Compliance and standards

Regulatory Approvals: CE Mark, FCC Class B, CETLus, CU-EAC, TUV Ergo, TUV/GS, WEEE, ICES-003, UKRAINIAN

Cabinet

Finish: Texture
Foot: Black
Front bezel: Black
Rear cover: Black

What's in the box?

Cables: D-Sub cable, DP cable, USB cable, Audio

cable, Power cable Monitor with stand User Documentation



- * "IPS" word mark / trademark and related patents on technologies belong to their respective owners.
- * EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in your country.
- * Fast charging complies with USB BC 1.2 standard
- * Response time value equal to SmartResponse