

affordable, space-saving display

Look to the Philips 150S5 to save space and money: Great, reliable display for pumped up productivity, SmartManage for remote, LAN-based monitor management and low power consumption add up to smart, affordable display for smart businesses.

Best total cost of ownership solution

- SmartManage manages display devices remotely
- Lower power consumption than industry average
- Kensington anti-theft lock secures monitor against theft

Outstanding front of screen performance

- Fast response time capable of handling fast moving pictures
- XGA 1024x768 resolution for sharper display
- sRGB ensures color matching between display and printouts

Great convenience

- Embedded power supply eliminates external power adaptors
- VESA mounting pattern for easy wall mounting of display
- FlexiHolder to hold notes, cards, and photos



PHILIPS

15 inch LCD Monitor

Commercial Specifications

Picture/ Display

- LCD Panel Type 1024 x 768 pixels, Anti-glare Polarizer, RGB Vertical Stripe
- Panel Size 15" 38 cm
- Effective Viewing Area 304.1 x 228.1 mm
- Pixel Pitch 0.297 x 0.297 mm
- Brightness (nits) 250
- Contrast Ratio 400:1
- Display Colors 16 M
- Viewing Angle (C/R > 5)
 - Horizontal : 160°
 - Vertical : 140°
- Response Time 16 ms
- White Chromaticity, 6500° K $x = 0.313$ / $y = 0.329$
- White Chromaticity, 9300° K $x = 0.283$ / $y = 0.297$
- Maximum Resolution 1024 x 768 @ 75Hz
- Recommended Resolution 1024 x 768 @ 60Hz
- Factory Preset Modes 14 modes
- User Definable Modes 16 modes
- Horizontal Scanning Frequency 30 - 61 KHz
- Refresh Rate (V) 56 - 76 Hz
- sRGB Yes

Connectivity

- Signal Input Analog (VGA)

Convenience

- Convenience Enhancements On-screen Display, SmartManage
- Monitor Controls Auto, Brightness control, Left/Right, Menu (OK), Power On/Off, Up/Down
- OSD Languages English, French, German, Italian, Simplified Chinese, Spanish
- Other Convenience Features Kensington Lock
- Plug & Play Compatibility DDC/CI, sRGB, Windows 98/ME/2000/XP
- Regulatory Approvals CE Mark, E2000, EMC, FCC-B, UL, CSA, MPR-II, Low Emission, NUTEK, Energy Star, SEMKO, TCO '03, TCO '99, TUV/IGS, TUV Ergo
- Tilt -5° to 25°
- VESA Mount 100 mm x 100 mm

Accessories

- User Manual Yes
- Included Accessories AC Power Cord, VGA Cable

Dimensions

- Depth (with base) 180 mm
- Height (with base) 344 mm
- Width (with base) 342 mm
- MTBF 50,000 (excl. CCFL 40,000) hrs
- Relative Humidity 20 % - 80 %
- Temperature Range (Operation) 5°C to 40°C
- Temperature Range (Storage) -20°C to 60°C
- Weight 2.8 kg

Power

- Complies With E2000, Energy Star, NUTEK
- Consumption 17 W (Typical)
- Off Mode < 1 W
- Power LED Indicator Operation, Green; Stand by/Sleep, Amber
- Power Supply Built-in

Product Highlights

SmartManage

A system for monitoring, managing and checking status of display devices as well as delivering remote support to users who experience difficulties all accomplished over a LAN.

Lower power consumption

Reduction of the electrical power required to operate a device.

Kensington anti-theft lock

A security device that fixes the monitor in place to prevent theft.

Fast response time

The amount of time it takes for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Lower numbers mean faster transitions and therefore results in fewer visible image artifacts.

XGA, 1024 x 768 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. For example, a 1024-by-768 pixel screen is capable of displaying 1024 distinct dots on each of 768 lines, or about 786 thousand pixels. XGA provides resolutions of 640 by 480 or 1024 by 768 pixels. In addition, XGA allows monitors to be non-interlaced. This ensures a better display performance and accurate color display effect.

sRGB ready

Calibrated RGB that is optimized for the vast majority of computer peripherals, monitors, operating systems and browsers, allowing accurate color mapping with very little data overhead.

Embedded power supply

A power adaptor built into the body of a display device that replaces a bulky external power adaptor.

VESA mounting holes

A unified industry standard for wall mounting IT equipment set by the Video Electronics Standards Association.

FlexiHolder

A slim groove that improves efficiency by holding reminder notes, documents, name cards, and photos on the top of monitor to be more efficient.



design award
winner
2004



Trademarks owned by Royal Philips Electronics
2004 © Royal Philips Electronics - All rights reserved
As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency.
Microsoft and Windows are registered trademarks of Microsoft Corporation.
All data subject to change without notice
Release date: June 2004
www.philips.com