



Philips  
LCD monitor

48 cm (19")  
SXGA

190C7FS

## Elegance matters

Outstanding convenience meets great style: The environment friendly 190C7 will change the way you look at monitors with its clean, sophisticated, dual tone decor-enhancing design, thoughtful convenience features and superb value.

### Design that complements any interior

- Chic dual-tone design enlivens your space
- Convenient, understated control buttons create a clean look
- 'Hug' bezel for a warm, harmonious design look

### Outstanding front of screen performance

- Empowered for Windows Vista
- 5ms fast response time

### Green design

- For your safety: Aerospace composite fire retardant case

### Great convenience

- Dual input accepts both analog VGA and digital DVI signals
- Easy to adjust display settings with Philips SmartControl
- Embedded power supply eliminates external power adaptors
- Cable clip manages cables for a tidy work space

**PHILIPS**

# Highlights

## Dual tone design

Dual tone design combines a glossy black strip located in the middle of the bottom bezel with a silver front bezel to make the front bezel appear slimmer. The subtle contrast between the two elements adds a lively spirit, eye appeal and interesting, unique elements to a room's decor.

## Clean-look design

Convenient, unobtrusive controls are integrated with the brand banner, placing them at your fingertips when you need them, but making control buttons inconspicuous when not required to create an integral, crisp and clean look with simple, yet stylish aesthetic appeal.

## 'Hug' bezel design

A 'hug' bezel is a specially designed slanting surface that joins front and rear design elements in warm embrace, creating a warm, harmonious and smoothly flowing overall appearance.

## Windows Vista ready

Philips Vista-ready monitors are empowered for vibrant, exciting display of this new, visually

sophisticated and demanding Windows operating system, designed to enhance your entertainment experience, make you more productive and help you control your computing experience at home and in the office, making viewing, finding and organizing information for work or play quick, efficient and easy.

## 5ms on/off response time

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and, therefore, results in fewer visible image artifacts in the display of transition of texts and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

## Flame retardant cabinet

PC/ABS plastic composite is the industry's best and toughest flame-retardant casing material; and is a space-age compound deployed in the aerospace and automotive industries as well as

in fire detectors that is compliant with most stringent fire safety standards.

## Dual input

Dual input provides connectors to accommodate input of both analog VGA and digital DVI signals.

## SmartControl

PC software for fine tuning display performance and settings. Philips offers users two choices for display setting adjustment. Either navigate the multilevel On Screen Display menu through buttons on the display itself or use the Philips SmartControl software to easily adjust the various display settings in a familiar way.

## Embedded power supply

An embedded power supply is a power adaptor built into the body of a display device that replaces a bulky external power adaptor.

## Cable clip

A clip shipped with monitors that manages cables by clipping them together for a tidy work space.



# Specifications

## Picture/Display

- LCD panel type: 1280 x 1024 pixels, Anti-glare polarizer, RGB vertical stripe
- Panel Size: 19"/ 48 cm
- Effective viewing area: 376.3 x 301.1 mm
- Pixel pitch: 0.294 x 0.294 mm
- Brightness: 300 cd/m<sup>2</sup>
- Contrast ratio (typical): 800:1
- Display colors: 16.7 M
- Viewing angle: 160° (H) / 160° (V), @ C/R > 10
- Response time (typical): 5 ms
- Maximum Resolution: 1280 x 1024 @ 75 Hz
- Optimum resolution: 1280 x 1024 @ 60 Hz
- Video Dot Rate: 140 MHz
- Horizontal Scanning Frequency: 30 - 83 kHz
- Vertical Scanning Frequency: 56 - 76 Hz
- sRGB

## Connectivity

- Signal Input: VGA (Analog), DVI-D
- Sync Input: Composite Sync, Separate Sync, Sync on Green

## Convenience

- User convenience: On-screen Display, SmartControl
- Monitor Controls: Auto, Brightness Control (Up/Down), Left/Right, Menu (OK), Power On/Off
- OSD Languages: English, French, German, Italian, Russian, Spanish
- Other convenience: Kensington lock compatible
- Plug & Play Compatibility: DDC/CI, sRGB, Windows 98/ME/2000/XP/Vista
- Regulatory approvals: CE Mark, EMC, Energy Star,

- FCC-B, UL, CSA, SEMKO, TCO '99, TÜV/GS, TÜV Ergo
- Tilt: -5° to 25°

## Accessories

- Included accessories: AC Power Cord, VGA cable
- User Manual

## Dimensions

- Box dimensions (W x H x D): 534 x 194 x 538 mm
- Box dimensions in inch (W x H x D): 21 x 7.6 x 21.2 inch
- Set dimensions with stand (W x H x D): 442 x 420 x 201 mm
- Set dimensions with stand in inch (W x H x D): 17.4 x 16.5 x 7.9 inch
- MTBF: 50,000 (excl. CCFL 40,000) hrs
- Relative humidity: 20% - 80%
- Temperature range (operation): 0°C to 35°C
- Temperature range (storage): -20°C to 60°C
- Product weight (+stand): 5.3 kg
- Product weight (+stand) (lb): 11.7 lb
- Weight incl. Packaging: 7.2 kg
- Weight incl. Packaging (lb): 15.9

## Power

- Complies with: Energy Star
- Consumption (On mode): 36W (Typical)
- Consumption (Off Mode): < 1 W
- Power LED indicator: Operation - green, Stand by/ sleep - Amber
- Power supply: Built-in, 100-240VAC, 50/60Hz



Issue date 2022-04-21

Version: 3.0.5

12 NC: 8670 000 28301  
EAN: 87 12581 32431 5

© 2022 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)