

Philips Signage Solutions Multi-Touch Display

65"

Powered by Android Multi-touch



65BDL3652T

# Interactive classroom display

### Featuring multi-touch technology

Maximise engagement and inspire collaboration with an interactive Philips T-Line display. Featuring anti-glare toughened glass, these Android-powered displays are made to withstand heavy daily usage and feature up to 20 touchpoints

#### Smart and powerful

- Anti-glare toughened glass
- OPS slot allows for PC embedding without cabling
- · Whiteboard mode built in
- · Wireless screen sharing and advanced collaboration
- 0-gap touch frame

#### Interactive and collaborative

- · Operate, monitor and maintain with CMND and Control
- Multi-touch technology capable of 20 touchpoints
- · Advanced IR touch with smaller, shallower bezels
- Android: Run your own app or choose your favourite app to run



### Highlights

#### **Powered by Android**

With Android OS integrated into the display, you can work with the most developed OS on the planet and save your own app directly into the display. Or, choose from the large library of Android apps and play content from there. With the built-in scheduler, you can daypart your apps and content based on your customer and time of day and with the auto-orientation feature, showing content in portrait or landscape is as simple as turning the display.

#### **CMND** and Control



Run your display network over a local (LAN) connection. CMND and Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

#### **Multi-touch technology**

Create a memorable interactive experience with up to 20 touchpoints at the same time. Perfect for collaborative and competitive applications, this display connects your audience with any content - making it ideal for education, public venues, corporate, hospitality and retail settings. The touch panel is HID compliant, providing true plug-and-play operation.

#### **OPS** slot



Integrate a full-power PC or Android-powered CRD50 module directly into your Philips Professional Display. The OPS slot contains all the connections you need to run your slot-in solution, including a power supply.

#### Whiteboard mode built in

Inspire agile collaboration with whiteboard mode. Simply activate this feature to turn your display into a blank canvas that can be drawn on by multiple users by hand or with dedicated display markers. Everything on the screen can then be captured for easy printing or file sharing.

#### Wireless screen sharing

Display four feeds on the one screen. Wireless screen sharing allows you to connect multiple devices at the same time for quick content switching when you need it. Use your existing Wi-Fi network to instantly and securely connect devices or use our optional HDMI interact dongles to cast directly to the screen without needing to connect to your secured/protected network.













### Specifications

#### Picture/Display

- Diagonal screen size (metric): 163.9 cm
- Diagonal screen size (inch): 64.5 inch
- · Aspect ratio: 16:9
- Panel resolution: 3840 x 2160
- Pixel pitch: 0.372 x 0.372 mm
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 420 cd/m<sup>2</sup>
- Display colours: 1.07 Billion
- Contrast ratio (typical): 1300:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 9 ms
- Viewing angle (horizontal): 178 degree
- Viewing angle (vertical): 178 degree
- Picture enhancement: 3/2 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, Progressive scan, 3D MA deinterlacing, Dynamic contrast enhancement
- Surface treatment: Anti-Glare coating
- · Panel technology: IPS
- Operating system: Android 9

#### Connectivity

- Audio output: 3.5 mm Jack (x 2)
- Video input: Display Port1.2 (x 1), DVI-I (x 1), HDMI 2.0 (x 2), HDMI 2.0 (x 4), USB 2.0 (x 2), USB 3.0 (x 2), USB-C
- Audio input: 3.5 mm Jack (x 1)
- Other connections: OPS, micro SD
- Video output: DisplayPort 1.2 (x 1), DVI D (x 1), USB 2.0 (x 2), HDMI 2.0 (x 2)
- External control: IR (in/out) 3.5 mm jack, RJ45, RS232C (in/out) 2.5 mm jack

#### Convenience

- Placement: Portrait (12/7), Landscape (18/7)
- · Screen-saving functions: Pixel Shift, Low Brightness
- Keyboard control: Hidden, Lockable
- Remote control signal: Lockable
- Signal loop through: DisplayPort, RS232, IR Loop through

- · Ease of installation: Smart Insert
- · Energy-saving functions: Smart Power
- Other convenience: Carrying handles
- Picture performance: Advanced colour control
- Network controllable: RS232, RJ45

#### Sound

• Built-in speakers: 2 x 20 W RMS

#### Power

- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- Consumption (Typical): 175 W
- Consumption (Max): 350 W
- Standby power consumption: <0.5 W
- Power Saving Features: Smart Power
- Energy Label Class: G

#### **Supported Display Resolution**

- Computer formats: 640 × 350, 70 Hz, 640 × 480, 60, 67, 72, 75 Hz, 800 × 600, 56, 60, 72, 75 Hz, 832 × 624, 75 Hz, 848 × 480, 60 Hz, 960 × 720, 75 Hz, 1024 × 768, 60, 70 Hz, 1152 × 864, 60, 70, 75 Hz, 1152 × 900, 66 Hz, 1280 × 720, 60, 70 Hz, 1280 × 768, 60 Hz, 75 Hz, 1280 × 800, 60, 75 Hz, 1280 × 960, 60 Hz, 1280 × 1024, 60, 67, 75 Hz, 1360 × 768, 60 Hz, 1366 × 768, 60 Hz, 1400 × 1050, 60, 75 Hz, 1440 × 900, 60, 75 Hz, 1440 × 1050, 60 Hz, 1600 × 900, 60 Hz, 1600 × 1200, 60 Hz, 1680 × 1050, 60 Hz, 1920 × 1080, 60 Hz, 1920 × 1200, 60 Hz, 3840 × 2160, 24, 25, 30, 60 Hz
- Video formats: 480p, 60 Hz, 576p, 50 Hz, 720p, 60 Hz, 720p, 50, 60 Hz, 1080i, 50, 60 Hz, 1080p, 50, 60 Hz, 4K x 2K

#### **Dimensions**

- Smart Insert mount: 100 mm x 100 mm, 6 x M4L6
- Set Width: 1494.30 mm
- Product weight: 43.6 kg
- Set Height: 869.40 mm
- Set Depth: 80.2 mm (D@wall mount)/106.8 mm (D@speaker cover) mm

- Set Width (inch): 58.83 inch
- Set Height (inch): 34.23 inch
- Wall Mount: 400(H)x400(V), M8
- Set Depth (inch): 3.16 (D@wall mount)/4.20 (D@speaker cover) inch
- Bezel width: 17.8 mm(even)
- Product weight (lb): 96.12 lb

#### **Operating conditions**

- Altitude: 0 ~ 3000 m
- Temperature range (operation): 0  $\sim$  40  $^{\circ}$ C
- MTBF: 50,000 hour(s)
- Relative humidity: 20–80% (Operational), 5–95% (Storage) %
- Temperature range (storage): -20 ~ 60 °C

#### **Multimedia Applications**

- USB Playback Video: ASF, AVI, DAT, FLV, MKV, MP4, MPEG, MPG, TS, VOB, WEBM, WMV
- USB Playback Picture: BMP, JPEG, JPG, PNG
- USB Playback Audio: AAC, M4A, MP3, WMA

#### **Internal Player**

- CPU: MTK5680
- GPU: DDR4 4 GB
- Memory: 4 GB RAM
- Storage: 32 GB eMMc
- Wi-Fi: AP(WC0SR2511-88112BU), STA(WCT5GM2511MT7668AU)

#### Accessories

- Included Accessories: Cleaning cloth (x 1), DVI-D cable (1.8 m), M2 Screw (x 2), M3 screw (x 2), Philips logo (x 1), RS232 daisy-chain cable, Touch Pen (x 2), Touch USB (x 1), USB Cover (x 1), AC power cord, Batteries for remote control, HDMI cable, IR sensor cable (1.8 m) (x 1), Quick start guide (x 1), Remote control (x 1), RS232 cable
- Optional accessories: Interact dongles

## Specifications

#### **Miscellaneous**

- On-Screen Display Languages: Arabic, Dutch, Danish, English, French, Finnish, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Simplified Chinese, Turkish, Traditional Chinese
- Warranty: 5-year warranty
  Regulatory approvals: CE, FCC, Class A, RoHS,

CB, BSMI, EAC, EMF, PSB, ETL

#### **Interactivity**

- Multi-touch technology: 0-gap Infrared touch
  Touchpoints: 20 simultaneous touch points
- Plug and play: HID compliant
- Protection glass: Anti-Glare, Tempered safety glass



Issue date 2024-10-28

© 2024 Koninklijke Philips N.V. All Rights reserved.

Version: 2.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 78195 8

www.philips.com