



Vivid, crisp images beyond boundaries

Philips V line wide-view monitor gives viewing beyond boundaries, great value with essential features. Adaptive-Sync delivers smooth video display. Features like anti-glare, LowBlue mode, and flicker-free for easy-on-the eyes.

Perfectly designed for your space

• VESA mount allows for flexibility

Easy on the eyes

- EasyRead mode for a paper-like reading experience
- Less eye fatigue with Flicker-free technology
- LowBlue Mode for easy on-the-eyes productivity

Experience true multimedia

• HDMI ensures universal digital connectivity


Vivid pictures every time

- SmartContrast for rich black details
- SmartImage presets for easy optimized image settings
- VA display delivers awesome images with wide viewing angles
- Effortlessly smooth action with Adaptive-Sync technology

LCD monitor 241V8L/75

Highlights

VA display



Philips VA LED display uses an advanced multidomain vertical alignment technology which gives you super-high static contrast ratios for extra vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, web-browsing, movies, gaming, and demanding graphical applications. It's optimized pixel management technology gives you 178/178 degree extra wide viewing angle, resulting in crisp images.

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

SmartImage



SmartImage is an exclusive leading edge Philips technology that analyzes the content displayed on your screen and gives you optimized display performance. This user friendly interface allows you to select various modes like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimizes the contrast, color saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time with the press of a single button!

Adaptive-Sync technology



Gaming shouldn't be a choice between choppy gameplay or broken frames. Get fluid, artifact-free performance at virtually any framerate with Adaptive-Sync technology, smooth quick refresh and ultra-fast response time.

Flicker-free technology



Due to the way brightness is controlled on LEDbacklit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

EasyRead mode



EasyRead mode for a paper-like reading experience

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables high-quality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

















Specifications

Picture/Display

Panel Size: 23.8 inch / 60.5 cm

Aspect ratio: 16:9 LCD panel type: VA LCD Backlight type: W-LED system Pixel pitch: 0.2745 x 0.2745 mm

Brightness: 250 cd/m² Display colors: 16.7 M

Contrast ratio (typical): 3000:1 SmartContrast: Mega Infinity DCR Response time (typical): 4 ms (GtG)*

Viewing angle: 178° (H) / 178° (V), @ C/R > 10 Maximum resolution: 1920 x 1080 @ 75 Hz* Effective viewing area: 527 (H) x 296.5 (V) Scanning Frequency: 30 - 85 kHz (H) / 48 - 75 Hz

(V) sRGB Flicker-free Pixel Density: 93 PPI LowBlue Mode

Display Screen Coating: Anti-Glare, 3H, Haze 25%

EasyRead Adaptive sync

Connectivity

Signal Input: VGA (Analog), HDMI (digital, HDCP)

Sync Input: Separate Sync, Sync on Green Audio (In/Out): Audio out

Convenience

Plug & Play Compatibility: DDC/CI, Mac OS X,

sRGB, Windows 10 / 8.1 / 8 / 7

User convenience: Power On/Off, Menu/OK, Brightness/UP, Input/Down, SmartImage/Back OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian Other convenience: Kensington lock, VESA

Stand

Tilt: -5/20 degree

mount (100x100mm)

Power

Power supply: Built-in, 100-240VAC, 50-60Hz

Off mode: 0.3 W (typ.) On mode: 20.4 W (typ.) Standby mode: 0.5 W (typ.)

Power LED indicator: Operation - White, Standby

mode-White (blinking)

Dimensions

Packaging in mm (WxHxD): 608 x 415 x 121 mm Product without stand (mm): 540 x 322 x 51 mm Product with stand(max height): 540 x 416 x

220 mm

Weight

Product with packaging (kg): 4.25 kg Product with stand (kg): 3.03 kg Product without stand (kg): 2.64 kg

Operating conditions

Altitude: Operation: +12,000ft (3,658m), Non-

operation: +40,000ft (12,192m)

Temperature range (operation): 0°C to 40°C °C MTBF: 50,000 (Excluded backlight) hour(s)

Relative humidity: 20%-80 %

Temperature range (storage): -20°C to 60°C °C

Sustainability

Environmental and energy: RoHS, Mercury Free Recyclable packaging material: 100 %

Compliance and standards

Regulatory Approvals: UKRAINIAN, CB, TUV Ergo, TUV/GS, CU-EAC, EAEU RoHS, CE Mark, MEPS, RCM

Cabinet

Color: Black Finish: Textured

© 2025 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 77740 1

www.philips.com

Issue date 2025-03-25

Version: 2.0.3



^{*} Response time value equal to SmartResponse

^{*} The monitor may look different from feature images.