

Philips LCD monitor

V Line 23.6" / 59.9 cm

243V5QSBA

Great LED images in vivid colors

Enjoy vibrant pictures on this Philips display. Essential features like SmartContrast that ensures rich bright images makes it a great choice!

Great choice

- · Compact design saves space
- Mercury Free eco-friendly display
- · VESA mount allows for flexibility

Vivid pictures every time

- SmartContrast for rich black details
- MVA Display for wide viewing angles and deep contrast levels
- 16:9 Full HD display for crisp detailed images



Highlights

MVA Display Technology



Philips MVA LED display uses an advanced multi-domain vertical alignment technology which gives you super-high static contrast ratios for extra vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, webbrowsing, movies, gaming, and demanding graphical applications. It's optimized pixel management technology gives you 178/178 degree extra wide viewing angle, resulting in crisp images.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 \times 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colors expect a true to life picture.

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying,

automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

Compact design saves space

Compact design saves space

VESA mount

VESA mount allows for flexibility

















Specifications

Connectivity

- Signal Input: VGA (Analog), DVI-D (digital, HDCP)
- · Sync Input: Separate Sync, Sync on Green

Picture/Display

- Panel Size: 23.6 inch / 59.9 cm
- · Aspect ratio: 16:9
- · LCD panel type: MVA
- Backlight type: W-LED system
- Pixel pitch: 0.272 x 0.272 mm
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 250 cd/m²
- Display colors: 16.7 M
- Contrast ratio (typical): 3000:1
- SmartContrast: 10,000,000:1
- Response time (typical): 25 (Gray to Gray) ms
- Viewing angle: 178° (H) / 178° (V), @ C/R > 20
- Effective viewing area: 521.28 (H) x 293.22 (V)
- Scanning Frequency: 30 -83 kHz (H) / 56 -75 Hz (V)
- sRGB
- SmartResponse (typical): 8 (Gray to Gray) ms

Convenience

- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 7, Windows 8
- User convenience: Auto/Down, 4:3 Wide/Up, Brightness/Back, Menu/OK, Power On/Off
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian
- Other convenience: Kensington lock, VESA mount (100x100mm)

Stand

• Tilt: -5/20 degree

Power

- Power supply: Built-in, 100-240VAC, 50-60Hz
 Off mode: 0.5 W (typ.)
- On mode: 21.07 W (typ.) (EnergyStar 6.0 test

method)

- Standby mode: 0.5 W (typ.)
- · Power LED indicator: Operation White, Standby mode- White (blinking)
- Energy Label Class: E

Dimensions

- Product with stand (mm): $551 \times 420 \times 220$ mm
- Packaging in mm (WxHxD): 600 x 415 x 118 mm
- Product without stand (mm): 551 x 344 x 52 mm

Weight

- Product with packaging (kg): 5.00 kg
- Product with stand (kg): 3.66 kg
- Product without stand (kg): 3.22 kg

Operating conditions

- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- Temperature range (operation): 0°C to 40 °C
- MTBF: 30,000 hour(s)
- Relative humidity: 20%-80 %
- Temperature range (storage): -20°C to 60 °C

Sustainability

- Environmental and energy: EnergyStar 6.0, RoHS, Mercury Free
- Recyclable packaging material: 100 %

Compliance and standards

• Regulatory Approvals: BSMI, CE Mark, cETLus, FCC Class B, GOST, PSB, SASO, TCO Certified, TUV/ISO9241-307, WEEE

Cabinet

- Color: Black
- Finish: Hairline (front bezel) / Texture (rear cover)

What's in the box?

- · Cables: VGA. Power
- · Monitor with stand • User Documentation



Issue date 2024-03-25

© 2024 Koninklijke Philips N.V. All Rights reserved.

Version: 6.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 73174 8 www.philips.com

st Smart response time is the optimum value from either GtG or GtG (BW) tests.