

LCD monitor

Philips

V Line 24 (23.6"/59.9 cm diag.)

243V5LSB5

# Great LED images in vivid colours

Enjoy vivid LED pictures on this Philips display. Equipped with SmartContrast, it's a great choice!

### Vivid pictures every time

- LED technology for vivid colours
- SmartContrast for rich black details
- 16:9 Full HD display for crisp, detailed images

#### **Great choice**

- Compact design saves space
- Mercury Free eco-friendly display
- VESA mount allows for flexibility



## Highlights

#### LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content, which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of the LCD backlight, resulting in a super high contrast ratio. It also gives superior colour reproduction thanks to consistent brightness across the screen.

#### 16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display

features enhanced Full HD 1920 x 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colours, expect a true-to-life picture.

#### SmartContrast



SmartContrast is a Philips technology that analyses the contents you are displaying, automatically adjusting colours and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

#### **Mercury Free**

Philips monitors with LED backlighting are free from Mercury, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its lifecycle, from manufacturing to disposal.

#### Compact design saves space

Compact design saves space

#### **VESA** mount

VESA mount allows for flexibility











## Specifications

#### Connectivity

- Signal Input: VGA (Analogue), DVI-D (digital, HDCP)
- Sync Input: Separate Sync, Sync on Green

#### **Picture/Display**

- Panel Size: 23.6 inch/59.9 cm
- Aspect ratio: 16:9
- LCD panel type: TFT-LCD
- Backlight type: W-LED system
- Pixel pitch: 0.272 x 0.272 mm
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 250 cd/m<sup>2</sup>
- Display colours: 16.7 M
- Contrast ratio (typical): 1000:1
- SmartContrast: 10,000,000:1
- Response time (typical): 5 ms
- Viewing angle: 170° (H)/160° (V), @ C/R > 10
- Effective viewing area: 521.28 (H) x 293.22 (V) • Scanning Frequency: 30–83 kHz (H)/56–76 Hz (V)
- sRGB
- Pixel Density: 93 PPI

#### Convenience

- Plug and Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7
- User convenience: Power On/Off, Menu/OK, Brightness/Back, 4:3 Wide/Up, Auto/Down
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian
- Other convenience: Kensington lock, VESA mount (100 x 100 mm)

#### Stand

• Tilt: -5/20 degree

#### Power

- Power supply: Built-in, 100-240 VAC, 50-60 Hz
- Off mode: 0.5 W (typ.)
- On mode: 15.7 W (typ.) (EnergyStar 7.0 test

#### method)

- Standby mode: 0.5 W (typ.)
- Power LED indicator: Operation White, Standby mode - White (flashing)

#### Dimensions

- Product with stand (mm): 560 x 424 x 219 mm
- Packaging in mm (W x H x D): 608 x 419 x 121 mm
- Product without stand (mm): 560 x 348 x 53 mm

#### Weight

- Product with packaging (kg): 4.69 kg
- Product with stand (kg): 3.41 kg
- Product without stand (kg): 3.02 kg

#### **Operating conditions**

- Altitude: Operation: +12,000 ft (3658 m), Non-
- operation: +40,000 ft (12,192 m)
- Temperature range (operation): 0°C to 40°C °C
- MTBF: 50 000 (Excluded backlight) hour(s)
- Relative humidity: 20%-80 %
  Temperature range (storage): -20°C to 60°C °C

- Sustainability
- Environmental and energy: EnergyStar 7.0, RoHS, Mercury Free
- Recyclable packaging material: 100 %

#### **Compliance and standards**

 Regulatory Approvals: CE Mark, FCC Class B, TCO Certified, cETLus, TUV/ISO9241-307, BSMI, PSB, RCM, UKRAINIAN, EPA, KC, KCC, CECP, WEEE

#### Cabinet

Colour: BlackFinish: Hairline (front bezel)/Texture (rear cover)

#### What's in the box?

- Cables: D-Sub cable, Power cable
- Monitor with stand
- User Documentation



Version: 2.0.1 Specifi Trader

Issue date 2024-04-26

All Rights reserved. Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

© 2024 Koninklijke Philips N.V.

### 243V5LSB5/00