



LCD monitor with USB-C docking

**Business Monitor** 

**B** Line

27" (68.6 cm)

2560 x 1440 (QHD)



272B7QUPBEB

# Simplify your connections

### with USB-C docking monitor

This Philips QHD monitor with USB-C docking replaces cable clutter. View QHD images, secure connect to intranet and re-charge your notebook all at the same time with a single USB-C cable.

### **Brilliant performance**

- IPS technology for full colours and wide viewing angles
- Narrow-border display for a seamless appearance
- Ultra Wide-Color wider range of colours for a vivid picture
- LowBlue Mode for easy-on-the-eyes productivity

### **Single cable USB-C connection**

- Built-in RJ-45 Ethernet gives data security
- Built-in USB-C docking station
- Connect your notebook with one USB-C cable
- Power and re-charge compatible notebook from the monitor
- USB 3.2 high-speed data transfer
- View Crystalclear QHD 2560 x 1440 images

### Sustainable Eco-design

• PowerSensor saves up to 70% energy costs

### LCD monitor with USB-C docking

## Highlights

### **Built-in USB-C docking station**



This Philips display features a built-in USB type-C docking station with power delivery. Its slim, reversible USB-C connector allows for easy, one-cable docking. Keep it simple by connecting all your peripherals, like your keyboard, mouse and your RJ-45 Ethernet cable to the monitor's docking station. Simply connect your notebook to this monitor with a single USB-C cable to watch high-resolution video and transfer superspeed data while powering up and recharging your notebook at the same time.

### Power and re-charge notebook

This monitor features a built-in USB-C connector that meets USB Power Delivery standard. With intelligent and flexible power management, you can now power up and/or re-charge your compatible\* Notebook directly from the Monitor using a single USB-C cable.

### **Crystalclear QHD images**


These Philips screens deliver CrystalClear, Quad HD 2560 x 1440 or 2560 x 1080 pixel images. Utilising high-performance panels with high-density pixel count, enabled by high-bandwidth sources like USB-C, Displayport, HDMI and Duallink DVI, these new displays will make your images and graphics come alive. Whether you are a demanding professional requiring extremely detailed information for CAD-CAM solutions, are using 3D graphic applications or are a financial wizard working on huge spreadsheets, Philips displays will give you CrystalClear images.

### **Ultra Wide-Color Technology**



Ultra Wide-Color Technology delivers a wider spectrum of colours for a more brilliant picture. The Ultra Wide-Color wider "colour gamut" produces more natural-looking greens, vivid reds and deeper blues. Bring media entertainment, images and even productivity more alive with vivid colours from Ultra Wide-Color Technology.

### **IPS technology**



IPS displays use advanced technology that gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle — even in 90-degree Pivot mode! Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colours, making it ideal not only for Photos, films and web browsing, but also for professional applications that demand colour accuracy and consistent brightness at all times.

### LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave-length blue light rays from LED displays can cause eye

damage and affect vision over time. Developed for wellbeing, the Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

### **Ultra-narrow Border**



The new Philips displays feature ultra-narrow borders which allow for minimal distractions and maximum viewing size. Especially suited for multi-display or tiling setups like gaming, graphic design and professional applications, the ultra-narrow border display gives you the feeling of using one large display.

#### **PowerSensor**



PowerSensor is a built-in 'people sensor' that transmits and receives harmless infrared signals to determine if the user is present and automatically reduces monitor brightness when the user steps away from the desk, cutting energy costs by up to 70 percent and prolonging monitor life.

















### **Specifications**

### **Picture/Display**

Panel Size: 27 inch / 68.5 cm

Aspect ratio: 16:9

LCD panel type: IPS technology Backlight type: W-LED system Pixel pitch: 0.233 x 0.233 mm Brightness: 350 cd/m<sup>2</sup> Display colours: 16.7 M

Colour gamut (typical): NTSC 114%\*, sRGB

132%\*

Contrast ratio (typical): 1000:1 SmartContrast: 50,000,000:1

Response time (typical): 5 ms (Grey to Grey)\* Viewing angle: 178° (H)/178° (V), @ C/R > 10

Picture enhancement: SmartImage Maximum resolution: 2560 x 1440 @ 75 Hz\* Effective viewing area: 596.7 (H) x 335.7 (V) Scanning Frequency: 30 - 99 kHz (H) / 50 - 76 Hz

(V) sRGB Flicker-free Pixel Density: 109 PPI

LowBlue Mode

Display Screen Coating: Anti-Glare, 3H, Haze

25% EasyRead

### **Connectivity**

Signal Input: DisplayPort 1.2 x 1, HDMI 1.4 x 1 Sync Input: Separate Sync, Sync on Green Audio (In/Out): Headphone out RJ45: Ethernet LAN up to 1G\* Signal Output: DisplayPort out x 1 USB:: USB-C 3.2 x 1 (upstream), USB 3.2 x 3 (downstream, w/fast charging)\*

### USB

Power delivery: USB PD version 2.0 Super speed: Data and Video transfer DP: Built-in Display Port Alt mode USB-C max. power delivery: Up to 65 watts (5 V/3 A; 7 V/3 A; 9 V/3 A; 12 V/3 A; 15 V/3 A;

**USB-C**: Reversible plug connector

### Convenience

Built-in Speakers: 2 W x 2

Plug and Play Compatibility: DDC/CI, Mac OS X,

sRGB, Windows 10 / 8.1 / 8 / 7 User convenience: SmartImage, Input, PowerSensor, Menu, Power On/Off

OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian Other convenience: Kensington lock, VESA

mount (100 x 100 mm) Control software: SmartControl

#### Stand

Height adjustment: 150 mm

Pivot: 90 degree Swivel: -175/175 degree Tilt: -5/30 degree

### Power

ECO mode: 19.7 W (typ.)

Power supply: Built-in, 100-240 VAC, 50-60 Hz Off mode: Zero watts with Zero switch On mode: 19.02 W (typ.) (EnergyStar test

method)

Standby mode: < 0.5 W (typ.)

Power LED indicator: Operation - White, Standby

mode - White (flashing) **Energy Label Class: E** 

### **Dimensions**

Packaging in mm (W x H x D): 690 x 458 x

Product without stand (mm): 614 x 372 x 56 mm Product with stand (max height): 614 x 548 x

### Weight

Product with packaging (kg): 10.16 kg Product with stand (kg): 7.38 kg Product without stand (kg): 4.95 kg

### **Operating conditions**

Altitude: Operation: +12,000 ft (3658 m), Non-

operation: +40,000 ft (12,192 m)

Temperature range (operation): 0°C to 40 °C

Relative humidity: 20%-80 %

Temperature range (storage): -20°C to 60 °C MTBF (demonstrated): 70,000 hrs (excluded

backlight)

### **Sustainability**

Environmental and energy: PowerSensor, EnergyStar 8.0, EPEAT\*, TCO Certified Edge, RoHS, WEEE

Post-consumer recycled plastic: 85% Recyclable packaging material: 100 % Specific Substances: PVC/BFR free housing,

Mercury free

### **Compliance and standards**

Regulatory Approvals: CE Mark, FCC Class B, cETLus, CU-EAC, TUV Ergo, TUV/GS, EPA, UKRAINIAN, ICES-003, CECP, PSB, CB, CEL

### **Cabinet**

Finish: Texture Foot: Black Front bezel: Black Rear cover: Black

### What's in the box?

Cables: HDMI cable, DP cable, USB-C to C cable, USB-C to A cable, Power cable

Monitor with stand **User Documentation** 

\* For Video transmission via USB-C, your Notebook/device

must support USB-C DP Alt mode

- \* Activities such as screen sharing and online streaming over the Internet can impact your network performance. Your hardware and network bandwidth will determine the overall audio and video quality.
- \* For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details
- \* "IPS" word mark / trademark and related patents on technologies belong to their respective owners.
- \* The maximum resolution works for either USB-C, DP or HDMI input.
- \* Response time value equal to SmartResponse
- \* NTSC Area based on CIE 1976
- \* sRGB Area based on CIE1931
- \* If your Ethernet connection seems slow, please enter the OSD menu and select USB 3.0 or a higher version that can support the LAN speed up to 1G.
- \* EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in your country
- \* The monitor may look different from feature images.



© 2025 Koninklijke Philips N.V. All Rights reserved

Issue date 2025-02-19 Version: 7.0.1

EAN: 87 12581 75249 1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

