[field not found 'leaflet_type'] (2021, May 19)



LCD monitor

- V Line
- 21 (Viewable 20.7" / 52.6 cm) 1920 x 1080 (Full HD)

216V6LHSB2/89

Great LED images in vivid colors

Enjoy vivid LED pictures on this Philips display. Equipped with HDMI, it's a great choice!

Benefits

Vivid pictures every time

- LED technology for vivid colors
- SmartContrast for rich black details
- 16:9 Full HD display for crisp detailed images

Experience immersive multimedia

• HDMI-ready for Full HD entertainment

Features

LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of LCD backlight, resulting in super high contrast ratio. It also gives superior color reproduction thanks to consistent brightness across the screen.

Great choice

- Mercury Free eco-friendly display
- Compact design saves space
- · VESA mount allows for flexibility

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is



selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 \times 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colors expect a true to life picture.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables highquality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

Specifications

[field not found 'disclaimer_text']

Picture/Display

LCD panel type Backlight type Panel Size Effective viewing area Aspect ratio Optimum resolution Response time (typical) Brightness SmartContrast Contrast ratio (typical) Pixel pitch Viewing angle TFT-LCD W-LED system 20.7 inch / 52.6 cm 457.92 (H) x 257.58 (V) 16:9 1920 x 1080 @ 60 Hz 5 ms 200 cd/m²

10,000,000:1 600:1

0.2385 x 0.2385 mm 90° (H) / 65° (V) @ C/R > 10 16.7 M 30 -83 kHz (H) / 56 -76 Hz (V) Yes

Connectivity

sRGB

Display colors

Scanning Frequency

Signal Input

Sync Input

Audio (In/Out)

Convenience User convenience

OSD Languages

VGA (Analog) HDMI (digital, HDCP) Separate Sync Sync on Green HDMI audio out

Power On/Off Menu/OK Brightness/Back 4:3 Wide/Up Auto/Down Brazil Portuguese Czech Dutch English

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

Other convenience

Plug & Play Compati-

bility

Italian Japanese Korean Polish Portuguese Russian Simplified Chinese Spanish Swedish Traditional Chinese Turkish Ukranian Kensington lock VESA mount (100x100mm) DDC/CI Mac OS X sRGB

Windows 10 / 8.1 / 8 / 7

-5/20 degree

Finnish

French

Greek

German

Hungarian

Stand

Tilt

Power

On mode Standby mode Off mode Power LED indicator Power supply 24.87 W (typ.), 28.59 W (max.) 0.5 W (typ.) 0.3 W (typ.) Operation - White Standby mode- White (blinking) External 100-240VAC, 50-60Hz

data subject to change 2021, May 19

-					
Di	m	on	21	\mathbf{n}	21
		CII	5	0	13

Product with stand	488 x 365 x 200 mm
(mm) Product without	488 x 295 x 39 mm
stand (mm) Packaging in mm	560 x 427 x 110 mm
(WxHxĎ)	

Weight

0	
Product with stand	2.10 kg
(kg)	
Product without	1.82 kg
	1.02 Kg
stand (kg)	
Product with pack-	3.27 kg
aging (kg)	-

Operating conditions

Temperature range	0°C to 40°C °C
(operation)	
Temperature range	-20°C to 60°C °C
(storage)	
Relative humidity	20%-80 %

Altitude MTBF

Operation: +12,000ft (3,658m), Non-operation: +40,000ft (12,192m) 50,000 (Excluding backlight) hour(s)

Sustainability

Environmental and RoHS energy Recyclable packaging material

Mercury Free 100 %

Compliance and standards **Regulatory Approvals**

CEL WEEE СВ CCC CE Mark

Cabinet

Color Finish

Black Glossy / textured



data subject to change 2021, May 19

Version: 3.0.1 EAN: 8712581759209 © 2021 Koninklijke Philips N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com