

Philips Monitor USB-C monitor

5000 series 27" (68.6 cm) 3840 x 2160 (4K UHD)

27E1N5900E

Simplify your connections with USB-C

This Philips USB-C monitor offers clutter-free setup. With a single cable you can view video, and charge your laptop. Elegant ergonomic base provides excellent cable management. Elevate your viewing experience for work and play.

Features designed for you

- EasySelect menu toggle key for quick on-screen menu access
- · EasyRead mode for a paper-like reading experience
- MultiView enables simultaneous dual connection and view
- Cable management reduces cable clutter for neat workspace
- LowBlue mode and Flicker-free easy-on-the eyes viewing
- Tilt, pivot and height-adjust for an ideal viewing position

Single cable USB-C connection

· Magnify screen and recharge a device by one cable

Superb Picture Quality

- SmartContrast for rich black details
- IPS LED wide view technology for image and color accuracy
- UltraClear 4K UHD (3840x2160) resolution for precision
- SmartImage game mode optimized for gamers



USB-C monitor 5000 series 27" (68.6 cm), 3840 x 2160 (4K UHD)


27E1N5900E/93

Highlights

USB-C connectivity


This Philips monitor features a built-in USB-C connector which meets USB Power Delivery standard. With intelligent and flexible power management, you can power charge your compatible device directly from the monitor using a single USB-C cable. Its slim, reversible USB-C allows for easy connection, you can watch high resolution video from your laptop.

IPS technology



IPS displays use an advanced technology which gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colors, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand color accuracy and consistent brightness at all times.

UltraClear 4K UHD Resolution



These Philips displays utilize high performance panels to deliver UltraClear, 4K UHD (3840 x 2160) resolution images. Whether you are demanding professional requiring extremely detailed images for CAD solutions, using 3D graphics applications or a financial wizard working on huge spreadsheets, Philips displays will make your images and graphics come alive.

SmartImage Game mode




The new Philips gaming display has quick access OSD fine tuned for gamers, offering you multiple options. "FPS" mode (First person shooting) improves dark themes in games, allowing you to see hidden objects in dark areas. "Racing" mode adapts display with fastest response time, high color, along with image adjustments. "RTS" mode (Real time strategy) has a special SmartFrame mode which enables highlighting of specific area and allows for size and image adjustments. Gamer 1 and Gamer 2 enable you to save personal customized settings based on different games, ensuring best performance.

LowBlue Mode & Flicker-free



Our LowBlue Mode and Flicker-free technology have been developed to reduce eye strain and fatigue often caused by long hours in front of a monitor.

MultiView technology



With the ultra-high resolution Philips MultiView display you can now experience a world of connectivity. MultiView enables active dual connect and view so that you can work with multiple devices like a PC and notebook simultaneously, for complex multi-tasking.

Compact Ergo Base



The Compact Ergo Base is a people-friendly Philips monitor base that tilts, pivot and heightadjusts so each user can position the monitor for maximum viewing comfort and efficiency.

Cable management



Cable management is an intimate design that maintains tidy workspace by organizing cables and wires required for the operation of a display device.

EasyRead mode



EasyRead mode for a paper-like reading experience





















Specifications

Picture/Display

- Panel Size: 27 inch / 68.6 cm
- Aspect ratio: 16:9
- LCD panel type: IPS technology
- Backlight type: W-LED system
- Pixel pitch: 0.1554 x 0.1554 mm
- Brightness: 350 cd/m²
- Display colors: Color support 1.07 billion colors • Color gamut (typical): NTSC 109.21%*, sRGB 100%*
- Contrast ratio (typical): 1200:1
- SmartContrast: Mega Infinity DCR
- Response time (typical): 4 ms (Gray to Gray)* • Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Picture enhancement: SmartImage game
- Maximum resolution: 3840 x 2160 @ 60 Hz*
- Effective viewing area: 596.736 (H) x 335.664 (V) • Scanning Frequency: 30 - 114 kHz (H) / 48 - 60 Hz (V)
- sRGB
- Delta E: < 2 (sRGB)
- Flicker-free
- Pixel Density: 163.18 PPI
- LowBlue Mode
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
 SmartUniformity: 93 ~ 105%
- EasyRead
- Adaptive sync

Connectivity

- Signal Input: HDMI 2.0 x 1, DisplayPort 1.2 x 1, USB-C x 1 (video, DP Alt mode, Power Delivery up to 65W)
- Sync Input: Separate Sync
- Audio (In/Out): Audio out
- HDCP: HDCP 1.4 / HDCP 2.2 (HDMI / DisplayPort / USB-C)

Power Delivery

- Max power delivery: Up to 65W (5V/3A, 7V/3A, 9V/3A, 10V/3A, 12V/3A, 15V/3A, 20V/3.25A)
- Version: USB PD version 3.0

Convenience

- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 11 / 10 / 8.1 / 8 / 7
- User convenience: Power On/Off, Menu, Brightness, Input, SmartImage Game
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian

- Other convenience: Kensington lock, VESA mount (100x100mm)
- MultiView: PIP (2x devices), PBP (2x devices)

Stand

- Height adjustment: 130 mm
- Pivot: -/+ 90 degree
- Tilt: -5/20 degree

Power

- Power supply: Internal, 100-240VAC, 50-60Hz
- Off mode: 0.3 W (typ.)
- On mode: 33.1 W (typ.)
- Standby mode: 0.5 W (typ.)
- · Power LED indicator: Operation White, Standby mode- White (blinking)

Dimensions

- Packaging in mm (WxHxD): 780 x 525 x 186 mm
- Product without stand (mm): 613 x 365 x 53 mm
- Product with stand(max height): 613 x 510 x 212 mm

Weight

- Product with packaging (kg): 10.98 kg
- Product with stand (kg): 6.90 kg
- Product without stand (kg): 5.03 kg

Operating conditions

- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- Temperature range (operation): 0 to 40 °C
- MTBF: 50,000 hrs (excluding backlight) hour(s)
- Relative humidity: 20%-80 %
- Temperature range (storage): -20 to 60 $^\circ\text{C}$

Sustainability

- Environmental and energy: RoHS
- Recyclable packaging material: 100 %
- · Specific Substances: Mercury free, PVC / BFR free housing

Compliance and standards

 Regulatory Approvals: CB, CE Mark, FCC Class B, ICES-003, CCC, CECP, CEL

Cabinet

- Color: Black
- Finish: Textured

Design

• Designed in Amsterdam, NL



© 2024 Koninklijke Philips N.V. Issue date 2024-10-28 * Response time value equal to SmartResponse NTSC Area based on CIE1976 All Rights reserved. * SRGB Coverage based on CIE1731 * For USB-C power and charging function, your Notebook/device Version: 3.0.1 Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners. details

EAN: 69 51613 92178 4 www.philips.com * "IPS" word mark / trademark and related patents on technologies belong to their respective owners.

- The maximum resolution works for either HDMI input or DP input. * For best output performance, please always ensure that your graphic
 - ord is capile of achieving the maximum resolution and refresh rate of this Philips display.

 - must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more ^k For Video transmission via USB-C, your Notebook/device must
 - support USB-C DP Alt mod
 - * The monitor may look different from feature images.

E1N5900E/93