

P-Line Display

- 55
- · Powered by Android
- 700cd/m²

55BDL5057P/00

Tough and capable

Robust, bright 24/7 display.

Meet the demands of challenging environments with a robust P-Line professional Full HD display. Tough components keep this display working from kitchen to engine room. The wide viewing angle ensures crucial information is clear.

Benefits

Brilliant picture. Strong build.

- Android SoC processor. Native and web apps
- · D-image:clinically accurate imaging
- IPS panel: rich color consistency from every angle
- · Robust metal housing

Effortless setup. Total control.

- Operate, monitor and maintain with CMND & Control
- CMND & Create. Develop and launch your own content
- CMND & Deploy. Install and launch apps remotely

Features

Powered by Android

Control your display via an Internet connection. Android-powered Philips Professional Displays are optimized for native Android apps, and you can

- Integrated mPCle slot for optional 4G/LTE module
- Proof of Play for Android content. Know what's playing

Robust system solution

- FailOver ensures content is always playing
- OPS slot allows for PC embedding without cabling
- Energy-saving automatic backlight control
- Integrated HTML5 browser. Play and control online content



install web apps directly to the display too. A new Android OS ensures the software is kept secure and remain to the latest specification for longer.

integrated widgets ensure your stills, text, and video will be up and running in no time.

D-image



This Philips Professional Display is factory-calibrated to meet clinical compliance standards for greyscale performance. The optimal image achieved by the display can be used to review medical images in consultation rooms or lecture theatres.

CMND & Deploy

Quickly install and launch any app-even when you're off-site and working remotely. CMND & Deploy lets you add and update your own apps, as well as apps from the Philips Professional Display App Store. Simply scan the QR code, log in to the store, and click on the app you want to install. The app is automatically downloaded and launched.

Integrated mPCle slot

Easily connect 4G/LTE modules to your Philips professional display. The integrated mPCle slot enables your display to communicate with other devices that share the same wireless connectivity. Invaluable if you're installing displays in locations such as banks or government buildings, where you cannot get onto the local network.

CMND & Control







Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.

CMND & Create



Take control of your content with CMND & Create. A drag-and-drop interface makes it simple to publish your own content-whether it's a daily specials board or branded corporate information. Preloaded templates and





Integrate a full-power PC or Android-powered CRD50 module directly into your Philips Professional Display. The OPS slot contains all the connections you need to run your slot-in solution, including a power supply.

Specifications

[field not found 'disclaimer_text']

Picture/Display

Diagonal screen size 54.6 inch (inch) Diagonal screen size 138.78 cm (metric) 1920×1080p Panel resolution 1920 x 1080 @ 60Hz Optimum resolution Brightness 700 cd/m² 1300:1 Contrast ratio (typical) 500,000:1 Dynamic contrast

ratio
Aspect ratio 16:9
Response time 8 ms

(typical)

Pixel pitch 0.63 x 0.63 mm
Display colors 1.07 billion
Viewing angle (horizontal) 178 degree

178 degree

Viewing angle (vertical)

Operating system Android 5.1.1

Connectivity

Video input

Display Port1.2 (x1)

DVI-I (x 1)

HDMI 1.4 (x2)

USB 2.0 (x2)

USB 2.0 (x1)

Video output

DVI-I (x1)

DisplayPort 1.2 (x1)

DisplayPort 1.2 (x1)
Audio input 3.5 mm jack
Audio output 3.5mm jack
Other connections OPS

Micro SD (x1) Micro USB(type B)x1

Optional WiFi func- requires WiFi module and external

tionality antennas External control RJ45

RS232C (in/out) 2.5 mm jack IR (in/out) 3.5 mm jack

Supported Display Resolution

Computer formats 1920 x 1080, 60Hz

1360 x 768, 60Hz 1280 x 800, 60Hz 1280 x 768, 60Hz

1024 x 768, 60, 75Hz AC Power Cord 1280 x 1024, 60Hz RS232 cable Edge Alignment Kit (1)-2pcs 1600 x 1200, 60Hz Included Accessories Edge Alignment Kit (2)-1pcs 640 x 480, 60, 72, 75Hz $720 \times 400, 70$ Hz Logo guide $800 \times 600, 60, 75$ Hz Philips logo (x1) 1080p, 50, 60Hz 720p, 50, 60Hz 576p, 50Hz Thumbscrew (8pcs) Video formats RS232 daisy-chain cable BM04642/00(optional) Stand 480p, 60Hz 1080i, 25, 30Hz Multimedia Applications 480I, 30Hz USB Playback Audio AAC 576i, 25Hz M4A MP3 **Dimensions** WMA Set Width 1228.6 mm MP1 Set Height 699.4 mm MP2 Set Depth 71.1 mm USB Playback Picture **BMP** Set Width (inch) 48.4 inch **GIF** Set Height (inch) 27.6 inch **JPEG** Set Depth (inch) 2.80 inch JPG Bezel width 6.5 mm PNG Product weight (lb) 55.6 lb USB Playback Video MKV Product weight 25.2 kg MP4 400 x 400 mm, M6 **VESA Mount** MPG TS Convenience VOB 3GP **Placement** Landscape AVI Portrait DAT Up to 15 x 15 Tiled Matrix FLV Keyboard control Hidden MOV Lockable WEBM Signal loop through DVI VGA Miscellaneous RS232 IR Loopthrough On-Screen Display English DisplayPort Languages French Network controllable German RJ45 **RS232** Spanish HDMI (One Wire) Polish Energy saving func-Smart Power Turkish Russian Screen saving func-Pixel Shift, Low Bright Italian Simplified Chinese tions Ease of installation AC Out Traditional Chinese Carrying Handles Arabic Other convenience G sensor Japanese Danish Power Dutch **Finnish** Standby power <0.5 W Norwegian consumption Portuguese 100 ~ 240 VAC, 50 ~ 60 Hz Mains power Swedish Consumption 110 W BSMI Regulatory approvals (Typical) CB Consumption (Max) 245 W CCC Energy Label Class G CE CECP Operating conditions FAC Temperature range 0 ~ 40 °C **EMF** (operation) EnergyStar 7.0 Temperature range -20 ~ 60 °C PSB UL/cUL (storage) 20 ~ 80 % Relative humidity VCCI 0 ~ 3000 m FCC, Class A Altitude **MTBF** 60,000 hour(s) Warranty 3 year warranty Sound Internal Player 2 x 10W RMS Built-in speakers CPU Octacore Cortex A53 1.5GHz GPU Accessories PowerVR SGX6110 Memory 2GB DDR3

Storage

Remote Control

Quick start guide

Batteries for remote control

Included accessories

16GB EMMC



data subject to change 2021, June 5

Version: 10.2.1 EAN: 8712581742270 © 2021 Koninklijke Philips N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com