

Philips Brilliance LCD monitor with PowerSensor

**B Line** 24 (23.8" / 60.5 cm diag.) 1920 × 1080 (Full HD)

241B7QPJEB

# Crisp views, efficient performance

### with PowerSensor

The Philips PowerSensor display using 85% post consumer recycled plastics and PVC, BFR free housing is ideal for eco-friendly productivity

#### **Brilliant performance**

- SmartImage presets for easy optimized image settings
- · IPS technology for full colors and wide viewing angles
- · Narrow border display for a seamless appearance

#### Features for the way you work

- Built-in stereo speakers for multimedia
- $\bullet \ \, \text{SmartConnect with DisplayPort, HDMI and VGA connections} \\$
- USB 3.0 enables fast data transfers and smart phone charging

#### Sustainable Eco-design

- PowerSensor saves up to 70% energy costs
- · Designed to meet environmental standards


#### Designed for comfortable productivity

- SmartErgoBase enables people-friendly ergonomic adjustments
- · Less eye fatigue with Flicker-free technology
- LowBlue Mode for easy on-the-eyes productivity



## Highlights

#### **IPS** technology



IPS displays use an advanced technology which gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from almost any angle - even in 90 degree Pivot mode! Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colors, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand color accuracy and consistent brightness at all times.

#### **UltraNarrow Border**



The new Philips displays feature ultra-narrow borders which allow for minimal distractions and maximum viewing size. Especially suited for multi-display or tiling setup like gaming, graphic design and professional applications, the ultra-narrow border display gives you the feeling of using one large display.

#### **SmartImage**



SmartImage is an exclusive leading edge Philips technology that analyzes the content displayed

on your screen and gives you optimized display performance. This user friendly interface allows you to select various modes like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, Smartlmage dynamically optimizes the contrast, color saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time with the press of a single button!

#### LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

#### Flicker-free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

#### **SmartErgoBase**



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base can swivel, tilt and rotate to various angles to ensure maximum comfort. The height adjustable stand guarantees the optimal viewing level, reducing the physical strains of a long workday, while cable management reduces cable clutter and keeps the workspace neat and professional.

#### **USB 3.0 super speed**

Super Speed USB 3.0 deploys 5.0 gbit/s transfer rate, which is about 10 times faster than USB 2.0 standard significantly reducing data transfer time saving you time and money. With more bandwidth, super speed transfer rates, better power management and superior overall performance, USB 3.0 sets the global standard allowing you to use the large capacity storage devices. Sync-N-Go technology ensures you don't have to wait anymore for bandwidth to be freed up. Your investment in USB 2.0 devices is protected as it is backward compatible.

#### **SmartConnect**

With a plethora of connectivity, these Philips displays come equipped with multi connections like VGA, Display Port, universal HDMI connector, enabling you to enjoy high resolution uncompressed video and audio content. USB connections ensures that you can have super speed data transfers while having global connectivity. Regardless of what source you use, you can rest assured that this Philips display will ensure your investment is not made obsolete any time soon!



















## **Specifications**

#### Connectivity

- Signal Input: VGA (Analog), DisplayPort 1.2, HDMI
- USB: USB 3.0x2 (1 w/fast charging)\*
- Sync Input: Separate Sync, Sync on Green
- Audio (In/Out): PC audio-in, Headphone out

#### Picture/Display

- Panel Size: 23.8 inch / 60.5 cm
- Aspect ratio: 16:9
- LCD panel type: IPS technology
- Backlight type: W-LED system
- Pixel pitch: 0.275 x 0.275 mm
- Optimum resolution: 1920 x 1080 @ 60Hz
- Brightness: 250 cd/m<sup>2</sup>
- Display colors: 16.7 M
- Contrast ratio (typical): 1,000:1
- SmartContrast: 20,000,000:1
- Response time (typical): 5 ms (Gray to Gray)\*
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- · Picture enhancement: SmartImage
- Effective viewing area: 527 (H) x 296.5 (V)
- Scanning Frequency: 30 83 kHz (H) / 56 76 Hz (V)
- sRGB
- · Flicker-free
- Display Screen Coating: Anti-Glare, 3H, Haze 25%

#### **Convenience**

- Built-in Speakers: 2 W x 2
- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7
- User convenience: SmartImage, Input, PowerSensor, Menu, Power On/Off, Low Blue Mode
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
- · Other convenience: Kensington lock, VESA mount (100x100mm)
- · Control software: SmartControl

#### Stand

- · Height adjustment: 130 mm
- · Pivot: 90 degree
- Swivel: -175/175 degree
- Tilt: -5/20 degree

- ECO mode: 10.3 W (typ.)
- Power supply: Built-in, 100-240VAC, 50-60Hz
- Off mode: Zero watts with Zero switch
- On mode: 13.14 W (typ.) (EnergyStar test method)
   Standby mode: <0.3 W (typ.)
- · Power LED indicator: Operation White, Standby mode- White (blinking)

#### **Dimensions**

- Packaging in mm (WxHxD): 603 x 492 x 187 mm
- Product without stand (mm):  $541 \times 332 \times 57 \text{ mm}$
- Product with stand(max height): 541 x 492 x 257 mm

#### Weight

- Product with packaging (kg): 8.26 kg
- · Product with stand (kg): 5.83 kg
- Product without stand (kg): 3.52 kg

#### **Operating conditions**

- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- Temperature range (operation): 0°C to 40°C °C
- $\bullet$  Relative humidity: 20%-80 %
- Temperature range (storage): -20°C to 60°C °C
- MTBF (demonstrated): 70,000 hrs (excluded backlight)

#### **Sustainability**

- Environmental and energy: EnergyStar 8.0, PowerSensor, EPEAT\*, TCO Certified Edge, RoHS
- Post consumer recycled plastic: 85%
- Recyclable packaging material: 100 %
- · Specific Substances: PVC / BFR free housing, Mercury free

#### Compliance and standards

· Regulatory Approvals: CE Mark, FCC Class B, SEMKO, cETLus, CU-EAC, TUV Ergo, TUV/GS, EPA, WEEE, ICES-003, UKRAINIAN, MEPS, PSB,

#### **Cabinet**

- · Finish: Texture
- Foot: Black
- · Front bezel: Black
- · Rear cover: Black



Issue date 2024-03-24

EAN: 87 12581 74938 5

© 2024 Koninklijke Philips N.V. All Rights reserved.

Version: 5.0.2

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

\* Response time value equal to SmartResponse

st "IPS" word mark / trademark and related patents on technologies belong to their respective owners.

<sup>\*</sup> EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in your country.

\* Fast charging complies with USB BC 1.2 standard