

Q-Line Display

- 3840 x 2160 (4K UHD) Ultra HD

86BDL3050O/00

Show more

Simple, smart, sharp 18/7 display.

Turn up the stopping power with the Q-Line UHD Android display that goes big on resolution. Benefit from fast, hardware-free installation and superb picture quality. Easily display online and local content.

Benefits

Superb picture. Smooth performance

- Android SoC processor. Native and web apps
- Ultra-HD. Rich images. Stunning contrast

Effortless setup. Total control.

- Remote system management through CMND
- Operate, monitor and maintain with CMND & Control
- CMND & Create. Develop and launch your own content
- CMND & Deploy. Install and launch apps remotely

Cost-effective system solution

- Internal memory. Upload content for instant play
- · Energy-saving automatic backlight control
- Integrated HTML5 browser. Play and control online content
- Integrated media player. Easily schedule USB content

Features

Powered by Android

Control your display via an Internet connection. Android-powered Philips Professional Displays are optimized for native Android apps, and you can

install web apps directly to the display too. A new Android OS ensures the software is kept secure and remain to the latest specification for longer.



CMND

Take control of your Philips Professional Display network. CMND lets you manage, update, maintain, and play via one easy-to-use interface. From installation to daily operation.

CMND & Control



CMND tent without the need for a permanent external player. Your al display has an internal memory, which allows you to the display for instant playback. The internal memory also MND & CONTROL ons as a cache for online streaming.

CMND & Deploy

Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

CMND & Create



Take control of your content with CMND & Create. A drag-and-drop interface makes it simple to publish your own content-whether it's a daily specials board or branded corporate information. Preloaded templates and integrated widgets ensure your stills, text, and video will be up and running in no time.

Specifications

[field not found 'disclaimer_text']

Picture/Display

1280 x 768, 60Hz Diagonal screen size 85.6 inch 1280 x 800, 60Hz 1280 x 1024, 60Hz (inch) Diagonal screen size 1360 x 768, 60Hz 217.4 cm 1600 x 1200, 60Hz (metric) 3840×2160 1920 x 1080, 60Hz Panel resolution Optimum resolution 3840 x 2160 @ 60 Hz 3840 x 2160, 30, 60Hz 410 cd/m² Video formats 480i, 30, 60Hz Brightness 480p, 30, 60Hz 576i, 25, 50Hz 1200:1 Contrast ratio (typical) 576p, 25, 50Hz Response time 8 ms (typical) 720p, 50, 60Hz

16:9 1080i, 25, 30Hz Aspect ratio Viewing angle (hori-1080p, 50, 60Hz 178 degree 2160p, 30,50, 60Hz zontal) Viewing angle 178 degree

(vertical) Connectivity Pixel pitch 0.4935 x 0.4935 mm VGA (Analog D-Sub) Video input

Display colors 1.07 Billion DisplayPort (1.2) Picture enhancement 3/2 - 2/2 motion pull down

HDMI (x4) 3D Combfilter USB 2.0 (x2) Progressive scan Audio input 3.5 mm jack 3D MA deinterlacing

Audio Left/Right (RCA) Audio output Dynamic contrast enhancement External control RS232C (in/out) 2.5 mm jack Color Enhancement

IR (in/out) 3.5 mm jack Color Temperature Adjustment **RI45** De-interlacer **OPS** Other connections

Noise Reduction AC-out **Smart Picture** Analog (D-sub input) Operating system Android 5.0.1 Analog audio Left/Right out Panel technology Display Port

Supported Display Resolution

Computer formats

HDMI

IR out 640 x 480, 60, 72, 75Hz micro SD 720 x 400, 70Hz PC Audio in $800 \times 600, 60, 75$ Hz RS232 Serial 1024 x 768, 60, 75Hz **USB 2.0**

USB power outlet (5 V. 2 amp) Quick start guide HDMI cable IR sensor cable (1.8M) Convenience Included Accessories RS232 daisy-chain cable Pixel Shift, Low Brightness Screen saving func-USB Cover and screw x1 Keyboard control Lockable Multimedia Applications Network controllable LAN (RJ45) RS232 USB Playback Video MKV Card OPS RS232 MP4 **MPEG** HDMI (One Wire) Signal loop through RS232 MPG IR Loopthrough TS Smart İnsert Ease of installation VOB AC Out WMV Carrying Handles **ASF** Energy saving func-Smart Power AVI DAT **Placement** Landscape (18/7) FLV Remote control MOV Lockable TRP Tiled Matrix Up to 10 x 15 **WEBM** USB Playback Picture Memory 8GB eMMC BMP JPEG **Dimensions** JPG PNG Bezel width 15.15 (Top/Left/Right) 16.0 (Bottom) USB Playback Audio AAC M4A 1927.9 mm Set Width MP3 Set Height 1098.9 mm **WMA** Set Depth 85.9 mm 75.90 inch Set Width (inch) Miscellaneous Set Height (inch) 43.26 inch Set Depth (inch) 2.06 inch Warranty 3 year warranty 63.8 kg 140.65 lb Product weight On-Screen Display Arabic Product weight (lb)

Operating conditions

VESA Mount

tions

tions

signal

0 ~ 3000 m Altitude 0 ~ 40 °C Temperature range (operation) -20 ~ 60 °C Temperature range

(storage) Relative humidity 20 ~ 80 (operation),10 - 90%(storage)

MTBF 50,000 hour(s)

Power

Mains power 100 ~ 240 VAC, 50 ~ 60 Hz 302 W Consumption (On

Smart Power

600 x 400 mm, M8

mode)

Consupmtion at 350 265W nits <0.5W

Standby power consumption

Power Saving **Features**

Energy Label Class

Sound

Built-in speakers 2 x 10W RMS

Accessories

Included accessories AC Power Cord RS232 cable Remote Control

Batteries for remote control

Languages

Simplified Chinese

Traditional Chinese

English French German Italian Polish Russian Spanish . Turkish Japanese Czech Danish Dutch Finnish Norwegian

Portuguese Swedish CE UL/cUL

Regulatory approvals СВ

FCC, Class B **BSMI** CCC EAC EMF EnergyStar 7.0

PSB

Internal Player Storage

8GB eMMC CPU Ouad Core Full HD 2GB DDR3 Memory



data subject to change 2021, March 5

Version: 16.3.1 EAN: 8712581743604 © 2021 Koninklijke Philips N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com