

Philips LCD monitor

S Line 24 (23.6" / 59.9 cm diag.) 1920 x 1080 (Full HD)

243S5LDAB

Essential features, efficient performance

for maximum productivity

The Philips LED display using PVC, BFR free housing is ideal for eco-friendly productivity

Experience multimedia

- HDMI-ready for Full HD entertainment
- Built-in stereo speakers for multimedia

Vivid pictures every time

- LED technology for vivid colors
- SmartContrast for rich black details
- 16:9 Full HD display for crisp detailed images

Great choice

- Compact design saves space
- Mercury Free eco-friendly display
- VESA mount allows for flexibility



LCD monitor S Line 24 (23.6" / 59.9 cm diag.), 1920 x 1080 (Full HD)

Highlights

LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of LCD backlight, resulting in super high contrast ratio. It also gives superior color reproduction thanks to consistent brightness across the screen.

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 x 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colors expect a true to life picture.

HDMI Ready



HDMI-ready

An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables high-quality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

Built-in stereo speakers



A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

Compact design saves space

Compact design saves space

VESA mount

VESA mount allows for flexibility

















243S5LDAB/01

Specifications

Connectivity

- Signal Input: DVI-D (digital, HDCP), VGA (Analog), HDMI 1.4
- Sync Input: Separate Sync, Sync on Green
- Audio (In/Out): PC audio-in, Headphone out

Picture/Display

- Panel Size: 23.6 inch / 59.9 cm
- Aspect ratio: 16:9
- LCD panel type: TFT-LCD
- Backlight type: W-LED system
- Pixel pitch: 0.272 x 0.272 mm
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 250 cd/m²
- Display colors: 16.7 M
- Contrast ratio (typical): 1000:1
- SmartContrast: 10,000,000:1
- Response time (typical): 1 ms (Gray to Gray)*
- Viewing angle: 170° (H) / 160° (V), @ C/R > 10
- Effective viewing area: 521.28 (H) x 293.22 (V)
- Scanning Frequency: 30 -83 kHz (H) / 56 -76 Hz (V)
- sRGB
- Display Screen Coating: Anti-Glare, 3H, Haze 25%

Convenience

- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7
- Built-in Audio: 2 W x 2
- User convenience: Power On/Off, Menu, Input, Volume, Auto/Down
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian
- Other convenience: Kensington lock, VESA mount (100x100mm)

Stand

• Tilt: -5/20 degree

Power

- Power supply: Built-in, 100-240VAC, 50-60Hz
- Off mode: 0.3 W (typ.)
- On mode: 15.3 W (typ.) (EnergyStar 7.0 test

method)

- Standby mode: 0.5 W (typ.)
- Power LED indicator: Operation White, Standby mode- White (blinking)
- Energy Label Class: E

Dimensions

- Product with stand (mm): 560 x 424 x 219 mm
- Packaging in mm (WxHxD): 608 x 419 x 121 mm
- Product without stand (mm): 560 x 348 x 53 mm

Weight

- Product with packaging (kg): 5.03 kg
- Product with stand (kg): 3.58 kg
- Product without stand (kg): 3.18 kg

Operating conditions

- Åltitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- Temperature range (operation): 0°C to 40°C °C
- Relative humidity: 20%-80 %
- Temperature range (storage): -20°C to 60°C °C
 MTBF (demonstrated): 70,000 hrs (excluded
- backlight)

Sustainability

- Environmental and energy: EnergyStar 7.0, RoHS,
- Mercury Free • Recyclable packaging material: 100 %

Compliance and standards

 Regulatory Approvals: CE Mark, FCC Class B, SEMKO, TCO Certified, cETLus, TUV/ISO9241-307, BSMI, PSB, RCM, UKRAINIAN, WEEE

Cabinet

- Color: Black
- Finish: Hairline / Texture

What's in the box?

- Cables: D-Sub cable, HDMI cable, Audio cable,
- Power cableMonitor with stand
- User Documentation
- Oser Documenta



* Response time value equal to SmartResponse

243S5LDAB/01