



275S9JAL



Reliable and essential

for daily efficiency

Our S Line monitor delivers business efficiency. Features like Flicker-free and LowBlue mode make work easy on the eyes and increase your productivity.

Perfectly designed for your space

- VESA mount allows for flexibility
- Built-in stereo speakers for multimedia

Features for the way you work

- DisplayPort connection for maximum visuals
- HDMI ensures universal digital connectivity
- USB 3.2 high-speed data transfer

Great performance

- VA display delivers awesome images with wide viewing angles
- SmartImage pre-sets for easy optimised image settings
- Crystal clear images with Quad HD 2560 x 1440 pixels

Designed for comfortable productivity


- EasyRead mode for a paper-like reading experience
- Less eye fatigue with Flicker-Free technology
- LowBlue Mode for easy-on-the-eyes productivity

Business Monitor

LCD monitor

Highlights

VA display



The Philips VA LED display uses an advanced multi-domain vertical alignment technology that gives you super-high static contrast ratios for extra-vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, web browsing, films, gaming and demanding graphical applications. Its optimised pixel management technology gives you a 178/178 degree extrawide viewing angle, resulting in crisp images.

CrystalClear images



These Philips screens deliver Crystal Clear, Quad HD 2560 x 1440 or 2560 x 1080 pixel images. Utilising high-performance panels with a highdensity pixel count, enabled by high bandwidth sources like USB-C, Displayport and HDMI, these new displays will make your images and graphics come alive. Whether you are a demanding professional who requires extremely detailed information for CAD-CAM solutions and uses 3D graphic applications, or a financial wizard working on huge spreadsheets, Philips displays will give you Crystal Clear images.

SmartImage



SmartImage is an exclusive leading edge Philips technology that analyses the content displayed on your screen and optimises your display performance. This user-friendly interface allows you to select various modes, like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimises the contrast, colour saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time at the touch of a single button!

Flicker-Free technology



Due to the way brightness is controlled on LEDbacklit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-Free technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave-length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, the Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

Built-in stereo speakers



A pair of high-quality stereo speakers built into a display device. They may be visible front firing, or invisible down firing, top firing, rear firing etc. depending on model and design.















Business Monitor

LCD monitor

Highlights

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. An HDMI cable enables high-quality digital video and audio to be transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

DisplayPort connection



DisplayPort is a digital link from PC to monitor without any conversion. With higher capabilities than DVI standard, it is fully capable to support up to 15 metre cables and 10.8 Gbps/sec data transfer. With this high performance and zero latency, you get the fastest imaging and refresh rates — making DisplayPort the best choice for not only general office or home use, but also for the more demanding gaming and films, video editing and more. It also keeps interoperability in mind via the use of various adapters.

EasyRead mode



EasyRead mode for a paper-like reading experience













Business Monitor

LCD monitor

Specifications

Picture/Display

Panel Size: 27 inch / 68.5 cm Aspect ratio: 16:9 LCD panel type: VA LCD Backlight type: W-LED system Pixel pitch: 0.2331 x 0.2331 mm Brightness: 300 cd/m² Display colours: 16.7 M (8 bit) Colour gamut (typical): NTSC 97%*, sRGB 119%* Contrast ratio (typical): 4000:1 SmartContrast: 50,000,000:1 Response time (typical): 4 ms (Grey to Grey)* Viewing angle: 178° (H)/178° (V), @ C/R > 10 Picture enhancement: SmartImage Maximum resolution: 2560 x 1440 @ 75 Hz* Effective viewing area: 596.736 (H) x 335.664 (V) Scanning Frequency: 30–114 kHz (H)/48–75 Hz (V) sRGB Flicker-free Pixel Density: 108.79 PPI LowBlue Mode Display Screen Coating: Anti-Glare, 3H, Haze 25% EasyRead Adaptive sync

Connectivity

Signal Input: HDMI 1.4 x 1, DisplayPort 1.2 x 1 Sync Input: Separate Sync Audio (In/Out): Audio out HDCP: HDCP 1.4 (HDMI/DisplayPort) USB Hub: USB 3.2 Gen 1 / 5 Gbps, USB-B upstream x 1, USB-A downstream x 2 (with 1 for fast charge B.C 1.2)

Convenience

Built-in Speakers: 2 W x 2 Plug and Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 11 / 10 / 8.1 / 8 / 7 User convenience: SmartImage/Back, Brightness/UP, Input/Down, Menu/OK, Power On/Off

OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian Other convenience: Kensington lock, VESA mount (100 x 100 mm) Control software: SmartControl

Stand

Tilt: -5/25 degree

Power

ECO mode: 15.1 W (typ.) Power supply: Built-in, 100-240 VAC, 50-60 Hz Off mode: 0.3 W (typ.) On mode: 17.9 W (typ.) (EnergyStar test method) Standby mode: 0.3 W (typ.) Power LED indicator: Operation - White, Standby mode - White (flashing) **Energy Label Class: F**

Dimensions

Packaging in mm (W x H x D): 690 x 453 x 141 mm Product without stand (mm): 614 x 367 x 55 mm Product with stand (max height): 614 x 477 x 226 mm

Weiaht

Product with packaging (kg): 7.00 kg Product with stand (kg): 5.10 kg Product without stand (kg): 4.46 kg

Operating conditions

Altitude: Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m) Temperature range (operation): 0°C to 40 °C MTBF: 70,000 (Excluding backlight) hour(s) Relative humidity: 20%-80 % Temperature range (storage): -20°C to 60 °C

Sustainability

Environmental and energy: EnergyStar 8.0, EPEAT*, TCO Certified Edge, RoHS Post-consumer recycled plastic: 85% Recyclable packaging material: 100 % Specific Substances: Mercury free, PVC/BFR free housing

Compliance and standards

Regulatory Approvals: CB, CE Mark, CU-EAC, EAEU RoHS, FCC Class B, ICES-003, TUV Ergo, TUV/GS

Cabinet

Finish: Textured Foot: Black Front bezel: Black Rear cover: Black

© 2025 Koninklijke Philips N.V. All Rights reserved

Specifications are subject to change without notice. Trademarks are the

property of Koninklijke Philips N.V. or

their respective owners.

Issue date 2025-02-19 Version: 4.1.3

EAN: 87 12581 79641 9



* Response time value equal to SmartResponse

- * The maximum resolution works for either HDMI input or DP input
- * NTSC Area based on CIE 1976
- * sRGB Area based on CIE1931
- * EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in your country
- * The monitor may look different from feature images.

What's in the box?

Cables: HDMI cable Power cable Monitor with stand User Documentation

www.philips.com