

Multi-Touch Display

- 55'
- Powered by Android
- Multi-touch

55BDL4051T/00

Engage them

10-point Multi-Touch display.

Inspire collaboration. Deliver information. This responsive Philips Multi-Touch Professional Full HD Display is ideal for multi-finger, multi-user applications-from wayfinding to presentations. Up to 10 touch points can be active at once.

Benefits

Superb picture. Responsive touchscreen.

- Android SoC processor. Native and web apps
- Full HD. Clear images. Crisp contrast
- Plug-and-play 10-point Multi-Touch display

Effortless setup. Total control.

- CMND & Deploy. Install and launch apps remotely
- Operate, monitor and maintain with CMND & Control

• CMND & Create. Develop and launch your own content

Versatile system solution

- FailOver ensures content is always playing
- Internal memory. Upload content for instant play
- Energy-saving automatic backlight control



Features

Powered by Android

Control your display via an Internet connection. Android-powered Philips Professional Displays are optimized for native Android apps, and you can install web apps directly to the display too. A new Android OS ensures the software is kept secure and remain to the latest specification for longer.

CMND & Deploy

Quickly install and launch any app-even when you're off-site and working remotely. CMND & Deploy lets you add and update your own apps, as well as apps from the Philips Professional Display App Store. Simply scan the QR code, log in to the store, and click on the app you want to install. The app is automatically downloaded and launched.

FailOver





From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.

CMND & Control





tent without the need for a permanent external player. Your al display has an internal memory, which allows you to the display for instant playback. The internal memory also ne for online streaming.

Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

CMND & Create



Take control of your content with CMND & Create. A drag-and-drop interface makes it simple to publish your own content-whether it's a daily specials board or branded corporate information. Preloaded templates and integrated widgets ensure your stills, text, and video will be up and running in no time.

Specifications

[field not found 'disclaimer_text']

Picture/Display

Diagonal screen size 138.8 cm (metric)

Diagonal screen size

(inch)

Panel resolution Optimum resolution 1920 x 1080 @ 60 Hz Brightness

1100:1 Contrast ratio (typical)

Dynamic contrast

Surface treatment Aspect ratio

Response time 12 ms (typical)

Pixel pitch Display colors Viewing angle (hori-

zontal) Viewing angle (vertical)

Picture enhancement

54.64 inch

1920×1080p

450 cd/m²

500,000:1

Anti-Glare coating 16:9

 $0.63 \times 0.63 \text{ mm}$ 16.7 million 178 degree

178 degree

3/2 - 2/2 motion pull down 3D Combfilter

Motion compens. deinterlacing

Interactivity

Multi-touch technology

Touch points Plug and play

Protection glass

Infrared touch

Progressive scan

3D MA deinterlacing

10 simultaneous touch points HID compliant

Dynamic contrast enhancement

5 mm tempered safety glass

Anti-Glare

Connectivity

Display Port1.2 (x1) Video input

DVI-I (x 1) HDMI 1.4 (x2) USB 2.0 (x2) USB 2.0 (x1) DisplayPort (x1)

Video output DVI-I (x1)

Audio input 3.5 mm jack 3.5mm jack Audio output External control **RI45**

IR (in/out) 3.5 mm jack

data subject to change 2021, March 5

Power RS232C (in/out) 2.5 mm jack 100 ~ 240 VAC, 50/60Hz Other connections micro SD Mains power Micro USB(type B)x1 <0.5W Standby power consumption Supported Display Resolution 76 W Consumption (Typical) Computer formats 640 × 480, 60, 67, 72, 75Hz Power Saving Smart Power 800×600 , 56, 60, 72, 75Hz **Features** 1024 x 768, 60Hz **Energy Label Class** 1280 x 768, 60Hz 1280 x 800, 60Hz Accessories 1280 x 1024, 60Hz 1360 x 768, 60Hz Included accessories AC Power Cord 1366 x 768, 60Hz RS232 cable 1440 × 900, 60Hz Remote Control 1600 x 1200, 60Hz Batteries for remote control 1920 x 1080, 60Hz Quick start guide 1920 x 1200, 60Hz User manual on CD-ROM Universal Stand (Large size)(Optional) $720 \times 400, 70$ Hz Stand 800 x 600, 60, 72, 75Hz Included Accessories Logo guide Video formats 480i, 60Hz 480p, 60Hz Miscellaneous 576p, 50Hz On-Screen Display Arabic 576i, 50Hz English Languages 720p, 50, 60Hz French 1080i, 50, 60Hz German 1080p, 50, 60Hz Italian 1080i, 25, 30Hz Japanese 480i, 30, 60Hz Polish 576i, 25, 50Hz Spanish . Turkish Convenience Russian Simplified Chinese **Placement** Landscape Traditional Chinese **Portrait** Signal loop through IR Loopthrough Danish Dutch DisplayPort DVI Finnish RS232 Norwegian Network controllable RS232 Portuguese Swedish **RI45** BSMI HDMI (One Wire) Regulatory approvals Picture performance Advanced color control CB Picture in picture CE Screen saving func-Pixel Shift, Low Brightness EAC FCC, Class B tions Keyboard control Hidden **PSE** Lockable CCC Remote control Lockable **PSB** signal **RoHS** Energy saving func-Smart Power UL Warranty tions 3 year warranty Other convenience Carrying handles 16GB eMMC Multimedia Applications Memory **USB Playback Picture BMP Dimensions** GIF Set Width 1271.0 mm **IPEG** 741.8 mm JPG Set Height 91.4 mm Set Depth PDF Set Width (inch) 50.04 inch USB Playback Audio AAC Set Height (inch) 29.20 inch AIF Set Depth (inch) 3.60 inch AIFF Product weight ASF 31 kg 68.34 lb Product weight (lb) **LPCM** VESA Mount 400 x 400 mm, M6 M3U Bezel width 29.2 mm M4A MP3 MP4 Sound WAV 2 x 10W Built-in speakers WMA USB Playback Video M2TS Operating conditions M4V 0 - 40degC (Landscape)/0 - 35degC (Portrait) °C MK3D Temperature range (operation) MKV Relative humidity 20 ~ 80(operation),5~95%(storage) % MP4 50,000 hour(s) **MPEG MTBF** 0 ~ 3000 m MPG Altitude -20~60 °C MTS Temperature range (storage) TS TTS

VOB

WMV

Memory Storage 2GB DDR3 16GB EMMC

Internal Player

CPU

Quad Core Cortex A9, 1.6G



data subject to change 2021, March 5

Version: 8.0.1 EAN: 8712581739669 Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.