

Philips Momentum 4K HDR display with Ambiglow

Momentum 43 (42.51" / 108 cm diag.) 3840 x 2160 (4K UHD)



436M6VBPAB

Get in the moment

Experience a new level of entertainment immersion with the new Momentum 4K HDR display with Ambiglow lighting. An expansive 4K UHD display with DisplayHDR 1000 delivers ultra-crisp and vibrant image quality that will get you in the moment.

PHILIPS

Superb Picture Quality

- Quantum Dot Tech for see-it-to-believe-it color
- DisplayHDR 1000 for truly vivid details and realism

Brilliant performance

- · Ambiglow intensifies entertainment with halo of light
- Effortlessly smooth action with Adaptive-Sync technology
- Enhanced audio with DTS Sound™
- Low input lag reduces time delay between devices to monitor

Expand your viewing experience


- · MultiView enables simultaneous dual connection and view
- UltraClear 4K UHD (3840x2160) resolution for precision

Designed for the way you work

- All your connections through one USB-C cable
- USB 3.0 Hub for convenient access and fast charging

Highlights

UltraClear 4K UHD Resolution



These Philips displays utilize high performance panels to deliver UltraClear, 4K UHD (3840 x 2160) resolution images. Whether you are demanding professional requiring extremely detailed images for CAD solutions, using 3D graphics applications or a financial wizard working on huge spreadsheets, Philips displays will make your images and graphics come alive.

MultiView technology



With the ultra-high resolution Philips MultiView display you can now experience a world of connectivity. MultiView enables active dual connect and view so that you can work with multiple devices like a PC and notebook simultaneously, for complex multi-tasking.

VESA DisplayHDR 1000



VESA-certified DisplayHDR 1000 delivers a dramatically different visual experience vs. other 'HDR compatible' screens. Extreme deep blacks and bright whites contrast with brilliant colors, to bring out details that you've never experienced before. Gamers can spot enemies hiding the dark corners and shadows easily, and movie viewers can enjoy a more compelling and lifelike show. This Philips Momentum comes with several HDR modes, each optimized for your usage scenarios: HDR Game, HDR Movie, and HDR Photo.

Quantum Dot Technology



Quantum Dot Technology is an innovative semiconductor nanocrystal technology that precisely emits light to produce bluer blues, greener greens and redder reds. LCD monitors with Quantum Dot color produce a more dynamic range of colors and show the true natural palette of colors in the picture. The result - vibrant, dynamic, you-gotta-see-itto-believe-it color.

Ambiglow Technology



Ambiglow adds a new dimension to your viewing experience. The innovative Ambiglow technology enlarges the screen by creating an immersive halo of light. Its fast processor analyses the incoming image content and continuously adapts the color and brightness of the emitted light to match the image. User friendly options allow you to adjust the ambiance to your liking. Especially suited for watching movies, sports or playing games, Philips Ambiglow offers you a unique and immersive viewing experience.

DTS Sound™



DTS Sound is an audio processing solution designed to optimize the playback of music, movies, streaming and games on the PC regardless of form factors. DTS Sound enables an immersive virtual surround sound experience, complete with rich bass and dialog enhancement and maximized volume levels free of any clipping or distortion.

Low Input Lag



Input lag is the amount of time that elapses between performing an action with connected devices and seeing the result on screen. Low input lag reduces the time delay between entering a command from your devices to monitor, greatly improve on playing twitchsensitive video games, particularly important to whom plays fast-paced, competitive games.

Adaptive-Sync technology



Gaming shouldn't be a choice between choppy gameplay or broken frames. Get fluid, artifactfree performance at virtually any framerate with Adaptive-Sync technology, smooth quick refresh and ultra-fast response time.















VESA CERTIFIED DisplayHDR" 1000

Picture/Display

- Panel Size: 42.51 inch / 108 cm
- Aspect ratio: 16:9
- LCD panel type: MVA
- Backlight type: B-LED+QD Film
- Pixel pitch: 0.245 x 0.245 mm
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 720 cd/m² (typical), 1,000 cd/m² (peak) nit
- Display colors: 1.07 billion colors (10 bit*)
- Color gamut (typical): NTSC 119%*, sRGB 145%* • Color gamut (min.): BT. 709 Coverage: 100%*; DCI-P3 Coverage: 97.6%*
- Contrast ratio (typical): 4000:1
- SmartContrast: 50,000,000:1
- Response time (typical): 4 ms (Gray to Gray)*
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Picture enhancement: SmartImage
- Effective viewing area: 941.18 (H) x 529.42 (V)
- Scanning Frequency: 23 80 Hz (V) / 30 160 kHz (H)
- sRGB
- Flicker-free
- Pixel Density: 103.64 PPI
- LowBlue Mode
- Display Screen Coating: Anti-Glare, 3H, Haze 2%
- Adaptive sync
- HDR: DisplayHDR 1000 and UHDA certified

Connectivity

- Signal Input: HDMI 2.0 x 2, DisplayPort 1.4 x 1, mini DisplayPort 1.4 x 1, USB-C (DP Alt mode)
- USB: USB 3.0x2 (2 w/fast charging)³
- Sync Input: Separate Sync, Sync on Green
- Audio (In/Out): PC audio-in, Headphone out

Convenience

- Built-in Speakers: 7 W x 2 with DTS sound
- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7
- User convenience: Menu/OK, Input/Up, SmartImage Game/Return, Volume/Down, Power On/Off
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
- Other convenience: Ambiglow, Low Input Lag, Kensington lock, VESA mount (200x200mm)
- Control software: SmartControl
- · Remote control type: Philips RC6 remote control • MultiView: PIP/PBP mode, 2x devices

UPC: 6 09585 25164 9

Stand

• Tilt: -5/10 degree

Power

- Power supply: Internal, 100-240VAC, 50-60Hz
- Off mode: 0.5 W (typ.)
- On mode: 62.69 W (typ.) (EnergyStar 7.0 test method)
- Standby mode: 0.5 W (typ.)
- · Power LED indicator: Operation White, Standby mode- White (blinking)

Dimensions

- Product with stand (mm): 976 x 661 x 264 mm
- Product with stand in inch: 38.4 x 26.0 x 10.4 inch
- Packaging in mm (WxHxD): 1090 x 764 x 338 mm
- Product without stand (mm): 976 x 574 x 63 mm
- Packaging in inch (WxHxD): 42.9 x 30.1 x 13.3 inch
- Product without stand in inch: 38.4 x 22.6 x 2.5 inch

Weight

- Product with packaging (kg): 20.72 kg
- Product with stand (kg): 14.71 kg
- Product with packaging (lb): 45.58 lb
- Product with stand (lb): 32.36 lb
- Product without stand (kg): 13.96 kg
- Product without stand (lb): 30.71 lb

Operating conditions

- Altitude: Operation: +12,000ft (3,658m), Non-
- operation: +40,000ft (12,192m)
- Temperature range (operation): 0 to 40 $^\circ\text{C}$
- MTBF: 50,000 hrs (excluding backlight) hour(s) Relative humidity: 20%-80 %
- Temperature range (storage): -20 to 60 °C

Sustainability

- Environmental and energy: EnergyStar 7.0, RoHS, WEEE
- Recyclable packaging material: 100 %
- Specific Substances: Mercury free, PVC / BFR free housing

Compliance and standards

• Regulatory Approvals: CE Mark, FCC Class B, RCM, BSMI, CB, CECP, cETLus, China RoHS, EAC, E-standby, ICES-003, J-MOSS, KC, KCC, KUCAS, Kuwait, PSB, PSE, SASO, SEMKO, TUV/ISO9241-307, UKRAINIAN, VCCI

- Monitor with stand
- User Documentation
- Accessory: Remote control



Issue date 2024-03-14	© 2024 Koninklijke Philips N.V. All Rights reserved.	* Respo * For V
Version: 10.0.1	Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.	* For v suppo * Fast c * BT. 7(* The n * NTSC

www.philips.com

Cabinet

Color: Black

• Finish: Glossy / Textured

What's in the box?

- Cables: USB-C cable, USB-A to USB-C cable,
- HDMI cable, DP cable, Power cable

ponse time value equal to SmartResponse Video transmission via USB-C, your Notebook/device must

36M6VBPAB/27

- ort USB-C DP Alt mode
- charging complies with USB BC 1.2 standard 709 / DCI-P3 Coverage based on CIE1976
- e monitor may look different from feature images. SC Area based on CIE1976