

Philips Brilliance LED-backlit LCD monitor

**B Line** 27" (68.6 cm) Quad HD (2560 x 1440)

272B4QPJCB

# Crisp images, efficient performance

with PowerSensor saves energy

This Philips PowerSensor LED display with PVC and BFR free housing, USB hub and ergonomic base is ready for eco-friendly productivity

## **Brilliant performance**

- MultiView enables simultaneous dual connection and view
- Crystal clear images with Quad HD 2560 x 1440 pixels
- · Less eye fatigue with Flicker-Free technology
- IPS-AHVA wide-view technology for image and colour accuracy

## **Designed for people**

- · Low bezel-to-table height for maximum reading comfort
- SmartErgoBase enables user-friendly ergonomic adjustments
- Built-in stereo speakers for multimedia
- MHL technology for enjoying mobile content on a big screen
- SmartConnect with HDMI, Display port and Dual link DVI
- USB 3.0 Hub for convenient access and fast charging

### Sustainable Eco-design

• PowerSensor saves up to 80% energy costs



# Highlights

# **IPS-AHVA** display




IPS-AHVA displays use an advanced technology that gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS-AHVA displays give you remarkably crisp images with vivid colours, making them ideal not only for Photos, movies and web browsing, but also for professional applications that demand colour accuracy and consistent brightness at all times.

# **CrystalClear images**



These Philips screens deliver Crystal Clear, Quad HD 2560  $\times$  1440 or 2560  $\times$  1080 pixel images. Utilising high-performance panels with a high-density pixel count, enabled by high bandwidth sources like USB-C, Displayport and HDMI, these new displays will make your images and graphics come alive. Whether you are a demanding professional who requires extremely detailed information for CAD-CAM solutions and uses 3D graphic applications, or a financial wizard working on huge spreadsheets, Philips displays will give you Crystal Clear images.

#### MultiView technology



With the ultra-high resolution Philips MultiView display, you can now experience a world of connectivity. MultiView enables active dual connect and view so that you can work with multiple devices like a PC and notebook simultaneously, for complex multitasking.

#### Flicker-Free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-Free technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

# **S**mart**E**rgo**B**ase



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base can

swivel, tilt and rotate to various angles to ensure maximum comfort. The height-adjustable stand guarantees the optimal viewing level, reducing the physical strains of a long workday, while cable management reduces cable clutter and keeps the workspace neat and professional.

#### **Built-in stereo speakers**



A pair of high-quality stereo speakers built into a display device. They may be visible front firing, or invisible down firing, top firing, rear firing etc. depending on model and design.

#### **SmartConnect**

With a plethora of connectivity, these Philips displays come equipped with multi connections like Dual link DVI, Display Port and universal HDMI connector, enabling you to enjoy high-resolution uncompressed video and audio content. The USB 3.0 option ensures that you can have super-speed data transfers while having global connectivity. Regardless of what source you use, you can rest assured that this Philips display will ensure your investment is not made obsolete any time soon!

# **USB 3.0 Hub with FastCharge**

Super Speed USB 3.0 deploys 5.0 gbit/s transfer rate, which is about 10 times faster than USB 2.0 standard, significantly reducing data transfer time to save you time and money. With more bandwidth, super speed transfer rates, better power management and superior overall performance, USB 3.0 sets the latest global standard and allows you to use large capacity storage devices. Now you don't have to wait so long for devices to charge. New FastCharge enables quick charging to charge and go. USB 3.0 is also backward compatible with USB 2.0 devices.



















# **Specifications**

#### Connectivity

- Signal Input: DVI-D (digital, HDCP), VGA (Analogue), DisplayPort x 1, MHL-HDMI (digital,
- USB: USB 3.0x4 (1 w/fast charging)\*
- Sync Input: Separate Sync, Sync on Green
- · Audio (In/Out): PC audio-in, Headphone out

#### Picture/Display

- Panel Size: 27 inch/68.6 cm
- · Aspect ratio: 16:9
- LCD panel type: IPS-AHVA LCD
- · Backlight type: W-LED system
- Pixel pitch: 0.233 x 0.233 mm
- Optimum resolution: 2560 x 1440 @ 60Hz
- Brightness: 350 cd/m<sup>2</sup>
- Display colours: Colour support: True 8 bit
- · Contrast ratio (typical): 1000:1
- SmartContrast: 20,000,000:1
- Response time (typical): 4 ms (Grey to Grey)\*
  Viewing angle: 178° (H)/178° (V), @ C/R > 10
- Picture enhancement: SmartImage
- Effective viewing area: 596.7 (H) x 335.7 (V)
- Scanning Frequency: 30 83 kHz (H) / 56 76 Hz (V) • sRGB

#### **Convenience**

- Built-in Speakers: 2 W x 2
- $\bullet$  Plug and Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 8.1 / 8 / 7
- User convenience: SmartImage, Multi-view, User, Menu, Power On/Off
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
- Other convenience: Kensington lock, VESA mount  $(100 \times 100 \text{ mm})$
- Control software: PowerSensor, SmartControl

- · Height adjustment: 120 mm
- Pivot: 90 degree
- Swivel: -65/65 degree
- Tilt: -5/20 degree

# **Power**

• ECO mode: 25 W (typ.)

- Power supply: 100-240 VAC, 50-60 Hz, External
- Off mode: <0.3 W (typ.)
- On mode: 24.4 W (typ.) (EnergyStar 7.0 test method)
- Standby mode: <0.5 W (typ.)
- · Power LED indicator: Operation White, Standby mode - White (flashing)

#### **Dimensions**

- Product with stand (mm):  $639 \times 540 \times 244$  mm
- Packaging in mm (W x H x D): 740 x 490 x 299 mm
- Product without stand (mm): 639 x 405 x 68 mm

#### Weight

- Product with packaging (kg): 10.60 kg
- Product with stand (kg): 6.72 kg
- Product without stand (kg): 4.40 kg

#### **Operating conditions**

- Altitude: Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m)
- $\bullet$  Temperature range (operation): 0°C to 40°C °C
- Relative humidity: 20%-80% %
- Temperature range (storage): -20°C to 60°C °C
- MTBF (demonstrated): 70,000 hrs (excluded backlight)

### **Sustainability**

- · Environmental and energy: EnergyStar 7.0, PowerSensor, RoHS
- Post-consumer recycled plastic: 65%
- Recyclable packaging material: 100 %
- · Specific Substances: PVC/BFR free housing, Mercury free

#### Compliance and standards

• Regulatory Approvals: cETLus, CE Mark, FCC Class B, SEMKO, TUV Ergo, TUV/GS, WEEE, CU-EAC, TCO Certified

#### Cabinet

- · Finish: Texture
- Foot: Black
- Front bezel: Black
- Rear cover: Black

### What's in the box?

- · Cables: VGA, DVI, DP, Audio, Power
- · Monitor with stand
- User Documentation



Issue date 2024-03-24

EAN: 87 12581 72908 0

Version: 5.0.2

© 2024 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

- \* This Philips display is MHL-certified. However, if your MHL device does not connect or work correctly, check with your MHL device FAQ or vendor directly for instructions. The policy of your device manufacturer may require you to purchase its brand-specific MHL cable or adapter in order for it to work
- \* Standby/Off energy saving of ErP is not applicable for the MHL charging functionality
  \* Requires optional MHL-certified mobile device and MHL cable (not
- included). Please check with your MHL device vendor for compatibility.
- \* For a complete list of MHL-enabled products, refer to
- www.mhlconsortium.org

  \* Fast charging through BC 1.2 standard

  \* Response time value equal to SmartResponse